INNOVATOR IN ELECTRONICS

MURATA PRODUCTS
Lineup 2020

K70E.pdf
Dec.12,2019

2020 MURATA PRODUCTS Lineup

p2

Capacitors

Ceramic Capacitors, Polymer Aluminum Electrolytic Capacitors 4
Single-Layer Microchip Capacitors, Thin Film Circuit Substrates (RUSUB) 30
Variable Capacitors 34
Silicon Capacitors 34
Film Capacitors 40

p41

Noise Suppression Products/EMI Suppression Filters

Noise Suppression Filters (Chip Ferrite Bead)/(Frequency Specified Noise Filters) 41
Noise Suppression Filters (Feed Through Chip EMI Filters) 43
Noise Suppression Filters (Chip LC Filters) 43
Noise Suppression Filters (Chip EMIFIL) 44
Noise Suppression Filters (Chip Common Mode Choke Coils/Chip Common Mode Noise Filters) 45
Noise Suppression Filters (Block Type) 46
ESD Protection Devices 47
Noise Suppression Filters (Lead Type), Others 47

p48

Inductors (Coils)

Inductors for Power Lines 49
RF Inductors 56
General Circuit Inductors 59
Variable Inductors 60

p62

Resistors

High Voltage Resistors 62

p63

Timing Devices

MEMS Resonator 64
Crystal Units 64
Crystal Oscillators 65
Ceramic Resonators CERALOCK 65



p67

Filters

Ceramic Filters CERAFIL 67
Ceramic Discriminators 67
Crystal Filters 68
SAW Filters for Mobile Communications 68
Dielectric Filters GIGAFIL 69
Chip Multilayer LC Filters 69



p70

RF Components

Antennas 70
Baluns 71
Couplers 72
Chip Multilayer Hybrid Dividers 72
Chip Multilayer Diplexers 72
Microwave Coaxial Connectors 73

p76

Sensors

Pyroelectric Infrared Sensors 78
Ultrasonic Sensors 78
AMR Sensors (Magnetic Sensors) 78
Shock Sensors 78
Accelerometers 78
Inclinometers 78
Gyro Sensors 78
Temperature Sensors (Thermistors) 78

K70E.pdf
Dec.12,2019

Bluetooth is a registered trademark or trademark of Bluetooth SIG, Inc. in the United States and other countries.
Wi-Fi is a registered trademark or trademark of Wi-Fi Alliance in the United States and other countries.
HDMI is a trademark of HDMI LICENSING L.L.C.

p80

Thermistors

NTC Thermistors for Temperature Sensor/Temperature Compensation 80
PTC Thermistors POSISTOR for Overheat Sensing 82
PTC Thermistors POSISTOR for Inrush Current Suppression 83
PTC Thermistors POSISTOR for Overcurrent Protection 83

p85

Power Devices

DC-DC Converters 85
High Voltage Power Supplies 87
Switching Power Supplies 87

p88

Batteries

Laminated Type Lithium Ion Batteries 88
Cylindrical Type Lithium Ion Batteries 88
Li-ion Energy Storage System 88
Coin Manganese Dioxide Lithium Batteries 91
Silver Oxide Batteries 94
Alkaline Manganese Batteries 95



p96

Sound Components (Buzzer)

SMD Piezoelectric Sounders 96
Pin Type Piezoelectric Sounders 97
Piezoelectric Buzzers 97
Piezoelectric Diaphragms 97

p98

Others

Wireless Communication Modules 98
Micromechatronics 99
Ionizer Modules: Ionissimo 100
Ozonizer Modules: Ionissimo 101
RFID Devices 102
Femtet, CAE Software 103

Application Guides

AI speaker (Voice recognition) 105
Hearable 106
HEMS 108
Smartmeter 110
Thermostat 112
Human Detection 114
Air Dispenser 115
Blood Pressure Monitor 116
Thermometer 118
Blood Glucose Meter 119
Diagnostic Imaging Apparatus 120
Automotive
- Powertrain/Safety 122
- HEV/PHEV/EV 124
- Information/Comfort/Accessory 126

Bike/EV Bike 128
Smart Phones 130
Wearable Devices 132
Base Stations 134
G-PON 136
Lighting 137
Data Center 138
Industrial Automation 140
3D Printer 142
Electronic POS 144
Heavy Duty Vehicles 146
Security Camera 148
Entrance and Exit Management System 150
Air Conditioner 152
Refrigerator 154
Washing Machine 155
Air Purifier 156
Microwave Oven 157
IH Rice Cooker 158
Vacuum Cleaner 159
Tablet Terminators 160
Notebook Computers 162
MFP (Multi Function Printer/Product/Peripheral) 164
Televisions 166
Set-top Box 168

Design Support Tool SimSurfing 170
Index 171

Capacitors

The most comprehensive product lineup in the industry, providing ideal solutions, responding to all possible requirements.

Summary

Using Murata' s unique ceramic material technology, we offer a wide lineup of products. Murata also offers technical support that includes design kits and a comprehensive set of software tools to simulate virtually any circuit condition, satisfying the demands of many applications. We are also expanding our lineup of products that use non-ceramic dielectric materials, such as silicon capacitors, to support various applications.

Lineup

- ●Ceramic Capacitors (SMD, lead type)
- ●Polymer Aluminum Electrolytic Capacitors
- ●Single-Layer Microchip Capacitors
- ●Thin Film Circuit Substrates (RUSUB) ●Variable Capacitors
- ●Silicon Capacitors ●Film Capacitors

https://www.murata.com/en-global/products/capacitor

Ceramic Capacitors

p4

Murata offers the No. 1 most abundant lineup in the industry, responding to all possible needs, and proposing ideal solutions.

Polymer Aluminum Electrolytic Capacitors

These are high-capacity capacitors that are characterized by a low profile and low ESR.
They handle the stabilization of voltage in circuits where serious voltage control is demanded, and contribute to the advanced features in customer products.



Single-Layer Microchip Capacitors

p30

Simple single-layer structure provides very reliable performance and excellent frequency characteristics. A wide selection of sizes from 0.25mm square enables the miniaturization of the circuit and higher density.

Thin Film Circuit Substrates (RUSUB)

RUSUB technology combines capacitor and thin film resistor in one chip.
Custom specifications (dimensions, capacitance values, etc.) are also available upon request.



Variable Capacitors

p34

Variable capacitors can carry out the variable of the capacitor by adjusting the tuning voltage.
They are designed for frequency matching use for HF band (13.56MHz).



Silicon Capacitors

p34

Murata High-Density Silicon Capacitors are based on a MOS Semiconductor technology and utilize a 3D structure that substantially increases their performance and enables compact design. Silicon Capacitors offer small size and low thickness, superior reliability, and stability over high temperatures and high frequencies. They are the ideal choice for all demanding markets, such as Networking (RF Power and Broadband), Medical (Implantable devices), Automotive, or High-Reliability applications. Murata can provide customized Silicon Capacitors or Integrated Passive Devices (IPDs) to optimize your design.

Film Capacitors

p40

The FH series uses materials with high heat resistance. Therefore, it has a higher allowable ripple current under a higher temperature environment than conventional PP film capacitors.
This feature is more prominent in the high-frequency range. For example, when the ambient temperature is at 105°C, the PP film capacitors would be already at its limit for allowable ripple current, but because of the higher heat resistance of the FH series, the allowable ripple current can be increased drastically.

Ceramic Capacitors, Polymer Aluminum Electrolytic Capacitors

Icons

General	For applications that do not require a particular reliability, such as general equipment.
Info-tainment	Infotainment for Automotive Products for entertainment equipment like car navigation, car audio, and body control equipment like wipers and power windows.
Power-train	Powertrain/Safety for Automotive Products used for applications (running, turning, stopping, and safety devices) that particularly concern human life, such as in devices for automotive.
Medical Device	Medical-grade products for Implanted Medical Devices These products are intended for use in implanted medical devices such as cardiac pacemakers, cochlear implants, insulin pumps, and gastric electrostimulators. They are suitable for use in non-critical circuits.*1 *1 Non-critical circuits This term refers to circuits in implanted medical devices that are not directly linked to life support, i.e., circuits that will not directly endanger the life of the patient should the functionality of the device be reduced or halted by failure of the circuit.
AEC-Q200	AEC-Q200 compliant product
Safety standard	Products that acquired safety standard certification IEC60384-14.
Japanese Safety Law	Products that are based on the Electrical Appliance and Material Safety Law of Japan.
High Q	Low dissipation for high frequency By devising ceramic materials and electrode materials, low dissipation is achieved in frequency bands of VHF, UHF, and microwave or beyond.
Low ESL	Low inductance This capacitor is designed so that the parasitic inductance component (ESL) that the capacitor has on the high frequency side becomes lower.
Fail safe	Fail safe product This capacitor is designed to prevent failures as much as possible by short mode.
Deflecting crack	Product resistant to deflection cracking This capacitor is designed to prevent failures as much as possible by short mode caused by cracking when there is board deflection.
Soldering crack	Product with solder cracking suppression This capacitor is configured with metal terminals and leads connected to the chip. The metal terminals and leads relieve the stress from expansion and contraction of the solder, to suppress solder cracking.
Anti-noise	Product suitable for acoustic noise reduction and low distortion This product suppresses acoustic noise, which occurs when a ceramic capacitor is used, by devising the materials and configuration.
Effective Cap	No DC bias characteristics Polymer capacitor is no capacitance change with DC bias due to aluminum oxidized film for dielectric.
EMI Filter	Low-inductance product suitable for noise suppression This product has extremely low ESL and is suitable for suppression of noise, including high frequencies.
Bonding	Product for bonding Since gold is used for the external electrodes, the capacitor can be mounted by die bonding/wire bonding.
Limited to conductive glue mounting	Limited to Conductive Glue Mounting Since silver palladium is used for the external electrodes, the capacitor can be mounted by conductive adhesive.

Product Lineup

For general

General

SMD

Solder mounting

Chip type

GRM			p6
GRM		For LCD backlight inverter circuit only	p8
GR3	Anti-noise	High effective capacitance & high ripple current	p8
GRJ	Deflecting crack	Soft termination	p8
GR4		For information devices only	p9
GR7		For camera flash circuit only	WEB
GJM	High Q		p9
GQM	High Q	High power	p9
GA2	Japanese Safety Law	Based on the Electrical Appliance and Material Safety Law of Japan	p10
GA3	Safety standard		p10
LLL	Low ESL	LW reversed	p11
LLA	Low ESL	8 terminals	p11
LLM	Low ESL	10 terminals	p12
LLR	Low ESL	LW reversed controlled ESR	p12
NFM	Low ESL, EMI Filter	3 terminals	p12
GJ4	Anti-noise	Low distortion	WEB

On interposer board

ZRA	Anti-noise		WEB
ZRB	Anti-noise		WEB

Metal terminal type

KRM	Anti-noise, Deflecting crack, Soldering crack		p13
KR3	Anti-noise, Deflecting crack, Soldering crack	High effective capacitance & high ripple current	p13

Resin molding SMD type

DK1	Safety standard		p28

Polymer Aluminum Electrolytic Capacitors

ECAS	Anti-noise, Deflecting crack, Effective Cap		p29
ECNS	Anti-noise, Deflecting crack, Effective Cap		p29

Wire bonding mounting

Bonding

Chip type

GMA		Microchip	p13
GMD			p14

Lead type

Solder mounting

RDE	Anti-noise, Deflecting crack, Soldering crack		p22
DE1	Safety standard	X1/Y1 Class certified product	p24
DE2	Safety standard	X1/Y2 Class certified product	p25

Infotainment for automotive

Info-tainment, AEC-Q200

SMD

Solder mounting

Chip type

GRT			p14

Powertrain/Safety for automotive

Power-train, AEC-Q200

SMD

Solder mounting

Chip type

GCM			p15
GC3	Anti-noise	High effective capacitance & high ripple current	p17
GCJ	Fail safe, Deflecting crack	Soft termination	p17
GCQ	High Q		p18
GCD	Fail safe, Deflecting crack	MLSC design	p18
GCE	Fail safe, Deflecting crack	Soft termination MLSC design	p18
NFM	Low ESL, EMI Filter	3 terminals	p19

Metal terminal type

KCM	Anti-noise, Deflecting crack, Soldering crack		p19
KC3	Anti-noise, Deflecting crack, Soldering crack	High effective capacitance & high ripple current	p19
KCA	Safety standard, Anti-noise, Deflecting crack, Soldering crack		p20

Limited to Conductive Glue Mounting

Limited to conductive glue mounting

Chip type

GCB	Deflecting crack, Soldering crack	Ni plating + Pd plating termination conductive glue mounting	WEB
GCG	Deflecting crack, Soldering crack	AgPd termination conductive glue mounting	p20

Lead type

Solder mounting

RCE	Anti-noise, Deflecting crack, Soldering crack		p26
RHE	Anti-noise, Deflecting crack, Soldering crack	150°C operation leaded	p27
RHS	Anti-noise, Deflecting crack, Soldering crack	200°C operation leaded	p28
DE6	Safety standard		p28

Medical-grade products for implanted medical devices

Medical Device

SMD

Solder mounting

Chip type

GCH			p21

Ceramic capacitors SMD type For General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose

GRM

General

Temperature Compensating Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F)
GRM01	0.25X0.125 <008004>	25	0.20pF – 100pF
		16	0.20pF – 100pF
GRM02	0.4X0.2 <01005>	50	0.20pF – 100pF
		25	120pF – 220pF
		16	120pF – 220pF
GRM03	0.6X0.3 <0201>	100	0.10pF – 100pF
		50	0.10pF – 220pF
		25	270pF – 1000pF
GRM15	1.0X0.5 <0402>	100	150pF – 1000pF
		50	270pF – 6800pF
		35	10000pF
		25	10000pF
		10	2700pF – 4700pF
GRM18	1.6X0.8 <0603>	250	10pF – 47pF
		100	1000pF – 3900pF
		50	1000pF – 10000pF
		10	5600pF – 22000pF
GRM21	2.0X1.25 <0805>	630	10pF – 2200pF
		250	10pF – 10000pF
		200	10pF – 4700pF
		100	1000pF – 22000pF
		50	2700pF – 47000pF
		10	56000pF – 0.10μF
GRM31	3.2X1.6 <1206>	2000	10pF – 68pF
		1000	10pF – 1000pF
		630	10pF – 4700pF
		500	10pF – 4700pF
		250	6800pF – 22000pF
		200	6800pF – 10000pF
		100	4700pF – 0.10μF
		50	12000pF – 0.22μF
GRM32	3.2X2.5 <1210>	2000	100pF – 220pF
		1000	1500pF – 2200pF
		630	1500pF – 15000pF
		500	1500pF – 10000pF
GRM42	4.5X2.0 <1808>	3150	10pF – 100pF
GRM43	4.5X3.2 <1812>	1000	3300pF – 4700pF
		630	15000pF – 22000pF
		500	15000pF – 22000pF
GRM55	5.7X5.0 <2220>	1000	6800pF – 10000pF
		630	33000pF – 47000pF
		500	33000pF – 47000pF



Continued on the following page.↗

High Dielectric Constant Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GRM01	0.25X0.125 <008004>	10	100pF – 470pF
		6.3	1000pF – 10000pF
GRM02	0.4X0.2 <01005>	16	100pF – 10000pF
		10	100pF – 10000pF
		6.3	1000pF – 0.10μF
		4	15000pF – 0.10μF
		2.5	0.10μF
GRM03	0.6X0.3 <0201>	50	100pF – 1500pF
		35	0.10μF
		25	100pF – 0.22μF
		16	2200pF – 0.22μF
		10	4700pF – 1.0μF
		6.3	4700pF – 1.0μF
		4	0.22μF – 1.0μF
		2.5	1.0μF
GRM15	1.0X0.5 <0402>	100	220pF – 4700pF
		50	2200pF – 0.47μF
		35	0.22μF – 1.0μF
		25	22000pF – 2.2μF
		16	0.22μF – 2.2μF
		10	0.22μF – 4.7μF
		6.3	1.0μF – 10μF
		4	1.0μF – 10μF
		2.5	4.7μF – 10μF
GRM18	1.6X0.8 <0603>	50	2.2μF
		35	2.2μF – 4.7μF
		25	2.2μF – 10μF
		16	2.2μF – 10μF
		10	2.2μF – 10μF
		6.3	4.7μF – 22μF
		4	10μF – 22μF
GRM21	2.0X1.25 <0805>	100	1.0μF
		50	4.7μF
		35	4.7μF – 10μF
		25	2.2μF – 22μF
		16	4.7μF – 22μF
		10	22μF – 47μF
		6.3	22μF – 100μF
		4	22μF – 100μF
		2.5	47μF – 100μF
GRM31	3.2X1.6 <1206>	50	4.7μF
		25	10μF – 22μF
		16	22μF – 47μF
		10	22μF – 100μF
		6.3	22μF – 220μF
		4	47μF – 220μF
		2.5	220μF
GRM32	3.2X2.5 <1210>	100	10μF
		25	22μF
		16	22μF – 47μF
		10	47μF – 100μF
		6.3	47μF – 220μF
		4	100μF – 220μF
GRM43	4.5X3.2 <1812>	1000	33000pF – 47000pF
		630	68000pF – 0.10μF

Continued on the following page.↗

Ceramic Capacitor, Polymer Aluminum Electrolytic Capacitors

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F)										
			0.1p	1p	10p	100p	1000p	10000p	0.1μ	1μ	10μ	100μ	1000μ
GRM43	4.5X3.2 <1812>	500							0.15μF – 0.22μF				
		250							0.15μF – 0.47μF				
GRM55	5.7X5.0 <2220>	1000						68000pF – 0.10μF					
		630							0.15μF – 0.22μF				
		500							0.33μF – 0.47μF				
		250							0.33μF – 1.0μF				
		200							0.33μF – 1.0μF				

Chip Multilayer Ceramic Capacitors for LCD Backlight Inverter Circuit only

GRM

General

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F)										
			0.1p	1p	10p	100p	1000p	10000p	0.1μ	1μ	10μ	100μ	1000μ
GRM42	4.5X2.0 <1808>	3150			5.0pF – 47pF								

High Effective Capacitance & High Ripple Current Chip Multilayer Ceramic Capacitors for General Purpose

GR3

General Anti-noise

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F)										
			0.1p	1p	10p	100p	1000p	10000p	0.1μ	1μ	10μ	100μ	1000μ
GR321	2.0X1.25 <0805>	250					10000pF – 22000pF						
GR331	3.2X1.6 <1206>	630					10000pF – 15000pF						
		450					10000pF – 47000pF						
		250					33000pF – 68000pF						
GR332	3.2X2.5 <1210>	630					22000pF – 47000pF						
		450						68000pF – 0.10μF					
		250						0.10μF – 0.15μF					
GR343	4.5X3.2 <1812>	630							68000pF				
		450							0.15μF				
		250							0.22μF – 0.33μF				
GR355	5.7X5.0 <2220>	630							0.10μF – 0.22μF				
		450							0.22μF – 0.47μF				
		250							0.47μF – 1.0μF				

Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose

GRJ

General Deflecting crack

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F)										
			0.1p	1p	10p	100p	1000p	10000p	0.1μ	1μ	10μ	100μ	1000μ
GRJ21	2.0X1.25 <0805>	100								1.0μF			
		25									10μF		
GRJ31	3.2X1.6 <1206>	50									4.7μF		
GRJ32	3.2X2.5 <1210>	25									22μF		
		10									47μF		
GRJ43	4.5X3.2 <1812>	1000						33000pF – 47000pF					
		630						68000pF – 0.10μF					

Continued on the following page. ↗

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GRJ43	4.5X3.2 <1812>	250	0.15μF – 0.47μF
GRJ55	5.7X5.0 <2220>	1000	68000pF – 0.10μF
		630	0.15μF – 0.22μF
		250	0.33μF – 1.0μF

Chip Multilayer Ceramic Capacitors for Ethernet LAN and primary-secondary coupling of DC-DC converters

GR4

General

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GR442	4.5X2.0 <1808>	2000	220pF – 1500pF
GR443	4.5X3.2 <1812>	2000	1800pF – 4700pF
GR455	5.7X5.0 <2220>	2000	10000pF

Chip Multilayer Ceramic Capacitors for Splitter Circuit of G-Fast, xDSL

GR4

General

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GR431	3.2X1.6 <1206>	630	1000pF – 4700pF
GR432	3.2X2.5 <1210>	630	6800pF – 15000pF

High Q Chip Multilayer Ceramic Capacitors for General Purpose

GJM

General High Q

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GJM02	0.4X0.2 <01005>	25	0.20pF – 22pF
GJM03	0.6X0.3 <0201>	100	0.30pF – 15pF
		50	0.20pF – 0.90pF
		25	1.0pF – 33pF
GJM15	1.0X0.5 <0402>	50	0.10pF – 47pF

High Q and High Power Chip Multilayer Ceramic Capacitors for General Purpose

GQM

General High Q

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GQM15	1.0X0.5 <0402>	200	0.10pF – 33pF
		100	36pF – 47pF
GQM18	1.6X0.8 <0603>	250	1.0pF – 47pF
GQM21	2.0X1.25 <0805>	500	1.0pF – 22pF
		250	1.0pF – 100pF
GQM22	2.8X2.8 <1111>	500	1.0pF – 100pF

Continued on the following page.↗

Ceramic Capacitor, Polymer Aluminum Electrolytic Capacitors

Based on the Electrical Appliance and Material Safety Law of Japan Chip Multilayer Ceramic Capacitors for General Purpose

GA2

General | Japanese Safety Law

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (V)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GA242	4.5X2.0 <1808>	AC250 (r.m.s.)	470pF – 1000pF
GA243	4.5X3.2 <1812>	AC250 (r.m.s.)	2200pF – 47000pF
GA255	5.7X5.0 <2220>	AC250 (r.m.s.)	0.10μF

Safety Standard Certified Chip Multilayer Ceramic Capacitors for General Purpose Type GB IEC60384-14 Class X2

GA3 Type GB

General | Safety standard

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (V)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GA355	5.7X5.0 <2220>	AC250 (r.m.s.)	10000pF – 56000pF

Safety Standard Certified Chip Multilayer Ceramic Capacitors for General Purpose Type GD Acquired certifications of UL60950-1

GA3 Type GD

General | Safety standard

Temperature Compensating Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (V)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GA342	4.5X2.0 <1808>	AC250 (r.m.s.)	10pF – 82pF

High Dielectric Constant Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (V)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GA342	4.5X2.0 <1808>	AC250 (r.m.s.)	100pF – 1500pF
GA343	4.5X3.2 <1812>	AC250 (r.m.s.)	1800pF – 4700pF

Safety Standard Certified Chip Multilayer Ceramic Capacitors for General Purpose Type GF Acquired certifications of IEC60384-14 Class X1/Y2 and UL60950-1

GA3 Type GF

General | Safety standard

Temperature Compensating Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (V)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GA342	4.5X2.0 <1808>	AC250 (r.m.s.)	10pF – 82pF

Continued on the following page.↗

High Dielectric Constant Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (V)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GA342	4.5X2.0 <1808>	AC250 (r.m.s.)	100pF – 1000pF
GA352	5.7X2.8 <2211>	AC250 (r.m.s.)	100pF – 1500pF
GA355	5.7X5.0 <2220>	AC250 (r.m.s.)	1800pF – 4700pF

LW Reversed Low ESL Chip Multilayer Ceramic Capacitors for General Purpose

LLL

General Low ESL

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
LLL15	0.5X1.0 <0204>	6.3	0.10μF – 0.22μF
		4	0.47μF – 1.0μF
LLL1U	0.6X1.0 <02404>	4	4.3μF
LLL18	0.8X1.6 <0306>	50	2200pF – 4700pF
		25	10000pF – 22000pF
		16	22000pF – 47000pF
		10	0.10μF – 0.22μF
		4	0.22μF – 2.2μF
LLL21	1.25X2.0 <0508>	50	10000pF – 22000pF
		25	22000pF – 0.10μF
		16	47000pF – 0.22μF
		10	0.22μF – 1.0μF
		6.3	0.47μF
		4	1.0μF – 2.2μF
LLL31	1.6X3.2 <0612>	50	10000pF – 0.10μF
		25	47000pF – 0.47μF
		16	0.22μF – 1.0μF
		10	0.47μF – 2.2μF
		6.3	2.2μF – 10μF

8 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose

LLA

General Low ESL

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
LLA18	1.6X0.8 <0603>	4	0.10μF – 2.2μF
LLA21	2.0X1.25 <0805>	25	10000pF – 47000pF
		16	47000pF – 0.22μF
		10	0.22μF – 0.47μF
		6.3	0.47μF – 1.0μF
		4	1.0μF – 4.7μF

Continued on the following page.↗

10 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose

LLM

General | Low ESL

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
LLM21	2.0X1.25 <0805>	25	10000pF – 22000pF
		16	47000pF – 0.10μF
		6.3	0.22μF – 0.47μF
		4	1.0μF

LW Reversed Controlled ESR Low ESL Chip Multilayer Ceramic Capacitors for General Purpose

LLR

General | Low ESL

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	ESR (mΩ) 100	220	470	1000	Capacitance Range
LLR18	0.8X1.6 <0306>	4					1.0μF

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose

NFM

General | Low ESL | EMI Filter

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
NFM15	1.0X0.5 <0402>	16	2200pF – 47000pF
		10	2200pF – 0.22μF
		6.3	0.10μF – 0.47μF
		4	0.47μF – 1.0μF
		2.5	4.3μF – 9.1μF
NFM18	1.6X0.8 <0603>	16	100pF – 0.10μF
		10	2.2μF
		6.3	0.22μF – 2.2μF
NFM21	2.0X1.25 <0805>	50	220pF – 22000pF
		25	0.10μF
		16	0.22μF – 1.0μF
		10	1.0μF – 4.7μF
		6.3	2.2μF – 10μF
NFM3D	3.2X1.25 <1205>	50	220pF – 22000pF
NFM31	3.2X1.6 <1206>	100	10000pF – 0.10μF
		50	10000pF – 0.10μF
		6.3	27μF
NFM41	4.5X1.6 <1806>	100	470pF – 22000pF
		50	1.5μF
		25	1.5μF

Continued on the following page.↗

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose



KRM

General | Deflecting crack | Soldering crack | Anti-noise

Temperature Compensating Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
KRM55	6.1X5.1	630	15000pF – 54000pF

High Dielectric Constant Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
KRM21	2.2X1.25	25	10μF – 22μF
		16	10μF
KRM31	3.5X1.7	100	1.0μF
		50	4.7μF
		35	10μF
		25	10μF
	3.6X1.7	50	2.2μF
	3.7X1.85	100	2.2μF
KRM55	6.1X5.3	1000	68000pF – 0.22μF
		630	0.15μF – 0.47μF
		450	0.33μF – 1.0μF
		250	0.68μF – 2.2μF
		100	4.7μF – 22μF
		63	4.7μF – 22μF
		50	4.7μF – 33μF
		35	10μF – 47μF
		25	15μF – 100μF

High Effective Capacitance & High Allowable Ripple Current Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose



KR3

General | Deflecting crack | Soldering crack | Anti-noise

Series	LXW (mm)	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
KR355	6.1X5.3	630	0.10μF – 0.56μF
		450	0.22μF – 1.2μF
		250	0.47μF – 2.2μF

Wire Bonding Mount Multilayer Microchip Capacitors for General Purpose

GMA

General | Bonding

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GMA0D	0.38X0.38 <015015>	10	1000pF – 10000pF
GMA05	0.5X0.5 <0202>	100	100pF – 1000pF
		25	1500pF – 4700pF
		10	6800pF – 22000pF

Continued on the following page.↗

Ceramic Capacitor, Polymer Aluminum Electrolytic Capacitors

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GMA05	0.5X0.5 <0202>	6.3	0.10μF
GMA08	0.8X0.8 <0303>	100	1500pF 6800pF
		25	10000pF 22000pF
		10	33000pF 0.10μF
		6.3	0.47μF

Wire Bonding/AuSn Soldering Mount Chip Multilayer Ceramic Capacitors for General Purpose

GMD

General Bonding

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GMD03	0.6X0.3 <0201>	25	100pF 1500pF
		16	1800pF 3300pF
		10	3900pF 10000pF
		6.3	56000pF 0.10μF
GMD15	1.0X0.5 <0402>	50	220pF 4700pF
		25	5600pF 47000pF
		16	56000pF 0.10μF
		10	0.12μF 0.47μF

Ceramic capacitors SMD type For Automotive

AEC-Q200 Compliant Chip Multilayer Ceramic Capacitors for Infotainment

GRT

Info-tainment AEC-Q200

Temperature Compensating Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GRT03	0.6X0.3 <0201>	100	1.0pF 100pF
		50	1.0pF 220pF
		25	1.0pF 1000pF
GRT15	1.0X0.5 <0402>	100	1.0pF 100pF
		50	1.0pF 1000pF
		25	10pF 1000pF
GRT18	1.6X0.8 <0603>	100	120pF 1500pF
		50	1200pF 10000pF
		25	1200pF 10000pF
GRT21	2.0X1.25 <0805>	100	1800pF 3300pF
		50	18000pF 22000pF
		25	1800pF 2200pF
GRT31	3.2X1.6 <1206>	100	3900pF 22000pF
		50	56000pF 0.10μF
		25	0.10μF 0.12μF
		16	0.12μF

Continued on the following page.↗

High Dielectric Constant Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GRT03	0.6X0.3 <0201>	35	0.10μF
		25	100pF – 0.10μF
		16	10000pF – 0.10μF
		10	1500pF – 1.0μF
		6.3	2200pF – 1.0μF
		4	68000pF – 1.0μF
		2.5	1.0μF
GRT15	1.0X0.5 <0402>	50	220pF – 0.10μF
		35	0.22μF – 1.0μF
		25	10000pF – 2.2μF
		16	10000pF – 2.2μF
		10	0.22μF – 4.7μF
		6.3	22000pF – 4.7μF
		4	1.0μF – 4.7μF
		2.5	10μF
GRT18	1.6X0.8 <0603>	100	3300pF – 10000pF
		50	1.0μF – 2.2μF
		35	1.0μF – 4.7μF
		25	0.15μF – 10μF
		16	0.33μF – 10μF
		10	10μF – 22μF
		6.3	10μF – 22μF
		4	1.0μF – 22μF
		2.5	22μF
GRT21	2.0X1.25 <0805>	100	47000pF
		50	0.47μF – 4.7μF
		35	4.7μF
		25	2.2μF – 22μF
		16	2.2μF – 22μF
		10	3.3μF – 22μF
		6.3	3.3μF – 47μF
		4	47μF
GRT31	3.2X1.6 <1206>	50	1.0μF – 10μF
		35	10μF
		25	1.5μF – 10μF
		16	1.5μF – 22μF
		10	47μF
		6.3	15μF – 47μF
GRT32	3.2X2.5 <1210>	50	3.3μF – 4.7μF
		25	6.8μF
		16	47μF
		10	47μF
		6.3	33μF – 100μF

Chip Multilayer Ceramic Capacitors for Automotive

GCM

Temperature Compensating Type

Power-train AEC-Q200

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GCM03	0.6X0.3 <0201>	50	1.0pF – 100pF
		25	1.0pF – 100pF
GCM15	1.0X0.5 <0402>	50	1.0pF – 1000pF
GCM18	1.6X0.8 <0603>	100	1.0pF – 10000pF

Continued on the following page.↗

Ceramic Capacitor, Polymer Aluminum Electrolytic Capacitors

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GCM18	1.6X0.8 <0603>	80	1800pF – 3900pF
		50	1000pF – 10000pF
GCM21	2.0X1.25 <0805>	630	10pF – 2200pF
		250	10pF – 10000pF
		100	1000pF – 3300pF
		80	4700pF – 22000pF
		50	12000pF – 22000pF
GCM31	3.2X1.6 <1206>	1000	10pF – 1000pF
		630	10pF – 4700pF
		250	6800pF – 22000pF
		100	3900pF – 0.10μF
		80	27000pF – 33000pF
		50	68000pF – 0.10μF
GCM32	3.2X2.5 <1210>	1000	1500pF – 2200pF
		630	1500pF – 10000pF
GCM43	4.5X3.2 <1812>	1000	3300pF – 4700pF
		630	15000pF – 22000pF
GCM55	5.7X5.0 <2220>	1000	6800pF – 10000pF
		630	33000pF – 47000pF

High Dielectric Constant Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GCM03	0.6X0.3 <0201>	25	100pF – 3300pF
		16	330pF – 3300pF
		10	4700pF – 10000pF
GCM15	1.0X0.5 <0402>	100	220pF – 4700pF
		50	220pF – 0.10μF
		25	10000pF – 0.10μF
		16	33000pF – 0.22μF
		10	0.47μF – 1.0μF
GCM18	1.6X0.8 <0603>	100	6800pF – 22000pF
		50	0.22μF
		25	0.22μF – 1.0μF
		16	0.33μF – 1.0μF
		6.3	2.2μF – 10μF
		4	10μF
GCM21	2.0X1.25 <0805>	100	33000pF – 1.0μF
		50	0.22μF – 1.0μF
		35	0.68μF – 4.7μF
		25	0.33μF – 4.7μF
		16	1.0μF – 10μF
		10	2.2μF – 10μF
		6.3	10μF
GCM31	3.2X1.6 <1206>	100	0.22μF – 2.2μF
		50	1.0μF – 4.7μF
		25	1.0μF – 10μF
		16	4.7μF – 10μF
		10	22μF
		6.3	22μF
GCM32	3.2X2.5 <1210>	100	4.7μF
		50	4.7μF – 10μF
		35	10μF
		25	10μF – 22μF
		16	22μF
		10	22μF – 47μF
		6.3	47μF

Continued on the following page.↗

High Effective Capacitance & High Ripple Current Chip Multilayer Ceramic Capacitors for Automotive

GC3

Power-train | AEC-Q200 | Anti-noise

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) (0.1p, 1p, 10p, 100p, 1000p, 10000p, 0.1μ, 1μ, 10μ, 100μ, 1000μ)
GC321	2.0X1.25 <0805>	250	10000pF – 22000pF
GC331	3.2X1.6 <1206>	630	10000pF – 15000pF
		450	10000pF – 47000pF
		250	33000pF – 68000pF
GC332	3.2X2.5 <1210>	630	22000pF – 47000pF
		450	68000pF – 0.10μF
		250	0.10μF – 0.15μF
GC343	4.5X3.2 <1812>	630	68000pF
		450	0.15μF
		250	0.22μF – 0.33μF
GC355	5.7X5.0 <2220>	630	0.10μF – 0.22μF
		450	0.22μF – 0.47μF
		250	0.47μF – 1.0μF

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive

GCJ

Power-train | AEC-Q200 | Fail safe | Deflecting crack

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) (0.1p, 1p, 10p, 100p, 1000p, 10000p, 0.1μ, 1μ, 10μ, 100μ, 1000μ)
GCJ18	1.6X0.8 <0603>	100	1000pF – 0.10μF
		50	1000pF – 0.22μF
		35	33000pF – 68000pF
		25	1000pF – 1.0μF
		16	27000pF – 0.47μF
		10	0.22μF
		6.3	2.2μF – 4.7μF
GCJ21	2.0X1.25 <0805>	250	1000pF – 22000pF
		100	27000pF – 1.0μF
		50	82000pF – 1.0μF
		35	0.12μF – 0.47μF
		25	0.12μF – 2.2μF
		16	0.27μF – 4.7μF
		10	2.2μF – 10μF
GCJ31	3.2X1.6 <1206>	1000	1000pF – 10000pF
		630	1000pF – 22000pF
		250	15000pF – 0.10μF
		100	0.15μF – 2.2μF
		50	0.47μF – 4.7μF
		35	0.56μF – 1.0μF
		25	2.2μF – 10μF
		16	3.3μF – 10μF
		10	6.8μF – 22μF
		6.3	22μF
GCJ32	3.2X2.5 <1210>	1000	15000pF – 22000pF
		630	6800pF – 47000pF
		250	68000pF – 0.22μF
		100	2.2μF – 4.7μF

Continued on the following page.↗

Ceramic Capacitor, Polymer Aluminum Electrolytic Capacitors

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GCJ32	3.2X2.5 <1210>	50	4.7μF – 10μF
		25	4.7μF – 22μF
		16	6.8μF – 22μF
		6.3	47μF
GCJ43	4.5X3.2 <1812>	1000	33000pF – 47000pF
		630	33000pF – 0.10μF
		250	0.15μF – 0.47μF
GCJ55	5.7X5.0 <2220>	1000	68000pF – 0.10μF
		630	0.10μF – 0.22μF
		250	0.33μF – 1.0μF

High Q Chip Multilayer Ceramic Capacitors for Automotive

GCQ

Power-train | AEC-Q200 | High Q

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GCQ15	1.0X0.5 <0402>	50	0.10pF – 47pF

MLSC Design Chip Multilayer Ceramic Capacitors for Automotive

GCD

Power-train | AEC-Q200 | Fail safe | Deflecting crack

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GCD18	1.6X0.8 <0603>	100	1000pF – 22000pF
		50	1000pF – 22000pF
		25	27000pF – 47000pF
GCD21	2.0X1.25 <0805>	100	27000pF – 0.10μF
		50	27000pF – 0.10μF
		16	0.47μF

Soft Termination MLSC Design Chip Multilayer Ceramic Capacitors for Automotive

GCE

Power-train | AEC-Q200 | Fail safe | Deflecting crack

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
GCE18	1.6X0.8 <0603>	100	1000pF – 22000pF
		50	1000pF – 22000pF
		25	27000pF – 47000pF
GCE21	2.0X1.25 <0805>	100	27000pF – 0.10μF
		50	27000pF – 0.10μF

Continued on the following page. ↗

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for Automotive

NFM

Power-train | AEC-Q200 | Low ESL | EMI Filter

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
NFM18	1.6X0.8 <0603>	16	1.0μF
		6.3	1.0μF
NFM21	2.0X1.25 <0805>	50	220pF – 22000pF
		16	1.0μF
		10	0.10μF – 0.47μF
NFM31	3.2X1.6 <1206>	100	10000pF
		50	10000pF – 0.10μF

Metal Terminal Type Multilayer Ceramic Capacitors for Automotive

KCM

Power-train | AEC-Q200 | Deflecting crack | Soldering crack | Anti-noise

Temperature Compensating Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
KCM55	6.1X5.1	630	15000pF – 54000pF

High Dielectric Constant Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
KCM55	6.1X5.3	100	4.7μF – 22μF
		63	4.7μF – 22μF
		50	4.7μF – 33μF
		35	10μF – 47μF
		25	15μF – 100μF

High Effective Capacitance & High Allowable Ripple Current Metal Terminal Type Multilayer Ceramic Capacitors for Automotive



KC3

Power-train | AEC-Q200 | Deflecting crack | Soldering crack | Anti-noise

Series	LXW (mm)	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
KC355	6.1X5.3	630	0.10μF – 1.2μF
		450	0.22μF – 2.2μF
		250	0.47μF – 2.2μF

Continued on the following page. ↗

Safety Standard Certified Metal Terminal Type Multilayer Ceramic Capacitors for Automotive

KCA

Power-train | AEC-Q200 | Safety standard | Deflecting crack | Soldering crack | Anti-noise

Series	LXW (mm)	Rated Voltage (V)	Capacitance Range (F) (0.1p, 1p, 10p, 100p, 1000p, 10000p, 0.1μ, 1μ, 10μ, 100μ, 1000μ)
KCA55	6.1X5.1	AC250 (r.m.s.)	100pF – 10000pF

AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive

GCG

Power-train | AEC-Q200 | Deflecting crack | Soldering crack | Limited to conductive glue mounting

Temperature Compensating Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) (0.1p, 1p, 10p, 100p, 1000p, 10000p, 0.1μ, 1μ, 10μ, 100μ, 1000μ)
GCG15	1.0X0.5 <0402>	50	120pF – 470pF
GCG18	1.6X0.8 <0603>	100	10pF – 10000pF
		50	10pF – 2200pF
GCG21	2.0X1.25 <0805>	50	1000pF – 10000pF

High Dielectric Constant Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F) (0.1p, 1p, 10p, 100p, 1000p, 10000p, 0.1μ, 1μ, 10μ, 100μ, 1000μ)
GCG15	1.0X0.5 <0402>	50	220pF – 4700pF
		25	5600pF – 10000pF
		16	15000pF – 0.10μF
GCG18	1.6X0.8 <0603>	100	1000pF – 0.10μF
		50	1200pF – 0.22μF
		25	0.12μF – 0.47μF
		16	0.15μF – 1.0μF
		10	2.2μF
		6.3	2.2μF
GCG21	2.0X1.25 <0805>	50	0.15μF – 1.0μF
		35	0.68μF – 1.0μF
		25	0.27μF – 1.0μF
		16	0.33μF – 4.7μF
		10	10μF
		6.3	10μF
GCG31	3.2X1.6 <1206>	50	0.22μF – 0.33μF
		25	1.2μF – 4.7μF
		16	0.68μF – 4.7μF
		6.3	22μF
GCG32	3.2X2.5 <1210>	50	10μF
		35	10μF
		25	10μF – 22μF
		16	6.8μF – 10μF
		6.3	47μF

Continued on the following page.↗

Ceramic capacitors SMD type For Medical Devices

Chip Multilayer Ceramic Capacitors for Implantable Medical devices (Non Life support circuit)

GCH

Medical Device

Temperature Compensating Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F)
GCH15	1.0X0.5 <0402>	50	1.0pF – 1000pF
GCH18	1.6X0.8 <0603>	100	1.0pF – 1500pF
		50	1500pF – 3300pF
GCH21	2.0X1.25 <0805>	100	2200pF – 3300pF
		50	4700pF – 22000pF
GCH31	3.2X1.6 <1206>	100	4700pF – 10000pF
		50	33000pF – 0.10μF

High Dielectric Constant Type

Series	LXW (mm) <Size Code (inch)>	Rated Voltage (Vdc)	Capacitance Range (F)
GCH03	0.6X0.3 <0201>	25	1000pF
GCH15	1.0X0.5 <0402>	100	220pF – 4700pF
		50	220pF – 0.10μF
		25	10000pF – 47000pF
		16	47000pF – 0.22μF
		10	0.10μF – 1.0μF
GCH18	1.6X0.8 <0603>	100	10000pF – 22000pF
		50	0.22μF
		25	0.10μF – 1.0μF
		16	0.47μF – 1.0μF
		10	2.2μF
		6.3	2.2μF
GCH21	2.0X1.25 <0805>	100	47000pF – 1.0μF
		50	0.47μF – 1.0μF
		35	1.0μF – 4.7μF
		25	2.2μF – 4.7μF
		16	2.2μF – 4.7μF
		10	4.7μF – 10μF
		6.3	10μF
GCH31	3.2X1.6 <1206>	100	0.22μF
		50	2.2μF
		16	10μF
GCH32	3.2X2.5 <1210>	50	4.7μF
		10	22μF
		6.3	47μF

Continued on the following page. ↗

Ceramic capacitors lead type For General Purpose

Leaded MLCC for General Purpose

RDE RDE RDE

General | Deflecting crack | Soldering crack | Anti-noise

Temperature Compensating Type

Series	LXW (mm)	Rated Voltage (Vdc)	Capacitance Range (F)	
RDE5C	4.0X3.5	100	1.0pF	1500pF
		50	1.0pF	3900pF
	4.5X3.5	630	10pF	2200pF
		250	10pF	10000pF
		100	1800pF	3300pF
		50	4700pF	22000pF
	5.0X3.5	100	1.0pF	3300pF
		50	1.0pF	22000pF
	5.5X4.0	1000	10pF	1000pF
		630	10pF	4700pF
		250	10pF	22000pF
		100	3900pF	22000pF
		50	27000pF	0.10μF
RDE7U	4.5X3.5	250	100pF	4700pF
	5.5X4.0	1000	10pF	1000pF
		630	10pF	4700pF
		250	6800pF	22000pF
	5.5X5.0	1000	1500pF	2200pF
		630	6800pF	10000pF
		250	33000pF	47000pF
	7.5X5.5	1000	3300pF	4700pF
		630	15000pF	22000pF
	7.5X8.0	1000	6800pF	10000pF
		630	33000pF	47000pF
	7.7X13.0	1000	20000pF	
		630	94000pF	

High Dielectric Constant Type

Series	LXW (mm)	Rated Voltage (Vdc)	Capacitance Range (F)	
RDEC7	4.0X3.5	25	0.22μF	1.0μF
	4.5X3.5	50	1.0μF	
		25	2.2μF	
	5.0X3.5	50	1.0μF	
		25	0.22μF	2.2μF
	5.5X4.0	50	4.7μF	
		25	4.7μF	10μF
	5.5X5.0	100	1.5μF	2.2μF
		50	10μF	
		25	22μF	
	5.5X7.5	100	4.7μF	
		50	22μF	
		25	47μF	
RDED7	5.5X4.0	630	10000pF	15000pF
		450	10000pF	47000pF

Continued on the following page.↗

Ceramic Capacitor, Polymer Aluminum Electrolytic Capacitors

Series	LXW (mm)	Rated Voltage (Vdc)	Capacitance Range (F) (0.1p, 1p, 10p, 100p, 1000p, 10000p, 0.1μ, 1μ, 10μ, 100μ, 1000μ)
RDED7	5.5X4.0	250	33000pF – 68000pF
	5.5X5.0	630	22000pF – 47000pF
		450	68000pF – 0.10μF
		250	0.10μF – 0.15μF
	7.5X5.5	630	68000pF
		450	0.15μF
		250	0.22μF – 0.33μF
	7.5X7.5	450	0.22μF – 0.56μF
		250	0.47μF – 1.0μF
	7.5X8.0	630	0.10μF – 0.27μF
	7.7X12.5	450	1.0μF – 1.2μF
		250	2.2μF
	7.7X13.0	630	0.47μF – 0.56μF
RDER7	4.0X3.5	100	220pF – 22000pF
		50	220pF – 0.10μF
		25	0.10μF
	4.5X3.5	500	1000pF – 10000pF
		250	1000pF – 22000pF
		100	33000pF – 0.47μF
		50	0.15μF – 0.47μF
	5.0X3.5	100	220pF – 0.47μF
		50	220pF – 0.47μF
		25	0.10μF
	5.5X4.0	1000	470pF – 10000pF
		630	1000pF – 22000pF
		500	15000pF – 47000pF
		250	33000pF – 0.10μF
		100	0.15μF – 1.0μF
		50	0.68μF – 2.2μF
	5.5X5.0	1000	15000pF – 22000pF
		630	33000pF – 47000pF
		500	68000pF – 0.10μF
		250	0.15μF – 0.22μF
		50	3.3μF
	7.5X5.5	1000	33000pF – 47000pF
		630	68000pF – 0.10μF
		500	0.15μF – 0.22μF
		250	0.33μF – 0.47μF
	7.5X7.5	500	0.33μF – 0.47μF
		250	0.68μF – 1.0μF
	7.5X8.0	1000	68000pF – 0.10μF
		630	0.15μF – 0.22μF
	7.7X12.5	500	0.68μF – 1.0μF
		250	2.2μF
	7.7X13.0	1000	0.22μF
		630	0.47μF

Continued on the following page.↗

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose / IEC60384-14 Class X1/Y1 Type RA [500Vac (r.m.s.) product]

DE1 Type RA

General Safety standard

Temperature Compensating Type

Series	Rated Voltage (V)	D (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ)
DE11X	X1: AC500V (r.m.s.), Y1: AC500V(r.m.s.)	6.0 to 9.0	10pF – 68pF

High Dielectric Constant Type

Series	Rated Voltage (V)	D (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ)
DE1B3	X1: AC500V (r.m.s.), Y1: AC500V(r.m.s.)	6.0 to 9.0	100pF – 680pF
DE1E3	X1: AC500V (r.m.s.), Y1: AC500V(r.m.s.)	8.0 to 14.0	1000pF – 4700pF

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose / IEC60384-14 Class X1/Y1 Type RA [250Vac, 300Vac rated]

DE1 Type RA

General Safety standard

Temperature Compensating Type

Series	Rated Voltage (V)	D (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ)
DE11X	X1: AC440V (r.m.s.), Y1: AC300V(r.m.s.)	6.0 to 8.0	10pF – 68pF
	X1: AC440V (r.m.s.), Y1: AC250V(r.m.s.)	6.0 to 8.0	10pF – 68pF

High Dielectric Constant Type

Series	Rated Voltage (V)	D (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ)
DE1B3	X1: AC440V (r.m.s.), Y1: AC300V(r.m.s.)	6.0 to 8.0	100pF – 680pF
	X1: AC440V (r.m.s.), Y1: AC250V(r.m.s.)	6.0 to 8.0	100pF – 680pF
DE1E3	X1: AC440V (r.m.s.), Y1: AC300V(r.m.s.)	7.0 to 12.0	1000pF – 4700pF
	X1: AC440V (r.m.s.), Y1: AC250V(r.m.s.)	7.0 to 12.0	1000pF – 4700pF

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose / IEC60384-14 Class X1/Y1 Type RB [X1:760Vac(r.m.s)product]

DE1 Type RB

General Safety standard

Temperature Compensating Type

Series	Rated Voltage (V)	D (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ)
DE11X	X1: AC760V (r.m.s.), Y1: AC500V(r.m.s.)	6.0 to 9.0	10pF – 68pF

Continued on the following page. ↗

High Dielectric Constant Type

Series	Rated Voltage (V)	D (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ)
DE1B3	X1: AC760V (r.m.s.), Y1: AC500V(r.m.s.)	6.0 to 9.0	100pF – 680pF
DE1E3	X1: AC760V (r.m.s.), Y1: AC500V(r.m.s.)	8.0 to 14.0	1000pF – 4700pF

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose / IEC60384-14 Class X1/Y2 Type SA [400Vac (r.m.s.) product]

DE2 Type SA

General Safety standard

Temperature Compensating Type

Series	Rated Voltage (V)	D (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ)
DE21X	X1: AC440V (r.m.s.), Y2: AC400V(r.m.s.)	6.0 to 9.0	10pF – 68pF

High Dielectric Constant Type

Series	Rated Voltage (V)	D (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ)
DE2B3	X1: AC440V (r.m.s.), Y2: AC400V(r.m.s.)	6.0 to 8.0	100pF – 680pF
DE2E3	X1: AC440V (r.m.s.), Y2: AC400V(r.m.s.)	7.0 to 17.0	1000pF – 10000pF

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose / IEC60384-14 Class X1/Y2 Type SA [250Vac, 300Vac rated]

DE2 Type SA

General Safety standard

Temperature Compensating Type

Series	Rated Voltage (V)	D (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ)
DE21X	X1: AC300V (r.m.s.), Y2: AC300V(r.m.s.)	6.0 to 8.0	10pF – 68pF
	X1: AC300V (r.m.s.), Y2: AC250V(r.m.s.)	6.0 to 8.0	10pF – 68pF

High Dielectric Constant Type

Series	Rated Voltage (V)	D (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ)
DE2B3	X1: AC300V (r.m.s.), Y2: AC300V(r.m.s.)	6.0 to 7.0	100pF – 680pF
	X1: AC300V (r.m.s.), Y2: AC250V(r.m.s.)	6.0 to 7.0	100pF – 680pF
DE2E3	X1: AC300V (r.m.s.), Y2: AC300V(r.m.s.)	6.0 to 15.0	1000pF – 10000pF
	X1: AC300V (r.m.s.), Y2: AC250V(r.m.s.)	6.0 to 15.0	1000pF – 10000pF

Continued on the following page.↗

Ceramic capacitors lead type For Automotive

Leaded MLCC for Automotive



RCE

Temperature Compensating Type

Power-train | AEC-Q200 | Deflecting crack | Soldering crack | Anti-noise

Series	LXW (mm)	Rated Voltage (Vdc)	Capacitance Range (F) (0.1p – 1000μ)
RCE5C	3.6X3.5	100	1.0pF – 1500pF
		50	1.0pF – 3900pF
	4.0X3.5	630	10pF – 2200pF
		250	10pF – 10000pF
		100	1800pF – 3300pF
		50	4700pF – 22000pF
	5.5X4.0	1000	10pF – 1000pF
		630	10pF – 4700pF
		250	10pF – 22000pF
		100	3900pF – 10000pF
		50	27000pF – 0.10μF
RCE7U	4.0X3.5	250	100pF – 4700pF
	5.5X4.0	1000	10pF – 1000pF
		630	10pF – 4700pF
		250	6800pF – 10000pF
	5.5X5.0	1000	1500pF – 2200pF
		630	6800pF – 10000pF
	7.5X5.5	1000	3300pF – 4700pF
		630	15000pF – 22000pF
	7.5X8.0	1000	6800pF – 10000pF
		630	33000pF – 47000pF
	7.7X13.0	1000	20000pF
		630	94000pF

High Dielectric Constant Type

Series	LXW (mm)	Rated Voltage (Vdc)	Capacitance Range (F) (0.1p – 1000μ)
RCEC7	4.0X3.5	50	1.0μF
	5.5X4.0	50	4.7μF
	5.5X5.0	100	1.5μF – 2.2μF
		50	10μF
	5.5X7.5	100	4.7μF
		50	22μF
RCER7	3.6X3.5	100	220pF – 22000pF
		50	220pF – 0.10μF
		25	0.10μF – 0.22μF
	4.0X3.5	250	1000pF – 22000pF
		100	33000pF – 0.33μF
		50	0.15μF – 0.47μF
		25	0.33μF – 1.0μF
	5.5X4.0	1000	1000pF – 10000pF
		630	1000pF – 22000pF
		250	33000pF – 0.10μF
		100	0.15μF – 1.0μF
		50	0.68μF – 2.2μF
		25	1.5μF – 4.7μF

Continued on the following page.↗

Series	LXW (mm)	Rated Voltage (Vdc)	Capacitance Range (F) (0.1p – 1000μ)
RCER7	5.5X5.0	1000	15000pF – 22000pF
		630	33000pF – 47000pF
		250	0.15μF – 0.22μF
		50	3.3μF – 4.7μF
		25	10μF
	5.5X7.5	50	10μF
		25	22μF
	7.5X5.5	1000	33000pF – 47000pF
		630	68000pF – 0.10μF
		250	0.33μF – 0.47μF
	7.5X7.5	250	0.68μF – 1.0μF
	7.5X8.0	1000	68000pF – 0.10μF
		630	0.15μF – 0.22μF
	7.7X12.5	250	2.2μF
	7.7X13.0	1000	0.22μF
		630	0.47μF

150°C Operation Leaded MLCC for Automotive

RHE

Temperature Compensating Type

Power-train | AEC-Q200 | Deflecting crack | Soldering crack | Anti-noise

Series	LXW (mm)	Rated Voltage (Vdc)	Capacitance Range (F) (0.1p – 1000μ)
RHE5G	3.6X3.5	100	100pF – 1500pF
		50	100pF – 3900pF
	4.0X3.5	100	1800pF – 3300pF
		50	4700pF – 10000pF

High Dielectric Constant Type

Series	LXW (mm)	Rated Voltage (Vdc)	Capacitance Range (F) (0.1p – 1000μ)
RHEL8	3.6X3.5	100	220pF – 22000pF
		50	220pF – 0.10μF
		25	0.10μF – 0.22μF
	4.0X3.5	100	33000pF – 0.10μF
		50	0.15μF – 0.33μF
		25	0.33μF – 1.0μF
	5.5X4.0	100	0.15μF – 0.22μF
		50	0.47μF – 2.2μF
		25	1.5μF – 4.7μF
	5.5X5.0	50	3.3μF – 4.7μF
		25	10μF
	5.5X7.5	50	10μF
		25	22μF

Continued on the following page.↗

175°C/200°C Operation Leaded MLCC for Automotive



RHS

Power-train | AEC-Q200 | Deflecting crack | Soldering crack | Anti-noise

Series	LXW (mm)	Rated Voltage (Vdc)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1µ 1µ 10µ 100µ 1000µ)
RHS7G	3.9X3.5	100	100pF – 1500pF
	4.2X3.5	100	1800pF – 3300pF
RHS7J	4.2X3.5	200	100pF – 4700pF
	5.5X4.0	500	100pF – 4700pF
		200	6800pF – 10000pF

Safety Standard Certified Lead Type Disc Ceramic Capacitors for Automotive

DE6

Power-train | AEC-Q200 | Safety standard

Series	Rated Voltage (V)	D (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1µ 1µ 10µ 100µ 1000µ)
DE6E3	X1: AC440V (r.m.s.), Y2: AC300V(r.m.s.)	7.0 to 12.0	1000pF – 4700pF

Resin Molding SMD Type Ceramic Capacitors

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose

DK1

General | Safety standard | Deflecting crack | Soldering crack

Temperature Compensating Type

Series	Rated Voltage (V)	LXW (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1µ 1µ 10µ 100µ 1000µ)
DK11X	X1: AC440V (r.m.s.), Y1: AC300V(r.m.s.)	11.4X6.0	10pF – 47pF
	X1: AC440V (r.m.s.), Y1: AC250V(r.m.s.)	11.4X6.0	10pF – 47pF

High Dielectric Constant Type

Series	Rated Voltage (V)	LXW (mm)	Capacitance Range (F) (0.1p 1p 10p 100p 1000p 10000p 0.1µ 1µ 10µ 100µ 1000µ)
DK1B3	X1: AC440V (r.m.s.), Y1: AC300V(r.m.s.)	11.4X6.0	100pF – 680pF
	X1: AC440V (r.m.s.), Y1: AC250V(r.m.s.)	11.4X6.0	100pF – 680pF
DK1E3	X1: AC440V (r.m.s.), Y1: AC300V(r.m.s.)	11.4X6.0	1000pF – 1500pF
	X1: AC440V (r.m.s.), Y1: AC250V(r.m.s.)	11.4X6.0	1000pF – 1500pF

Continued on the following page. ↗

Polymer Aluminum Electrolytic Capacitors

ECAS

ECNS

General | Deflecting crack | Anti-noise | Effective Cap

Series	LxW (mm)	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
ECAS	7.3X4.3	25	10μF – 33μF
		20	33μF – 47μF
		16	6.8μF – 68μF
		12.5	10μF – 100μF
		10	10μF – 150μF
		6.3	10μF – 330μF
		4	68μF – 330μF
		2.5	330μF – 470μF
		2	100μF – 560μF
ECNS	3.5X2.8	25	10μF – 15μF
		16	15μF – 33μF
		6.3	22μF – 100μF

Detailed Catalogs

For more details, please refer to our printed catalogs and the PDF catalogs on our website.



- Chip Multilayer Ceramic Capacitors for General — Cat. No. C02E
- Chip Multilayer Ceramic Capacitors for Automotive — Cat. No. C03E
- Lead Type Disc Ceramic Capacitors (Safety Standard Certified, DC2k to DC6.3kV) Resin Molding SMD Type Ceramic Capacitors (Safety Standard Certified) — Cat. No. C85E
- Polymer Aluminum Electrolytic Capacitors — Cat. No. C90E
- Leaded MLCC — Cat. No. C49E

Single-Layer Microchip Capacitors, Thin Film Circuit Substrates (RUSUB)

Single-Layer Microchip Capacitors

Very reliable performance and excellent frequency characteristics

Temperature Compensating Type



Capacitance Change (Temperature Range)	Series	Size (mm)	Rated Voltage (Vdc)	Capacitance Range at 25°C (pF) (0.1 – 1 – 10 – 100 – 1000)	Operating Temperature Range (°C)
0±30ppm/°C (-25 to 85°C)	CLB0A	0.25X0.25	100	0.1	-55 to 125
	CLB0C	0.35X0.25	100	0.2	-55 to 125
	CLB0D	0.38X0.38	100	0.2 – 0.4	-55 to 125
	CLB05	0.50X0.50	100	0.3 – 0.6	-55 to 125
	CLB0E	0.55X0.38	100	0.5 – 0.6	-55 to 125
	CLB0F	0.64X0.64	100	0.3 – 1.0	-55 to 125
	CLB0G	0.70X0.50	100	0.7 – 1.0	-55 to 125
	CLB0H	0.71X0.38	100	0.7 – 0.8	-55 to 125
	CLB0J	0.76X0.76	100	0.4 – 1.3	-55 to 125
	CLB09	0.90X0.90	100	0.5 – 1.8	-55 to 125
	CLB1A	1.00X0.64	100	1.1 – 1.6	-55 to 125
	CLB1B	1.09X0.76	100	1.5 – 2.0	-55 to 125
	CLB1C	1.27X1.27	100	1.0 – 3.6	-55 to 125
	CLB1E	1.49X0.90	100	2.0 – 2.7	-55 to 125
	CLB1G	1.73X1.27	100	3.9 – 4.7	-55 to 125
	CLB1H	1.78X1.78	100	1.8 – 6.8	-55 to 125
	CLB2C	2.19X1.27	100	5.1	-55 to 125
	CLB2E	2.29X2.29	100	3.0 – 10	-55 to 125
	CLB2L	2.95X1.78	100	7.5 – 10	-55 to 125
	CLB3G	3.71X2.29	100	11 – 16	-55 to 125
-750±60ppm/°C (-25 to 85°C)	CLB0A	0.25X0.25	100	0.3 – 0.7	-55 to 125
	CLB0B	0.30X0.25	100	0.8	-55 to 125
	CLB0C	0.35X0.25	100	0.9	-55 to 125
	CLB0D	0.38X0.38	100	0.9 – 1.6	-55 to 125
	CLB05	0.50X0.50	100	1.0 – 2.4	-55 to 125
	CLB0E	0.55X0.38	100	1.8 – 2.4	-55 to 125
	CLB0F	0.64X0.64	100	2.0 – 4.3	-55 to 125
	CLB0G	0.70X0.50	100	2.7 – 3.0	-55 to 125
	CLB0H	0.71X0.38	100	2.7	-55 to 125
	CLB0J	0.76X0.76	100	3.0 – 6.2	-55 to 125
	CLB09	0.90X0.90	100	3.3 – 6.8	-55 to 125
	CLB1A	1.00X0.64	100	4.7 – 6.2	-55 to 125
	CLB1B	1.09X0.76	100	6.8 – 7.5	-55 to 125
	CLB1C	1.27X1.27	100	7.5 – 15	-55 to 125
	CLB1E	1.49X0.90	100	7.5 – 9.1	-55 to 125
	CLB1H	1.78X1.78	100	13 – 15	-55 to 125
	CLB2E	2.29X2.29	100	20	-55 to 125

All Single Layer Microchip Capacitors are produced after receiving an order.

High Dielectric Constant Type



Capacitance Change (Temperature Range)	Series	Size (mm)	Rated Voltage (Vdc)	Capacitance Range at 25°C (pF) (0.1 / 1 / 10 / 100 / 1000)	Operating Temperature Range (°C)
±10% (-25 to 85°C)	CLB0A	0.25X0.25	100	5.6 – 12	-55 to 125
	CLB0B	0.30X0.25	100	13 – 15	-55 to 125
	CLB0C	0.35X0.25	100	16 – 18	-55 to 125
	CLB0D	0.38X0.38	100	18 – 30	-55 to 125
	CLB05	0.50X0.50	100	22 – 43	-55 to 125
	CLB0E	0.55X0.38	100	33 – 43	-55 to 125
	CLB0F	0.64X0.64	100	43 – 75	-55 to 125
	CLB0G	0.70X0.50	100	47 – 68	-55 to 125
	CLB0H	0.71X0.38	100	47 – 56	-55 to 125
	CLB0J	0.76X0.76	100	68 – 110	-55 to 125
	CLB09	0.90X0.90	100	68 – 130	-55 to 125
	CLB1A	1.00X0.64	100	82 – 120	-55 to 125
	CLB1C	1.27X1.27	100	160 – 200	-55 to 125
	CLB1E	1.49X0.90	100	150 – 160	-55 to 125
	CLB1G	1.73X1.27	100	300	-55 to 125
	CLB1H	1.78X1.78	100	300 – 430	-55 to 125
	CLB2E	2.29X2.29	100	470 – 620	-55 to 125
+30, -80% (-25 to 85°C)	CLB0A	0.25X0.25	100	27 – 33	-55 to 125
	CLB0B	0.30X0.25	100	36 – 39	-55 to 125
	CLB0C	0.35X0.25	100	43 – 51	-55 to 125
	CLB0D	0.38X0.38	100	62 – 82	-55 to 125
	CLB05	0.50X0.50	100	75 – 130	-55 to 125
	CLB0E	0.55X0.38	100	91 – 120	-55 to 125
	CLB0F	0.64X0.64	100	130 – 220	-55 to 125
	CLB0G	0.70X0.50	100	150 – 200	-55 to 125
	CLB0H	0.71X0.38	100	130 – 150	-55 to 125
	CLB0J	0.76X0.76	100	200 – 300	-55 to 125
	CLB09	0.90X0.90	100	200 – 390	-55 to 125
	CLB1A	1.00X0.64	100	240 – 360	-55 to 125
+30, -90% (-25 to 85°C)	CLB0A	0.25X0.25	100	36 – 56	-55 to 125
	CLB0D	0.38X0.38	100	91 – 150	-55 to 125
	CLB05	0.50X0.50	100	130 – 220	-55 to 125
	CLB0F	0.64X0.64	100	220 – 390	-55 to 125
	CLB0J	0.76X0.76	100	330 – 560	-55 to 125
	CLB09	0.90X0.90	100	390 – 680	-55 to 125

All Single Layer Microchip Capacitors are produced after receiving an order.

Thin Film Circuit Substrates (RUSUB)

Customizable capacitors for impedance matching for RF power amplifiers and decoupling for optical communication devices.

Features

- Single-layer structure enhances self-resonant frequency, which allows stable operation even at a high frequency range.
- RUSUB technology achieves miniaturization of the device by combining a single-layer capacitor and a thin film resistor. In addition, it contributes to attenuation of unnecessary noise.
- By utilizing Au electrodes, die bonding with AuSn and wire bonding with gold wire are possible.
- A wide selection of substrate materials meets customers' requirements. (Please refer to the following table.)

Function	Dielectric Constant (ε_r) *1	Size min. (mm) (LxWxT) *2	Temperature Characteristics of Capacitance (ppm/°C) *3	Through Hole	TaN Resistance	L/S min. (μm) *4	Coefficient of Thermal Expansion (ppm/°C) *1	Temperature Conductivity (ppm/(m·°C)) *1
Impedance Matching	9	0.25X0.25X0.10	-	○	○	30/30 (Au thickness 4μm)	4.6	200.0
	10	0.25X0.25X0.20	-	○	○		7.0	33.5
	39	0.25X0.25X0.10	0±30	×	○		6.6	1.9
	90	0.25X0.25X0.10	-330±120	×	○		9.2	2.3
	150	0.25X0.25X0.10	-750±120	×	○		11.7	2.0
	250	0.25X0.25X0.10	-750±600	×	○		12.2	4.0
Decoupling	3000	0.25X0.25X0.10	±10%	×	○	50/50 (Au thickness 8μm)	10.7	2.5
	10000	0.25X0.25X0.10	+30, -80%	×	×		10.5	1.6
	15000	0.25X0.25X0.10	+30, -90%	×	×		14.0	2.4
	30000	0.25X0.25X0.25	±25%	×	○		11.2	7.35

*1 : Typical value
*2 : L = length, W = width, T = thickness
*3 : Temperature Range: -25 to 85°C, Reference Temperature: 25°C
*4 : L = line, S = space

Single-Layer Microchip Capacitors, Thin Film Circuit Substrates (RUSUB)

Thirteen types of standard products suitable for decoupling are also available.

RUCYT101 Series



RUCYT201 Series



RUCQD Series

(in mm)

Part Number	Size (mm) (LxWxT)	Capacitor			Resistor	
		Capacitance (pF)	Temperature Characteristics of Capacitance (-25 to 85°C)	Rated Voltage (V)	Resistance (Ω)	Temperature Coefficient of Resistance (ppm/°C)
RUCYT101K00009GNTC	1.0X0.5X0.11	100	±10%	100	50±20%	-70±50
RUCYT101K00011GNTC	1.0X0.5X0.11	100			100±20%	
RUCYT101K00012GNTC	1.0X0.5X0.11	100			200±20%	
RUCYT201K00010GNTC	1.0X1.0X0.12	200			50±20%	
RUCYT201K00013GNTC	1.0X1.0X0.12	200			100±20%	
RUCYT201K00014GNTC	1.0X1.0X0.12	200			200±20%	
RUCQD101RCC007GNTC	0.34X0.34X0.25	100	±25%	65	-	-
RUCQD431RCC001GNZB	0.70X0.70X0.25	430				
RUCQD471RCC002GNZB	0.73X0.73X0.25	470				
RUCQD511RCC003GNZB	0.76X0.76X0.25	510				
RUCQD561RCC004GNZB	0.80X0.80X0.25	560				
RUCQD102RCC008GNZB	1.07X1.07X0.25	1000				
RUCQD201ZCC005GNZB	1.10X0.60X0.25	200×4				

*Several samples for impedance matching are also available for your evaluation. Please find the details at the following link: https://www.murata.com/en-global/products/capacitor/rusub/matching

Detailed Catalogs

For more details, please refer to our printed catalogs and the PDF catalogs on our website.



- Single-Layer Microchip Capacitors/Thin Film Circuit Substrates
  Cat. No. C01E

Variable Capacitors

Variable capacitors can carry out the variable of the capacitor by adjusting the tuning voltage.
They are designed for frequency matching use for HF band (13.56MHz).

LXRW_V Series



LXRW0YV Series LXRW19V Series (in mm)

Series	LXW (mm)	Rated Voltage (Vdc)	Capacitance Range (F) 0.1p 1p 10p 100p 1000p 10000p 0.1μ 1μ 10μ 100μ 1000μ
LXRW0Y	0.6X0.6	CSP	33pF – 90pF
LXRW19	1.3X0.9	DFN	33pF – 200pF

Silicon Capacitors

Murata High-Density Silicon Capacitors are based on a MOS Semiconductor technology and utilize a 3D structure that substantially increases their performance and enables compact design. Silicon Capacitors offer small size and low thickness, superior reliability, and stability over high temperatures and high frequencies. They are the ideal choice for all demanding markets, such as Networking (RF Power and Broadband), Medical (Implantable devices), Automotive, or High-Reliability applications. Murata can provide customized Silicon Capacitors or Integrated Passive Devices (IPDs) to optimize your design.

Product Lineup

	Thickness	Standard (150°C)	High temp.	Operating Frequency	Low ESL
Solder Mounting	85μm				UESL (Typically 15pH) S p39
	100μm	LPSC R All p35		XBSC (100GHz+) UBSC (60GHz+) BBSC (40GHz) ULSC (20GHz) UBDC (60GHz+) B p36, 37	
	400μm	HSSC All p35	HTSC (200°C) XTSC (250°C) H p35		
Wire-bonding vertical	100μm	WLSC P A B p38		UWSC (26GHz+) (down to 10pH) B P p38	
	250μm	WBSC P A B p38	WTSC (200°C) WXSC (250°C) A P H p38		
Wire-bonding /Embedded horizontal	100μm	EMSC All MGSC M p35, 39		UBEC (60GHz+) BBEC (40GHz) ULEC (20GHz) B p37	
	250μm		ETSC (200°C) EXSC (250°C) H ATSC (200°C) A p36, 39		

Target application

- A Automotive
- M Medical
- H High Reliability
- All All applications
- S Signal Integrity
- P Power Amp for RF
- B BroadBand
- R RFID

High stability and reliability Si capacitors (HSSC)

BV 11V BV 30V

Series	Size (inch)	Size (mm)
HSSC	1812	4.70X3.60
	1206	3.40X1.80
	0805	2.20X1.40
	0603	1.80X1.10
	0402	1.20X0.70
	0201	0.80X0.60



Low-profile Si capacitors down to 100μm (LPSC)

BV 11V BV 30V

Series	Size (inch)	Size (mm)
LPSC	1206	3.40X1.80
	0805	2.20X1.40
	0603	1.80X1.10
	0402	1.20X0.70
	0402	1.20X0.70
	0201	0.80X0.60
	0201	0.80X0.60



Xtreme temperature Si capacitors up to 250°C (HTSC/XTSC)

BV 11V BV 30V

Series	Size (inch)	Size (mm)
HTSC XTSC	1812	4.70X3.60
	1206	3.40X1.80
	0603	1.80X1.10
	0402	1.20X0.70
	0201	0.80X0.60



Wire-bondable or embedded low-profile Si capacitors down to 100μm (EMSC)

BV 11V BV 30V

Series	Size (inch)	Size (mm)
EMSC	1208	3.07X2.07
	0605	1.59X1.32
	0505	1.32X1.32
	0404	1.07X1.07
	0202	0.63X0.63



△ Available parts. For other values, contact your Murata sales representative. △ Under development.

Silicon Capacitors

Extreme temperature wire-bondable Si capacitors up to 250°C (ETSC/EXSC)

BV 11V BV 30V

Series	Size (inch)	Size (mm)	Capacitance Range (F)
ETSC EXSC	2016	5.07X4.07	
	1616	4.07X4.07	
	1612	4.07X3.07	
	1208	3.07X2.07	
	0605	1.59X1.32	
	0505	1.32X1.32	
	0404	1.07X1.07	
	0202	0.63X0.63	



Ultra broadband surface mounted Si capacitor up to 100GHz+ (XBSC)

BV 11V BV 30V

Series	Size (inch)	Size (mm)	Capacitance Range (F)
XBSC	0201M	0.60X0.30	



Ultra broadband surface mounted Si capacitors up to 60GHz+ (UBSC)

BV 11V BV 30V

Series	Size (inch)	Size (mm)	Capacitance Range (F)
UBSC	0402	1.20X0.70	
	0201	0.80X0.60	
	0201M	0.60X0.30	



Ultra broadband surface mounted Si capacitors up to 40GHz (BBSC)

BV 11V BV 30V

Series	Size (inch)	Size (mm)	Capacitance Range (F)
BBSC	0402	1.20X0.70	
	0201	0.80X0.60	
	0201M	0.60X0.30	



△ Available parts. For other values, contact your Murata sales representative. △ Under development.

Ultra broadband surface mounted Si capacitors up to 20GHz (ULSC)

BV 11V BV 30V

Series	Size (inch)	Size (mm)	Capacitance Range (F)
ULSC	0603	1.80X1.10	
	0402	1.20X0.70	
	0201	0.80X0.60	
	0201M	0.60X0.30	

Capacitance Range (F): 1n, 5.6n, 10n, 22n, 47n, 100n

Ultra Broadband surface mounted differential Si capacitors pairs up to 60GHz+ (UBDC)

BV 11V BV 30V

Series	Size (inch)	Size (mm)	Capacitance Range (F)
UBDC	0402M	1.00X0.50	

Capacitance Range (F): 2x5.6n, 2x10n

Ultra broadband wire-bondable embedded Si capacitors up to 60GHz+ (UBEC)

BV 11V BV 30V

Series	Size (inch)	Size (mm)	Capacitance Range (F)
UBEC	0404	1.07X1.07	
	0201M	0.60X0.30	

Capacitance Range (F): 1n, 3.3n, 5.6n, 10n, 33n, 100n

Ultra broadband wire-bondable embedded Si capacitors up to 40/20GHz (BBEC/ULEC)

BV 11V BV 30V

Series	Size (inch)	Size (mm)	Capacitance Range (F)
BBEC ULEC	0404	1.07X1.07	
	0201M	0.60X0.30	

Capacitance Range (F): 1n, 5.6n, 10n, 33n, 100n

△ Available parts. For other values, contact your Murata sales representative. △ Under development.

Silicon Capacitors

Ultra large-band wire-bondable vertical Si capacitors up to 26GHz+ (UWSC)

BV 11V | BV 30V | BV 50V | BV 100V | BV 150V | BV 450V

Series	Size (inch)	Size (mm)
UWSC	0504	1.25X1.00
	0402	1.00X0.50
	0303	0.80X0.80
	0303	0.80X0.80
	0302	0.80X0.50
	0202	0.50X0.50
	0201	0.50X0.25
	015015	0.381X0.381
	0101/0101+	0.25X0.25/0.294X0.294



Wire-bondable vertical Si capacitors up to 250°C (WBSC/WTSC/WXSC)

BV 11V | BV 30V | BV 50V | BV 100V | BV 150V | BV 450V

Series	Size (inch)	Size (mm)
WBSC WTSC WXSC	0504	1.25x1.00
	0402	1.00x0.50
	0303	0.80x0.80
	0303	0.80x0.80
	0302	0.80x0.50
	0202	0.50x0.50



Wire-bondable vertical low-profile Si capacitors down to 100μm (WLSC)

BV 11V | BV 30V | BV 50V | BV 100V | BV 150V | BV 450V

Series	Size (inch)	Size (mm)
WLSC	0504	1.25X1.00
	0402	1.00X0.50
	0303	0.80X0.80
	0303	0.80X0.80
	0302	0.80X0.50
	0202	0.50X0.50
	0201	0.50X0.25
	015015	0.381X0.381
	0101/0101+	0.25X0.25/0.294X0.294



△ Available parts. For other values, contact your Murata sales representative. △ Under development.

Automotive high temperature Si capacitors up to 200°C (ATSC)

BV 30V

Series	Size (inch)	Size (mm)	Capacitance Range (F)
ATSC	1616	4.07X4.07	
	0605	1.59X1.32	
	0505	1.32X1.32	
	0202	0.63X0.63	



Ultra low ESL and ultra-low-profile Si capacitors down to 85µm (UESL)

BV 5V

Series	Size (inch)	Size (mm)	Capacitance Range (F)
UESL	0404	1.04X1.04	
	0402M	1.00X0.50	
	0204M	0.50X1.00	
	0201M	0.60X0.30	



Medical grade Si capacitors (MGSC)

BV 30V

Series	Size (inch)	Size (mm)	Capacitance Range (F)
MGSC	1616	4.07X4.07	
	0605	1.59X1.32	
	0505	1.32X1.32	
	0202	0.63X0.63	



△ Available parts. For other values, contact your Murata sales representative. △ Under development.

Film Capacitors

The FH series uses materials with high heat resistance. Therefore, it has a higher allowable ripple current under a higher temperature environment than conventional PP film capacitors.
This feature is more prominent in the high-frequency range. For example, when the ambient temperature is at 105°C, the PP film capacitors would be already at its limit for allowable ripple current, but because of the higher heat resistance of the FH series, the allowable ripple current can be increased drastically.

FHA50Y206KS

FHA50Y156KS
FHA50Y106KS

Specifications

Items	Basic Specifications
Rated Capacitance	10,15,20μF
Rated Voltage	500V
Operational Life	125°C/500V 2000h
Biased Humidity	85°C/85%RH/500V 1000h



Dimensions

Part Number	Capacitance	Dimensions (mm)			
		W	H	T	S
FHA50Y206KS	20μF	35.0	37.0	20.0	29.0
FHA50Y156KS	15μF	35.0	35.5	14.5	29.0
FHA50Y106KS	10μF				

Noise Suppression Products/ EMI Suppression Filters

Broad lineup of Noise Suppression Products and EMI Suppression Filters

Summary

Using Murata's ceramic processing technology and unique materials, we offer a variety of Noise Suppression Products and EMI Suppression Filters.

Lineup

- EMI (chip and lead type)
- Noise Suppression Products for Automotive
- ESD Protection Devices

https://www.murata.com/en-global/products/emc

Noise Suppression Filters (Chip Ferrite Bead)/ (Frequency Specified Noise Filters)

			Series	Size Code inch (mm)	Max. Rated Current (mA)	Impedance at 100MHz (Rated Current)
For General Band Noise	Universal Type [Power Lines/Signal Lines]		BLM02AX	01005 (0402)	750	10Ω to 330Ω (0.15A to 0.75A)
			BLM03AX	0201 (0603)	1000	10Ω to 1000Ω (0.2A to 1A)
			BLM15AX	0402 (1005)	1740	10Ω to 1000Ω (0.35A to 1.74A)
	Signal Lines Type	For General Signal Lines	BLM03AG	0201 (0603)	-	10Ω to 1000Ω
			BLM15AG	0402 (1005)	-	10Ω to 1000Ω
			BLM18AG	0603 (1608)	-	120Ω to 1000Ω
			BLM21AG	0805 (2012)	-	120Ω to 1000Ω
			BLM18TG	0603 (1608)	-	120Ω to 1000Ω
			BLA2AA (4 circuits array)	0804 (2010)	-	120Ω to 1000Ω
			BLA31AG (4 circuits array)	1206 (3216)	-	30Ω to 1000Ω
		For High Speed Signal Lines	BLM02BX*	01005 (0402)	-	120Ω to 240Ω
			BLM03BX	0201 (0603)	-	1000Ω to 1800Ω
			BLM02BB/BC	01005 (0402)	-	10Ω to 100Ω
			BLM03BB/BC/BD	0201 (0603)	-	10Ω to 600Ω
			BLM15BA/BB/BC/BD	0402 (1005)	-	5Ω to 1800Ω
			BLM15BX	0402 (1005)	-	75Ω to 1800Ω
			BLM18BA/BB/BD	0603 (1608)	-	5Ω to 2500Ω
			BLM21BB/BD	0805 (2012)	-	5Ω to 2700Ω
			BLA2AB (4 circuits array)	0804 (2010)	-	10Ω to 1000Ω
			BLA31BD (4 circuits array)	1206 (3216)	-	120Ω to 1000Ω
		For Digital Interface Lines	BLM18RK	0603 (1608)	-	120Ω to 1000Ω
			BLM21RK	0805 (2012)	-	120Ω to 1000Ω

* The derating of rated current is required for some items according to the operating temperature.
For automotive grade products, please refer to the catalog C51E, "EMI Suppression Filters (for DC)/Chip Inductors for Automotive."

Continued on the following page.↗

Noise Suppression Filters (Chip Ferrite Bead)/(Frequency Specified Noise Filters)

		Series	Size Code inch (mm)	Max. Rated Current (mA)	Impedance at 100MHz (Rated Current)
For General Band Noise	Power Lines Type	BLM02KX*	01005 (0402)	1500	10Ω to 18Ω (1.2A to 1.5A)
		BLM02PX*	01005 (0402)	1100	10Ω to 60Ω (0.5A to 1.1A)
		BLM03PX*	0201 (0603)	1800	22Ω to 120Ω (0.9A to 1.8A)
		BLM03PG	0201 (0603)	900	22Ω to 33Ω (0.75A to 0.9A)
		BLM15KD*	0402 (1005)	3800	20Ω to 120Ω (1.5A to 3.8A)
		BLM15PX*	0402 (1005)	3000	33Ω to 600Ω (0.9A to 3A)
		BLM15PD*	0402 (1005)	2200	30Ω to 120Ω (1.3A to 2.2A)
		BLM15PG	0402 (1005)	1000	10Ω (1A)
		BLM18PG*	0603 (1608)	3000	30Ω to 470Ω (1A to 3A)
		BLM21PG*	0805 (2012)	6000	22Ω to 330Ω (1.5A to 6A)
		BLM31PG*	1206 (3216)	6000	33Ω to 600Ω (1.5A to 6A)
		BLM41PG*	1806 (4516)	6000	60Ω to 1000Ω (1.5A to 6A)
		BLM18SN* (Low DC Resistance Type)	0603 (1608)	8000	22Ω (8A)
		BLM18KG* (Low DC Resistance Type)	0603 (1608)	6000	26Ω to 1000Ω (1A to 6A)
		BLM18SD* (Low DC Resistance Type)	0603 (1608)	6000	22Ω (6A)
		BLM18SG* (Low DC Resistance Type)	0603 (1608)	6000	26Ω to 330Ω (1.5A to 6A)
		BLM21SN*/SP* (Low DC Resistance Type)	0805 (2012)	8500	30Ω to 1000Ω (1.6A to 8.5A)
		BLM31SN* (Low DC Resistance Type)	1206 (3216)	12000	50Ω (12A)
		BLM31KN*	1206 (3216)	6000	120Ω to 1000Ω (2A to 6A)
		BLE18PS*	0603 (1608)	8000	8.5Ω (8A)
		BLE32PN	1210 (3225)	10000	26Ω to 30Ω (10A)
For GHz Band Noise	Universal Type [Power Lines/Signal Lines]	BLM03EB*	0201 (0603)	600	25Ω to 50Ω (0.4A to 0.6A)
		BLM15EG*	0402 (1005)	1500	120Ω to 220Ω (0.7A to 1.5A)
		BLM15EX*	0402 (1005)	1800	120Ω to 470Ω (0.95A to 1.8A)
		BLM18EG*	0603 (1608)	2000	100Ω to 600Ω (0.5A to 2A)
		BLM18HE*	0603 (1608)	800	600Ω to 1500Ω (0.5A to 0.8A)
	Signal Lines Type	BLM03HG	0201 (0603)	-	600Ω to 1200Ω
		BLM03HD	0201 (0603)	-	330Ω to 1800Ω
		BLM03HB	0201 (0603)	-	190Ω to 400Ω
		BLM15HG	0402 (1005)	-	600Ω to 1000Ω
		BLM15HD	0402 (1005)	-	600Ω to 1800Ω
		BLM15HB	0402 (1005)	-	120Ω to 220Ω
		BLM18HG	0603 (1608)	-	470Ω to 1000Ω
		BLM18HD	0603 (1608)	-	470Ω to 1000Ω
		BLM18HB	0603 (1608)	-	120Ω to 330Ω
		BLM18HK	0603 (1608)	-	330Ω to 1000Ω
For High-GHz Band Noise	Signal Lines Type	BLM15GG	0402 (1005)	-	220Ω to 470Ω
		BLM15GA	0402 (1005)	-	75Ω
		BLM18GG	0603 (1608)	-	470Ω
	Power Lines Type	BLM18DN*	0603 (1608)	1400	150Ω to 600Ω

* The derating of rated current is required for some items according to the operating temperature.
For automotive grade products, please refer to the catalog C51E, "EMI Suppression Filters (for DC)/Chip Inductors for Automotive."

Continued on the following page.↗

		Series	Size Code inch (mm)	Max. Rated Current (A)	Impedance at 700MHz
Frequency Specified Noise Filters	For 700MHz Band	BLF02JD*	01005 (0402)	-	360Ω to 470Ω
		BLF02GD	01005 (0402)	-	1600Ω
		BLF03JD*	0201 (0603)	-	420Ω

		Series	Size Code inch (mm)	Max. Rated Current (A)	Impedance at 2.4GHz
Frequency Specified Noise Filters	For 2.4GHz Band	BLF02RD*	01005 (0402)	-	330Ω to 470Ω

		Series	Size Code inch (mm)	Max. Rated Current (A)	Impedance at 5GHz
Frequency Specified Noise Filters	For 5GHz Band	BLF03VK*	0201 (0603)	1.2	60Ω to 220Ω

		Series	Size Code inch (mm)	Max. Rated Current (A)	Impedance at 100MHz (Rated Current)
For General Band Noise	Large Current Type Power Lines Type	BLT5BPT*	2020 (5050)	11	68Ω (11A)

Noise Suppression Filters (Feed Through Chip EMI Filters)

	Series	Size Code inch (mm)	Max. Rated Current (mA)	Capacitance
Universal Type [Power Lines/Signal Lines]	NFE31PT	1206 (3216)	6000	22pF to 2200pF
	NFE61PT	2706 (6816)	2000	33pF to 4700pF

Noise Suppression Filters (Chip LC Filters)

	Series	Size Code inch (mm)	Max. Rated Current (mA)	Nominal Cut-off Frequency
Signal Lines Type	NFL18ST	0603 (1608)	-	50MHz to 500MHz
	NFL18SP	0603 (1608)	-	150MHz to 500MHz
	NFL21SP	0805 (2012)	-	10MHz to 500MHz
	NFA18SL (4 circuits array)	0603 (1608)	-	50MHz to 480MHz
	NFA18SD (4 circuits array)	0603 (1608)	-	180MHz to 200MHz
	NFA21SL (4 circuits array)	0805 (2012)	-	50MHz to 330MHz
	NFW31SP	1206 (3216)	-	10MHz to 500MHz

Noise Suppression Filters (Chip EMIFIL)

	Series	Size Code inch (mm)	Max. Rated Current (mA)	Impedance at 900MHz	Impedance at 1.7GHz
For Audio Lines	**NFZ03SG_10**	0201 (0603)	305	330Ω to 1600Ω	400Ω to 1200Ω
	NFZ15SG_10	0402 (1005)	500	770Ω to 4600Ω	900Ω to 1800Ω
	NFZ15SG_11	0402 (1005)	1100	100Ω to 330Ω	160Ω to 540Ω

	Series	Size Code inch (mm)	Max. Rated Current (mA)	Impedance at 100MHz	Impedance at 900MHz
For Audio Lines	**NFZ15SF_10**	0402 (1005)	-	1000Ω	-
	NFZ15SR_10	0402 (1005)	-	200Ω to 500Ω	1500Ω to 3500Ω
	NFZ18SM_10*	0603 (1608)	-	120Ω to 700Ω	-
	NFZ2MSM_10	0806 (2016)	-	100Ω to 600Ω	-
	NFZ32SW_10	1210 (3225)	-	300Ω to 900Ω	-

	Series	Size Code inch (mm)	Max. Rated Current (mA)	Impedance at 10MHz
For Audio Lines	**NFZ2MSD_10***	0806 (2016)	-	15Ω to 130Ω

	Series	Size Code inch (mm)	Max. Rated Current (mA)	Impedance at 1MHz
For LED Lighting Equipments	**NFZ5BBW_LN10***	2020 (5050)	4000	2.9Ω to 140Ω
	NFZ2HBM_10	1008 (2520)	1200	1.5Ω to 60Ω
	NFZ32BW_10*	1210 (3225)	2550	3.6Ω to 880Ω
	NFZ32BW_11*	1210 (3225)	2900	3.3Ω to 150Ω

* The derating of rated current is required for some items according to the operating temperature.
For automotive grade products, please refer to the catalog C51E, "EMI Suppression Filters (for DC)/Chip Inductors for Automotive."

Noise Suppression Filters (Chip Common Mode Choke Coils/ Chip Common Mode Noise Filters)

		Series	Size Code inch (mm)	Max. Rated Current (mA)	Common Mode Impedance at 100MHz
Signal Lines Type	For Audio Lines	DLM11GN	0504 (1210)	-	600Ω
	For Ultra-High-Speed Signal Lines	NFG0NCN (3 Lines)	03025 (0806)	-	25Ω
		DLM0QSN	025020 (0605)	-	50Ω to 90Ω
		DLM0QSB	025020 (0605)	-	12Ω to 35Ω
		DLM0NSN	03025 (0806)	-	50Ω to 90Ω
		DLM0NSM	03025 (0806)	-	90Ω
		DLM0NSB	03025 (0806)	-	12Ω to 28Ω
		DLM11SN	0504 (1210)	-	45Ω to 90Ω
		NFP0QHB	025020 (0605)	-	-
		NFP0QSB	025020 (0605)	-	(90Ω)
		DLP0QSA	025020 (0605)	-	7Ω to 35Ω
		DLP0NSC	03025 (0806)	-	28Ω to 90Ω
		DLP0NSN	03025 (0806)	-	35Ω to 120Ω
		DLP0NSA	03025 (0806)	-	7Ω to 15Ω
		DLP11SN	0504 (1210)	-	67Ω to 330Ω
		DLP11SA	0504 (1210)	-	35Ω to 90Ω
		DLP11RN	0504 (1210)	-	45Ω
		DLP11RB	0504 (1210)	-	15Ω to 40Ω
		DLP11TB	0504 (1210)	-	80Ω
		DLP31SN	1206 (3216)	-	120Ω to 550Ω
		DLP1NDN (2 circuits array)	05025 (1506)	-	35Ω to 90Ω
		DLP2ADA (2 circuits array)	0804 (2010)	-	35Ω to 90Ω
		DLP2ADN (2 circuits array)	0804 (2010)	-	67Ω to 280Ω
		DLP31DN (2 circuits array)	1206 (3216)	-	90Ω to 440Ω
		DLW21S	0805 (2012)	-	67Ω to 920Ω
		DLW21H	0805 (2012)	-	67Ω to 180Ω
		DLW31S	1206 (3216)	-	90Ω to 2200Ω
Universal Type [Power Lines/Signal Lines]		DLW44S*	1515 (4040)	3100	(100Ω) to (2400Ω)
		DLW5AH/DLW5BS*	2014 / 2020 (5036) / (5050)	5000	(190Ω) to (4000Ω)
		DLW5AT*/DLW5BT*	2014 / 2020 (5036) / (5050)	6000	(50Ω) to (2700Ω)

* The derating of rated current is required for some items according to the operating temperature.
For automotive grade products, please refer to the catalog C51E, "EMI Suppression Filters (for DC)/Chip Inductors for Automotive."

Continued on the following page.↗

	Series	Size Code inch (mm)	Max. Rated Current (A)	Common Mode Impedance at 10MHz
Large Current Type for Automotive Available	PLT5BPH*	2020 (5050)	5.6	100Ω to 500Ω
	PLT10HH*	-	18	45Ω to 1000Ω

	Series	Size Code inch (mm)	Max. Rated Current (mA)	Common Mode Impedance at 100MHz
Large Current Type for Automotive Available	UCMH0907	3527 (9070)	5000	(700Ω)

Noise Suppression Filters (Block Type)

		Series	Height (mm)	Rated Voltage (Vdc)	Rated Current (A)
Power Lines Type	SMD Type	BNX022*	3.1	50	20
		BNX023*	3.1	100	20
		BNX024*	3.5	50	20
		BNX025*	3.5	25	20
		BNX026*	3.5	50	20
		BNX027*	3.5	16	20
		BNX028*	3.5	16	20
		BNX029*	3.5	6.3	20
	Lead Type	BNX002	12.5 max.	50	10
		BNX003	12.5 max.	150	10
		BNX005	13.0 max.	50	15
		BNX012*	8.5 max.	50	15
		BNX016*	8.5 max.	25	15

* The derating of rated current is required for some items according to the operating temperature.
For automotive grade products, please refer to the catalog C51E, "EMI Suppression Filters (for DC)/Chip Inductors for Automotive."

ESD Protection Devices

Support ESD protection for various kinds of electronic devices.

Silicon ESD Protection Devices LXES_T Series

Applying accumulated design technology for excellent ESD suppression performance.



Noise Suppression Filters (Lead Type), Others

	Series				
Lead Type EMIFIL	BLL18AG	BL01	BL02	BL03	DSS1
EMIGUARD	VFC2H				
Common Mode Choke Coils	PLT09H	PLT10HN*			

* The derating of rated current is required for some items according to the operating temperature.

Detailed Catalogs

For more details, please refer to our printed catalogs and the PDF catalogs on our website.



- EMI Suppression Filters (Lead Type EMIFIL) Cat. No. C30E
- EMI Suppression Filters (for DC)/Chip Inductors for Automotive Cat. No. C51E
- Noise Suppression by EMIFIL Digital Equipment Application Manual Cat. No. C33E
- Noise Suppression by EMIFIL Application Guide Application Manual Cat. No. C35E
- Application Manual for Power Supply Noise Suppression and Decoupling for Digital ICs Cat. No. C39E

Inductors (Coils)

Broad Lineup of Chip Inductors and Power Inductors

Summary

Murata's chip inductors are optimally designed, making full use of multiple construction techniques, such as the multilayer construction technique, film construction technique, and the wire wound construction technique according to the application. We offer an extensive lineup of inductors for power supplies to high frequency.
In addition, newly adopted metal alloy material has extended the power inductor lineup.

Lineup

●Inductors for Power Lines ●RF Inductors
●General Circuit Inductors ●Variable Inductors

Online design support tool: SimSurfing

You can view inductor characteristics and select appropriate power inductors for DC-DC converters



https://ds.murata.co.jp/simsurfing/

Inductors for Power Lines

Main Type:
▪ Wound Metal Alloy ▪ Multilayer Type ▪ Wound Ferrite Core

We have an extensive lineup of inductors covering a wide range of sizes from 1.6 mm x 0.8 mm to 12 mm square, which are manufactured using multiple techniques that include metal alloy wire wound construction technique and ferrite multilayer technique. We offer the optimum inductors for a wide range of applications including wearable devices, smartphones, medical applications, industrial electronics, and on board devices.

Structure	Description	Series
Wound Metal Alloy	Supports high current by using metal materials in which magnetic saturation does not occur so easily. This product can be used for a wide range of high current power circuits from smart phones to industrial electronics and automotive device applications.	DFEC/DFES series FDSD series
Multilayer Type	The features of this product is its small size and low profile. For example, 2012 or smaller footprint and 0.6mm height. This is ideal for low power circuits, including wearable devices and smartphones.	LQM series
Wound Ferrite Core	A feature of this product is the extensive lineup which supports an inductance of 100 uH or more. It is suitable for step-up power supply circuits in backlights, and choke applications.	LQH series DEM series

Recommended Lineup (General)

List of inductance values



List of rated current values



Recommended Lineup (For Automotive)

List of inductance values



List of rated current values



For Power Circuits (For General)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound Metal Alloy	0603 (1608)	DFE18SAN		DFE18SAN_E0	0.8	240nH to 1μH	2A to 4.2A
				DFE18SAN_G0	1.0	240nH to 1μH	2.1A to 4.9A
		DFE18SBN		DFE18SBN_E0	0.8	470nH to 1μH	1.9A to 3.1A
Multilayer Type		LQM18PN		LQM18PN_B0	0.4	1.5μH	600mA
				LQM18PN_C0	0.55	470nH to 2.2μH	700mA to 850mA
				LQM18PN_D0	0.75	2.5μH	700mA
				LQM18PN_DH	0.75	2.2μH	650mA
				LQM18PN_F0	0.95	1μH	600mA
				LQM18PN_FH	0.95	470nH to 2.2μH	700mA to 1.4A
				LQM18PN_FR	0.95	220nH to 4.7μH	620mA to 1.25A
				LQM18PN_GH	1.0	1μH to 3.3μH	1.05A
				LQM18PW_CH	0.65	1μH to 2.5μH	750mA to 950mA
Wound Metal Alloy	0805 (2012)	DFE2012		DFE201208S	0.8	470nH to 2.2μH	1.8A to 4A
				DFE201210S	1.0	470nH to 2.2μH	2.1A to 4.8A
				DFE201210U	1.0	240nH to 2.2μH	2A to 6.5A
Multilayer Type		LQM21PN		LQM21PN_C0	0.55	470nH to 2.2μH	600mA to 1.1A
				LQM21PN_CA	0.65	2.2μH	1.05A
				LQM21PN_CH	0.55	470nH to 2.2μH	1.05A to 1.6A
				LQM21PN_EH	0.8	240nH to 2.2μH	1.1A to 2.8A
				LQM21PN_G0	1.0	470nH to 3.3μH	800mA to 1.3A
				LQM21PN_GC	1.0	1μH to 2.2μH	800mA to 900mA
				LQM21PN_GH	1.0	470nH to 4.7μH	1A to 2.4A
				LQM21PN_GR	1.0	1μH to 4.7μH	800mA to 1.3A
				LQM21PN_GS	1.0	2.2μH to 4.7μH	750mA to 950mA
Wound Metal Alloy	0806 (2016)	DFE2016		DFE201610C	1.0	560nH to 2.2μH	1.5A to 2.8A
				DFE201610E	1.0	240nH to 10μH	1A to 6.3A
				DFE201610P	1.0	240nH to 2.2μH	2A to 5.4A
				DFE201610R	1.0	470nH to 2.2μH	1.6A to 3A
				DFE201612C	1.2	470nH to 2.2μH	1.6A to 3.4A
				DFE201612E	1.2	240nH to 4.7μH	1.8A to 6.6A
				DFE201612P	1.2	240nH to 2.2μH	2.1A to 6.5A
				DFE201612R	1.2	470nH to 2.2μH	1.7A to 3.5A
Wound Ferrite Core		LQH2MCN		LQH2MCN_02	0.95	1μH to 82μH	90mA to 485mA
				LQH2MCN_52	0.7	1μH to 22μH	130mA to 595mA
		LQH2MPN		LQH2MPN_GR	0.95	330nH to 82μH	210mA to 2.2A
Multilayer Type		LQM2MPN		LQM2MPN_DH	0.7	2.2μH	1.27A
				LQM2MPN_EH	0.8	240nH to 2.2μH	1.1A to 4.1A
				LQM2MPN_G0	1.0	470nH to 4.7μH	1.1A to 1.6A
				LQM2MPN_GH	1.0	160nH to 2.2μH	1.3A to 5A

Continued on the following page. ↗

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound Metal Alloy	1008 (2520)	DFE2520		DFE252007F	0.7	470nH to 4.7μH	1.2A to 3.3A
				DFE252008C	0.8	470nH to 4.7μH	1.1A to 3A
				DFE252008U	0.8	470nH to 10μH	1A to 4.5A
				DFE252010C	1.0	470nH to 10μH	1A to 3.5A
				DFE252010F	1.0	220nH to 10μH	1.7A to 7.2A
				DFE252010P	1.0	330nH to 4.7μH	1.7A to 5.7A
				DFE252010R	1.0	1μH to 4.7μH	1.4A to 3A
				DFE252012C	1.2	470nH to 10μH	1A to 3.8A
				DFE252012F	1.2	330nH to 10μH	1.4A to 7.6A
				DFE252012P	1.2	330nH to 4.7μH	2A to 6.6A
				DFE252012R	1.2	1μH to 4.7μH	1.7A to 3.4A
Wound Ferrite Core		LQH2HPN		LQH2HPN_DR	0.6	470nH to 22μH	270mA to 1.67A
				LQH2HPN_GR	1.0	470nH to 100μH	210mA to 2.9A
				LQH2HPN_JR	1.2	470nH to 22μH	540mA to 3.5A
Multilayer Type		LQM2HPN		LQM2HPN_CH	0.55	240nH to 2.2μH	850mA to 2.55A
				LQM2HPN_E0	0.8	560nH	1.5A
				LQM2HPN_EH	0.8	240nH to 2.2μH	1.3A to 4.5A
				LQM2HPN_G0	1.0	470nH to 4.7μH	1.1A to 1.8A
				LQM2HPN_GC	1.0	1μH to 4.7μH	800mA to 1.5A
				LQM2HPN_GH	1.0	240nH to 2.2μH	1.5A to 5A
				LQM2HPN_GS	1.0	2.2μH to 4.7μH	1A to 1.1A
				LQM2HPN_J0	1.2	1μH to 3.3μH	1A to 1.5A
				LQM2HPN_JH	1.2	470nH to 2.2μH	1.5A to 3.2A
Wound Ferrite Core	3mm square	DEM28/DEM35		DEM2812C	1.2	470nH to 12μH	760mA to 3.1A
				DEM2815C	1.5	470nH to 15μH	800mA to 3.9A
				DEM2818C	1.8	470nH to 12μH	1A to 4.7A
				DEM3512C	1.2	680nH to 22μH	530mA to 2.5A
				DEM3518C	1.8	560nH to 22μH	880mA to 3.4A
		LQH3NPN		LQH3NPN_GR	1.0	470nH to 250μH	140mA to 2.82A
				LQH3NPN_JR	1.2	680nH to 47μH	570mA to 2.86A
				LQH3NPN_ME	1.5	1μH to 100μH	430mA to 3A
Multilayer Type	1206 (3216)	LQM31PN		LQM31PN_00	0.95	470nH to 4.7μH	700mA to 1.4A
Wound Metal Alloy	1210 (3225)	DFE3225		DFE322510C	1.0	470nH to 10μH	1A to 3.8A
				DFE322512C	1.2	470nH to 10μH	1.2A to 4.7A
				DFE322512F	1.2	330nH to 10μH	1.7A to 8.5A
Wound Ferrite Core		LQH32P		LQH32PB_N0	1.7	470nH to 120μH	200mA to 3.4A
				LQH32PB_NC	1.7	470nH to 22μH	650mA to 4.4A
				LQH32PN_N0	1.7	470nH to 120μH	200mA to 3.4A
				LQH32PN_NC	1.7	470nH to 22μH	650mA to 4.4A
Multilayer Type		LQM32PN		LQM32PN_G0	1.0	1μH	1.8A
				LQM32PN_GC	1.0	1μH	2.2A

Continued on the following page. ↗

Inductors for Power Lines

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound Metal Alloy	4mm square	FDSD04		FDSD0412	1.2	330nH to 4.7μH	2.5A to 7.5A
				FDSD0415	1.5	220nH to 4.7μH	2.9A to 12A
				FDSD0420	2.0	330nH to 10μH	2.5A to 11A
				FDSD0420W	2.0	15μH to 22μH	1.5A to 1.9A
Wound Ferrite Core		LQH44PN		LQH44PN_GR	1.0	680nH to 47μH	410mA to 2.5A
				LQH44PN_J0	1.2	1μH to 47μH	380mA to 2A
				LQH44PN_P0	1.8	1μH to 22μH	800mA to 2.95A
		LQH43P		LQH43PB_26	2.8	1μH to 220μH	240mA to 3.4A
				LQH43PN_26	2.8	1μH to 220μH	240mA to 3.4A
		DEM4518		DEM4518C	1.8	1.2μH to 22μH	1A to 3.5A
Wound Ferrite Core	5mm square	LQH5BP		LQH5BPB_T0	2.2	470nH to 22μH	1.4A to 7.7A
				LQH5BPN_38	4.0	1μH to 150μH	650mA to 7A
				LQH5BPN_T0	2.2	470nH to 22μH	1.4A to 7.7A
		D52LC/D53LC		D52LC	2.0	1.2μH to 100μH	260mA to 2.44A
				D53LC	3.0	1.1μH to 220μH	350mA to 3.87A
Wound Metal Alloy		FDV05		FDV0530S	3.0	0.12μH to 2.2μH	4.5A to 18A
		FDSD05		FDSD0512	1.2	1μH to 6.8μH	2.3A to 6.1A
				FDSD0515	1.5	1μH to 4.7μH	3.2A to 7A
				FDSD0518	1.8	680nH to 10μH	2.7A to 9A
Wound Ferrite Core	6 to 9mm square	DG60		DG6028C	2.8	1μH to 22μH	1.7A to 5.8A
				DG6045C	4.5	1μH to 100μH	900mA to 9.5A
				DG6050C	5.0	1.2μH to 100μH	1.2A to 9.8A
		D63		D63LCB	3.0	1μH to 150μH	440mA to 4.52A
		DS75LC		DS75LC	5.0	1μH to 470μH	430mA to 9.2A
		DEM80		DEM8030C	3.0	2.2μH to 47μH	1.3A to 6.2A
				DEM8040C	4.0	1.5μH to 33μH	2.4A to 10A
				DEM8045C	4.5	1.5μH to 47μH	2.1A to 11.2A
		DG80		DG8040C	4.0	1μH to 100μH	1.3A to 10.4A
Wound Metal Alloy		FCUL05		FCUL0530	3.0	360nH to 470nH	16A to 18A
		FDSD06		FDSD0630	3.0	680nH to 10μH	5.4A to 17A
		FCUL06		FCUL0624	2.4	220nH to 470nH	17A to 24A
				FCUL0630	3.0	120nH to 680nH	15A to 32A
		FDV05/FDV06		FDV0530	3.0	110nH to 4.7μH	3.6A to 19.6A
				FDV0618	1.8	240nH to 3.3μH	4.1A to 14A
				FDV0620	2.0	200nH to 4.7μH	3.5A to 16.2A
				FDVE0630	3.0	160nH to 10μH	3.1A to 20.7A
				FDVE0640	4.0	1.5μH to 4.7μH	5A to 8.2A
		FDUE06		FDUE0630	3.0	120nH to 240nH	27A to 36A
				FDUE0640	4.0	150nH to 420nH	22A to 33A
				FDUE0650	5.0	600nH to 1μH	16A to 18A

Continued on the following page. ↗

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound Ferrite Core	10mm square and over	DEM10050		DEM10050C	5.0	1.5μH to 33μH	3.5A to 15.3A
				DEM10050C_DD	5.0	1.5μH to 33μH	3.5A to 15.3A
		DS10/DS12		DS104C2	4.8	1.1μH to 120μH	970mA to 11.7A
				DS106C2	6.8	1.2μH to 330μH	690mA to 12A
				DS126C2	6.8	1.7μH to 680μH	580mA to 11.8A
Wound Metal Alloy		FDA10/FDA12		FDA1055	5.5	560nH to 5.6μH	8A to 27.7A
				FDA1254	5.4	680nH to 8μH	9.1A to 29.1A
		FDUE10		FDUE1040D	4.0	220nH to 1μH	18A to 32A
		FDVE10		FDVE1040	4.0	1.5μH to 10μH	6.1A to 14.6A
		FCUL10		FCUL1040	4.0	180nH to 420nH	34A to 53A
				FCUL1060	6.0	360nH to 560nH	34A to 41A
		FDUE12		FDUE1245	4.5	500nH to 2.2μH	17A to 30A
				FDUE1260	6.0	450nH	34A

For Choke Circuits (For General)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound Ferrite Core	0402 (1005)	LQW15DN		LQW15DN_00	0.7	10μH to 15μH	100mA to 120mA
Multilayer Type	0603 (1608)	LQM18FN		LQM18FN_00	0.9	1μH to 10μH	50mA to 150mA
	0805 (2012)	LQM21DN		LQM21DN_00	1.05	1μH to 47μH	7mA to 60mA
		LQM21FN		LQM21FN_00	1.45	1μH to 47μH	7mA to 220mA
				LQM21FN_70	1.45	4.7μH to 10μH	100mA to 120mA
				LQM21FN_80	1.45	4.7μH to 10μH	100mA to 120mA
Wound Ferrite Core	1206 (3216)	LQH31CN		LQH31CN_03	2.0	120nH to 100μH	80mA to 970mA
	1210 (3225)	LQH32CN		LQH32CN_23	2.2	1μH to 560μH	60mA to 800mA
				LQH32CN_33	2.2	150nH to 10μH	450mA to 1.45A
				LQH32CN_53	1.7	1μH to 100μH	100mA to 1A
		LQH32DN		LQH32DN_23	2.2	1μH to 560μH	60mA to 800mA
				LQH32DN_53	1.7	1μH to 100μH	100mA to 1A
	4mm square	LQH43CN		LQH43CN_03	2.8	1μH to 470μH	90mA to 1.08A
				LQH43CN_33	2.8	560nH to 3.9μH	1.6A to 2.95A
	5mm square	LQH55DN		LQH55DN_03	5.0	120nH to 10mH	50mA to 6A
	6 to 9mm square	LQH66SN		LQH66SN_03	5.0	270nH to 10mH	50mA to 6A

For Power Circuits (Infotainment)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Multilayer Type	0603 (1608)	LQM18PZ		LQM18PZ_CH	0.6	1μH to 2.5μH	750mA to 950mA
				LQM18PZ_DH	0.75	2.2μH	650mA
				LQM18PZ_FH	0.95	2.2μH	700mA
	0805 (2012)	LQM21PZ		LQM21PZ_C0	0.55	470nH to 2.2μH	600mA to 1.1A
				LQM21PZ_G0	1.0	470nH to 3.3μH	800mA to 1.3A
				LQM21PZ_GC	1.0	1μH to 2.2μH	800mA to 900mA
				LQM21PZ_GR	1.0	1μH to 4.7μH	800mA to 1.3A
Wound Metal Alloy	0806 (2016)	DFE2016		DFE201612P_D	1.2	150nH to 2.2μH	1.7A to 6.2A
Wound Ferrite Core		LQH2MPZ		LQH2MPZ_GR	0.95	330nH to 82μH	210mA to 2.2A
Multilayer Type		LQM2MPZ		LQM2MPZ_G0	1.0	470nH to 4.7μH	1.1A to 1.6A
				LQM2MPZ_JH	1.2	100nH	4A
Wound Ferrite Core	1008 (2520)	LQH2HPZ		LQH2HPZ_DR	0.6	470nH to 22μH	270mA to 1.67A
				LQH2HPZ_GR	1.0	470nH to 22μH	460mA to 2.9A
				LQH2HPZ_JR	1.2	470nH to 22μH	540mA to 3.5A
Multilayer Type		LQM2HPZ		LQM2HPZ_E0	0.8	560nH	1.5A
				LQM2HPZ_G0	1.0	470nH to 4.7μH	1.1A to 1.8A
				LQM2HPZ_GC	1.0	1μH to 4.7μH	800mA to 1.5A
				LQM2HPZ_GS	1.0	2.2μH to 4.7μH	1A to 1.1A
				LQM2HPZ_J0	1.2	1μH to 3.3μH	1A to 1.5A
Wound Metal Alloy		DFE2520		DFE252012P_D	1.2	330nH to 10μH	1.1A to 6A
Wound Ferrite Core	3mm square	LQH3NPZ		LQH3NPZ_GR	1.0	470nH to 47μH	460mA to 2.82A
				LQH3NPZ_JR	1.2	680nH to 47μH	570mA to 2.86A
				LQH3NPZ_ME	1.5	1μH to 100μH	430mA to 3A
Wound Metal Alloy	1210 (3225)	DFE3225		DFE322520F_D	2.0	1μH to 4.7μH	3.4A to 7.5A
Wound Ferrite Core		LQH32PZ		LQH32PZ_N0	1.7	470nH to 120μH	200mA to 3.4A
				LQH32PZ_NC	1.7	470nH to 22μH	650mA to 4.4A
	4mm square	LQH44PZ		LQH44PZ_GR	1.0	680nH to 47μH	410mA to 2.5A
		LQH43PZ		LQH43PZ_26	2.8	1μH to 220μH	240mA to 3.4A
	5mm square	LQH5BPZ		LQH5BPZ_T0	2.2	470nH to 22μH	1.4A to 7.7A
	6 to 9mm square	DEM80		DEM8045C_Z	4.5	1.5μH to 47μH	2.1A to 11.2A

For Power Circuits (Powertrain)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Multilayer Type	0603 (1608)	**LQM18PH**		**LQM18PH_FR**	0.95	220nH to 4.7μH	620mA to 1.25A
	0805 (2012)	**LQM21PH**		**LQM21PH_GO**	1.0	0.47μH to 0.54μH	1.3A
				LQM21PH_GC	1.0	1.0μH to 2.2μH	800mA to 1A
Wound Metal Alloy	0806 (2016)	**DFE2MCAH**		**DFE2MCAH_J0**	1.2	0.15μH to 2.2μH	1.7A to 6.1A
	1008 (2520)	**DFE2HCAH**		**DFE2HCAH_J0**	1.2	330nH to 2.2μH	2.5A to 5.8A
Wound Ferrite Core	1210 (3225)	**LQH32PH**		**LQH32PH_N0**	1.7	470nH to 10μH	750mA to 3.4A
				LQH32PH_NC	1.7	470nH to 22μH	650mA to 4.4A
	4mm square	**LQH44PH**		**LQH44PH_PR**	1.8	1μH to 220μH	330mA to 4.3A
		LQH43PH		**LQH43PH_26**	2.8	1μH to 220μH	240mA to 3.4A
	5mm square	**LQH5BPH**		**LQH5BPH_T0**	2.2	0.47μH to 47μH	850mA to 7.7A

For Choke Circuits (Infotainment)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound Ferrite Core	1210 (3225)	**LQH32D**		**LQH32DZ_23**	2.2	1μH to 470μH	60mA to 800mA
				LQH32DZ_53	1.7	1μH to 100μH	100mA to 1A

For Choke Circuits (Powertrain)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound Ferrite Core	1210 (3225)	**LQH32C**		**LQH32CH_23**	2.2	1μH to 22μH	250mA to 800mA
				LQH32CH_33	2.2	150nH to 10μH	450mA to 1.45A
				LQH32CH_53	1.7	1μH to 22μH	250mA to 1A
		LQW32F		**LQW32FT_0H**	2.5	10μH to 47μH	500mA to 700mA

RF Inductors



Main Type:
▪ Film Type ▪ Wire Wound Type ▪ Multilayer Type

An RF inductor is used for matching applications and choke applications in the RF section which has wireless communication functions. By using three characteristic methods, you can select the optimum series for the intended application. For a smartphone or a module film type LQP series which is compact and also has high Q characteristics is optimum. For an RF inductor of size 1005 mm or more, the high Q wound type LQW series which has a large rated current value is recommended for use in a base station or STB. While the multilayer LQG series has a good balance between cost and performance, it is recommended for a wide range of automotive applications, based on our market achievements over many years. Products that are suitable for choke circuits using magnetic materials, such as the LQW_CN series, LQW_H series and other series are also available for power lines. You can select the optimum series from our lineup, based on either the intended application or the relationship between the size and Q characteristics.

General (0.8×0.4 mm or less)

Lineup list



General (1.0×0.5 mm or more)

Lineup list



For Automotive

Lineup list



RF Circuits (0.8 x 0.4 mm or less)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound non-magnetic type	0201 (0603)	**LQW03A**		**LQW03AW_00**	0.45	1nH to 15.5nH	230mA to 900mA
	03019 (0805)	**LQW04A**		**LQW04AN_00**	0.45	0.8nH to 33nH	140mA to 1.8A
				LQW04AN_10	0.45	36nH to 56nH	180mA to 200mA
				LQW04AN_20	0.45	36nH to 56nH	120mA to 155mA
Film type	008004 (0201)	**LQP01**		**LQP01HQ**	0.213	0.3nH to 2.7nH	200mA to 500mA
	01005 (0402)	**LQP02**		**LQP02HQ_02**	0.32	0.2nH to 56nH	100mA to 1A
				LQP02TQ_02	0.22	0.2nH to 22nH	120mA to 990mA
				LQP02TN_02	0.22	0.2nH to 39nH	90mA to 320mA
	0201 (0603)	**LQP03**		**LQP03HQ_02**	0.42	0.5nH to 470nH	50mA to 1.1A
				LQP03TQ_02	0.32	0.6nH to 110nH	70mA to 1A
				LQP03TN_02	0.33	0.6nH to 270nH	60mA to 850mA
				LQP03TG_02	0.33	0.1nH to 120nH	80mA to 850mA
				LQP03PN_02	0.33	2.2nH to 4.7nH	900mA to 1.4A

RF Circuits (1.0 x 0.5 mm or more)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound non-magnetic type	0402 (1005)	**LQW15A**		**LQW15AN_00**	0.6	1.5nH to 120nH	110mA to 1A
				LQW15AN_10	0.6	1.3nH to 8.4nH	640mA to 1.2A
				LQW15AN_80	0.6	1.3nH to 75nH	320mA to 3.15A
				LQW15AW_80	0.66	51nH to 220nH	220mA to 480mA
	0603 (1608)	**LQW18A**		**LQW18AN_00**	1.0	2.2nH to 470nH	75mA to 850mA
				LQW18AN_10	1.0	2.2nH to 33nH	550mA to 1.4A
				LQW18AN_80	1.0	2.2nH to 390nH	190mA to 3.2A
				LQW18AS_00	1.0	1.2nH to 390nH	100mA to 700mA
				LQW18AS_0C	1.0	1.6nH to 390nH	100mA to 700mA
	0806 (2016)	**LQW2B**		**LQW2BAN_00**	1.52	3.2nH to 200nH	750mA to 3.8A
				LQW2BAS_00	1.52	2.7nH to 1μH	170mA to 910mA
				LQW2BHN_03	1.78	3.3nH to 470nH	160mA to 1.32A
				LQW2BHN_13	1.78	2.7nH to 27nH	900mA to 1.9A
	1008 (2520)	**LQW2U**		**LQW2UAS_00**	2.03	12nH to 4.7μH	260mA to 1A
				LQW2UAS_0C	2.03	12nH to 8.2μH	170mA to 1A
	1206 (3216)	**LQW31H**		**LQW31HN_03**	2.0	8.8nH to 100nH	230mA to 750mA
Film type	0402 (1005)	**LQP15M**		**LQP15MN_02**	0.45	1nH to 33nH	60mA to 400mA
	0603 (1608)	**LQP18M**		**LQP18MN_02**	0.6	1.3nH to 100nH	50mA to 300mA
Multilayer Type	0402 (1005)	**LQG15H**		**LQG15HN_02**	0.55	1nH to 120nH	150mA to 1A
				LQG15HS_02	0.55	1nH to 270nH	110mA to 1A
	0603 (1608)	**LQG18H**		**LQG18HN_00**	0.95	1.2nH to 100nH	350mA to 1.1A

For Choke/Tuner Circuits (1.0 x 0.5 mm or more)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound Ferrite Core type	0402 (1005)	LQW15C		LQW15CN_00	0.6	18nH to 200nH	390mA to 1.4A
				LQW15CN_10	0.6	20nH to 3.3μH	130mA to 2.2A
	0402 (1005)	LQW15D		LQW15DN_00	0.7	10μH to 15μH	100mA to 120mA
	0603 (1608)	LQW18C		LQW18CN_00	0.95	4.9nH to 650nH	430mA to 2.6A
	0805 (2012)	LQW21H		LQW21HN_00	1.0	470nH to 2.2μH	75mA to 160mA
	1206 (3216)	LQH31H		LQH31HN_03	2.0	54nH to 880nH	180mA to 920mA

LC trap filter

Part number	Impedance (Ω Typ.)			Insertion Loss Characteristic (dB Typ.)			DC Resistance Max.(Ω)	Rated Current (mA)	Self Resonant Frequency (GHz Typ.)
	at 2.40GHz	at 2.44GHz	at 2.50GHz	at 2.40GHz	at 2.44GHz	at 2.50GHz			
LQZ02HQ242A02	460	600	345	15.0	15.7	13.0	0.55	200	2.44

For RF Circuits (Infotainment)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound non-magnetic type	0402 (1005)	LQW15A		LQW15AN_0Z	0.6	1.5nH to 120nH	110mA to 1A
				LQW15AN_1Z	0.6	1.3nH to 8.4nH	640mA to 1.2A
				LQW15AN_8Z	0.6	1.3nH to 75nH	320mA to 3.15A
	0603 (1608)	LQW18A		LQW18AN_0Z	1.0	2.2nH to 470nH	75mA to 850mA
				LQW18AN_1Z	1.0	2.2nH to 33nH	550mA to 1.4A
				LQW18AN_8Z	1.0	2.2nH to 390nH	190mA to 3.2A
				LQW18AS_0Z	1.0	1.6nH to 390nH	100mA to 700mA
Film type	0201 (0603)	LQP03T		LQP03TN_Z2	0.33	0.6nH to 120nH	80mA to 850mA
Multilayer Type	0402 (1005)	LQG15H		LQG15HZ_02	0.55	1nH to 270nH	110mA to 1A
		LQG15W		LQG15WZ_02	0.6	0.7nH to 150nH	110mA to 1.2A

For RF Circuits (Powertrain)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Multilayer Type	0402 (1005)	LQG15H		LQG15HH_02	0.55	1nH to 270nH	110mA to 1A
		LQG15W		LQG15WH_02	0.6	0.7nH to 150nH	110mA to 1.2A
	0603 (1608)	LQG18H		LQG18HH_00	0.95	1.2nH to 270nH	200mA to 1.1A

For Choke/Tuner Circuits (Infotainment)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound Ferrite Core type	0402 (1005)	LQW15C		LQW15CN_0Z	0.6	18nH to 200nH	390mA to 1.4A
				LQW15CN_1Z	0.6	20nH to 560nH	300mA to 2.2A
	0603 (1608)	LQW18C		LQW18CN_0Z	0.95	4.9nH to 650nH	430mA to 2.6A
	1206 (3216)	LQH31H		LQH31HZ_03	2.0	54nH to 880nH	180mA to 920mA

General Circuit Inductors

Main Type:
▪ Multilayer Type ▪ Wire-wound Type ▪ 2in1 Type

We have an extensive lineup of general purpose inductors for a variety of circuits.
You can select an inductor to match your particular application. Wire-wound type LQH_M, LQH_N series are suitable for large inductance, multilayer type LQM_M, LQM_N series are suitable for small size.
In addition, we have the 2-in-1 type HEAWS series inductors for digital audio amplifiers.

General Purpose (For General)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound Ferrite Core type	03019 (0805)	LQW04CA		LQW04CA_00	0.55	60nH to 510nH	200mA to 620mA
	0402 (1005)	LQW15CA		LQW15CA_00	0.66	22nH to 2μH	130mA to 1.3A
	0603 (1608)	LQW18CA		LQW18CA_00	0.95	32nH to 580nH	450mA to 2.2A
	1206 (3216)	LQH31MN		LQH31MN_03	2.0	150nH to 100μH	45mA to 250mA
	1210 (3225)	LQH32MN		LQH32MN_23	2.2	1μH to 560μH	40mA to 445mA
	4mm square	LQH44NN		LQH44NN_03	4.5	510nH to 470μH	145mA to 4.5A
		LQH43M/N		LQH43MN_03	2.8	1μH to 1.5mH	40mA to 500mA
				LQH43NN_03	2.8	1μH to 2.4mH	25mA to 500mA
Multilayer Type	0402 (1005)	LQB15NN		LQB15NN_10	0.55	220nH to 560nH	300mA to 380mA
	0603 (1608)	LQB18NN		LQB18NN_10	0.95	220nH to 560nH	300mA to 450mA
		LQM18JN		LQM18JN_00	0.65	100nH to 160nH	550mA to 650mA
		LQM18NN		LQM18NN_00	0.95	47nH to 2.2μH	15mA to 50mA
	0805 (2012)	LQM21NN		LQM21NN_10	1.05	100nH to 4.7μH	30mA to 250mA

General Purpose (For Automotive Infotainment)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound Ferrite Core type	1210 (3225)	LQH32NZ		LQH32NZ_23	2.2	1μH to 470μH	45mA to 445mA
	4mm square	LQH43NZ		LQH43NZ_03	2.8	1μH to 2.4mH	25mA to 500mA
2in1 Type	10mm square and over	HEAWS		HEAWS	10.0	3.3uH to 10uH	5A to 8A

General Purpose (For Automotive Powertrain)

Structure	Size Code inch (mm)	Short Series Name/View		Series	Thickness (mm/max.)	Inductance Range	Rated Current Range
Wound Ferrite Core type	1210 (3225)	**LQH32NH**		**LQH32NH_23**	2.2	1μH to 560μH	40mA to 780mA
	4mm square	**LQH43NH**		**LQH43NH_03**	2.8	1μH to 2.2mH	30mA to 1.3A

Variable Inductors

Variable inductor products are coil products that allow the inductance to be easily varied by changing the position of the ferrite core in a threaded structure.
The interior is covered by a metal case that is magnetically shielded, while a resin molded structure protects the windings with a high degree of reliability.

5CCEG
6.5×5.9×6.0(H) mm MAX.

Supported inductance range: 0.05 to 2.7μH
Features
- High reliability that conforms to automotive standards
- Operating temperature range: -40°C to +85°C

Applications
- Ideal for use as RF matching transformers for car tuners

FSDVA
5.8×5.8×5.5(H) mm MAX.

Supported inductance range:
0.1 to 52mH(1 to 7 mH for corner sensor applications)
Features
- Resistant to mechanical stress
- Operating temperature range:
  Up to 20 mH (-40°C to +105°C)
  20 mH or more (-40°C to +85°C)
- Various reliability conditions guaranteed for 1,000 hours (evaluation performed up to 3,000 hours)
- Lead coplanarity guaranteed within 0.1 mm

5CCEG Series

Winding Connection (Bottom View)	Part Number	Test Frequency (MHz)	Resonance Capacitor Range (pF)	Unloaded Q
	#A1313AN-0001GGH=P3	100	11.4+3/-3%	72+/-20%
	#A1313AN-0002GRG=P3	100	11.4+5/-2%	61+/-20%
	#A1313AN-0003GRG=P3	100	11.4+2/-4%	54+/-20%
	#A1313AN-0004GGH=P3	100	11.7+3/-3%	72+/-20%

FSDVA Series

Winding Connection (Bottom View)	Part Number	Test Frequency (kHz)	Inductance Range (mH)	Unloaded Q
	**N1342JC-0143UG=P3**	252	4.4±3%	25 min.
	**N1342LE-0144BQE=P3**	252	2.5±5%	25 min.

DC-DC converters design assistant tool

No download necessary; available on web browsers.
We have released a design assistant tool to select inductors or capacitors for DC-DC converters efficiently.
Input converter work condition and click the calculation button; the ranking of efficiency with each inductor will be listed.

To use this tool, go to
https://ds.murata.co.jp/mpst

Detailed Catalogs

For more details, please refer to our printed catalogs and the PDF catalogs on our website.

- Chip Inductors (Chip Coils) Cat. No. O05E
- EMI Suppression Filters (for DC)/Chip Inductors for Automotive Cat. No. C51E

Resistors

Full lineup for various applications

Summary

Using Murata's ceramic processing technology and unique materials, we offer a series of resistor products.

Lineup

●High Voltage Resistors

https://www.murata.com/en-global/products/resistor

High Voltage Resistors

Featuring thick-film resistors, the Murata MHR series of high-voltage resistors is available in compact and thin SIP packages. Variants with small deviations are also available on request.



MHR03 Series



MHR04 Series



MHR06 Series

(in mm)

*The terminal pitch is an integral multiple of 2.54mm.

Series	Resistance (min.) (MΩ)	Resistance (max.) (MΩ)	Maximum Operating Voltage (Single Use) (kV)	Maximum Operating Voltage (Molded Use) (kV)	Rated Power (W)
MHR03	1	500 to 1000	2 to 8	3 to 14	0.3 to 1.0
MHR04	1	1000	3.5 to 10	10 to 18	0.6 to 1.4
MHR06	1	1000	3.5 to 10	10 to 20	0.8 to 1.6

Resistance 2 element type is also available.
For resistance value and ratio, please contact us.

Timing Devices

A stable timing source for microprocessors in various electronic devices

Summary

Murata's ceramic processing technology and unique piezoelectric material has led to the development of a range of small and thin ceramic timing devices that offer high oscillation frequency and remarkable oscillation tolerance.

Lineup

●MEMS Resonator ●Crystal Units ●Crystal Oscillators
●Ceramic Resonators CERALOCK



https://www.murata.com/en-global/products/timingdevice

IC Part Number - Timing Devices Search

Search for Timing Devices by IC part number or search for IC part number by Timing Devices on our website. It is also possible to search by either oscillating frequency or frequency range.



https://www.murata.com/simsurfing/

Detailed Catalogs

For more details, please refer to our printed catalogs and the PDF catalogs on our website.

▪ Ceramic Resonators (CERALOCK)	Cat. No. P16E
▪ Ceramic Resonator (CERALOCK) Application Manual	Cat. No. P17E
▪ Crystal Units/Crystal Oscillators	Cat. No. P79E

MEMS Resonator

The ultra small-sized and highly reliable resonator is realized with Murata's MEMS technology.
The small size makes the resonator suitable for a variety of applications such as miniature IoT devices, wireless modules, medical devices, and industrial equipment.
The resonator package is silicon based with low form factor which enables embedding with IC in over molded packages.

For Consumer/Industrial

WMRAG

(in mm)

Series	Frequency (kHz) 0 10 20 30 40 50 60 70	Frequency Tolerance (ppm) 0 20 40 60 80 100	Operating Temperature Range (°C)
WMRAG	32.768	±20	-40 to 125

Crystal Units

Crystals Unit utilize highly accurate frequency-based high-grade quartz crystal elements.
We offer a wide lineup of Crystal Units using Murata's proven package technology for small digital devices, automotive, etc.

For Consumer/Industrial



XRCTD XRCFD XRCMD XRCGB XRCHA XRCLH XRCLK

(in mm)

Series	Type	Seal	Frequency (MHz) 0 10 20 30 40 50 60	Frequency Tolerance (ppm) 0 20 40 60 80 100	Frequency Shift by Temperature (ppm max.)	Operating Temperature Range (°C)
XRCTD	MCR1210	Metal	32.0000 – 52.0000	±10	±10	-30 to 85
XRCFD	MCR1612	Metal	24.0000 – 29.9999	±10	±10	-20 to 70
XRCMD	MCR1612	Metal	30.0000 – 48.0000	±10	±10	-20 to 70
XRCGB-F-H	HCR2016	Resin	24.0000 – 25.0000	±10	±10	-20 to 70
			26.0000 – 32.0000	±10	±10	-30 to 85
XRCGB-F-P	HCR2016	Resin	16.0000 – 38.4000	±20	±20	-30 to 85
XRCGB-F-M	HCR2016	Resin	16.0000 – 32.0000	±30	±40	-30 to 85
			33.8688 – 50.0000	±45	±40	-30 to 85
XRCGB-F-L	HCR2016	Resin	16.0000 – 50.0000	±100	±50	-30 to 85
XRCHA-F-L	HCR2520	Resin	16.0000 – 20.0000	±100	±100	-30 to 85
XRCLH	TAS-5032F	Metal	10.0000 – 52.0000	±10	±15	-30 to 85
XRCLK	TSS-5032A	Seam	10.0000 – 52.0000	±10	±15	-30 to 85

For Automotive Applications



XRCHA-F-A XRCGE-F-A XRCGB-F-A XRCGB-F-C XRCGB-F-G

(in mm)

Series	Type	Seal	Frequency (MHz)	Frequency Tolerance (ppm)	Frequency Shift by Temperature (ppm max.)	Operating Temperature Range (°C)
XRCHA-F-A	HCR2520	Resin	16.0000 – 24.0000	±100	±100	-40 to 125
XRCGE-F-A	HCR2016	Resin	20.0000 – 23.9999	±30	±45	-40 to 125
			24.5454 – 27.6000	±15	±35	-40 to 125
XRCGB-F-A	HCR2016	Resin	24.0000 – 29.9999	±30	±35	-40 to 125
			30.0000 – 48.0000	±50	±65	-40 to 125
XRCGB-F-C	HCR2016	Resin	27.6000	±20	±20	-30 to 85
XRCGB-F-G	HCR2016	Resin	24.0000 – 48.0000	±30 ±45 ±100	±50	-40 to 85

Crystal Oscillators

We offer a lineup of Crystal Oscillators using highly reliable crystal units, and superior temperature compensation methods.

For Industrial Applications



XTCLH

(in mm)

Series	Type	VC Function	Frequency (MHz)	Initial Frequency Tolerance (ppm)	Frequency Shift by Temperature (ppm max.)	Frequency Aging (ppm max./year)	Operating Temperature Range (°C)
XTCLH_T	TTS14VSH	●	10.0000 – 50.0000	±0.5	±0.20	±0.5	-40 to 85
XTCLH_C	TTS14VCH	●	10.0000 – 50.0000	±0.5	±0.28	±0.5	-40 to 85

Ceramic Resonators CERALOCK

Wide product lineup of SMD and lead type versions for automotive and consumer applications.

MHz Chip Type for Automotive (Tight Frequency Tolerance)



CSTNR_GH5C CSTNE_GH5C CSTNE_VH3C

(in mm)

Series	Frequency (MHz)	Frequency Tolerance (%)	Frequency Shift by Temperature (% max.)	Operating Temperature Range (°C)
CSTNR_GH5C	4.00 – 7.99	±0.07	±0.13	-40 to 125
CSTNE_GH5C	8.00 – 13.99	±0.07	±0.13	-40 to 125
CSTNE_VH3C	14.00 – 20.00	±0.07	±0.13	-40 to 125

MHz Chip Type for Automotive (Standard Frequency Tolerance)



CSTCR_G_B



CSTNE_G_A



CSTNE_V_C

(in mm)

Series	Frequency (MHz) 0 10 20 30 40 50 60 70	Frequency Tolerance (%) 0 1	Frequency Shift by Temperature (% max.)	Operating Temperature Range (°C)
CSTCR_G_B	4.00 – 7.99	±0.5	±0.15	-40 to 125
CSTNE_G_A	8.00 – 13.99	±0.5	±0.20	-40 to 125
CSTNE_V_C	14.00 – 20.00	±0.5	±0.15	-40 to 125

MHz Chip Type for Consumer Electronics (Tight Frequency Tolerance)



CSTNR_GH5L



CSTNE_GH5L



CSTNE_VH3L

(in mm)

Series	Frequency (MHz) 0 10 20 30 40 50 60 70	Frequency Tolerance (%) 0 1	Frequency Shift by Temperature (% max.)	Operating Temperature Range (°C)
CSTNR_GH5L	4.00 – 7.99	±0.07	±0.11	-20 to 85
CSTNE_GH5L	8.00 – 13.99	±0.07	±0.11	-40 to 85
CSTNE_VH3L	14.00 – 20.00	±0.07	±0.11	-40 to 85

MHz Chip Type for Consumer Electronics (Standard Frequency Tolerance)



CSTCR_G



CSTNE_G



CSTNE_V

(in mm)

Series	Frequency (MHz) 0 10 20 30 40 50 60 70	Frequency Tolerance (%) 0 1	Frequency Shift by Temperature (% max.)	Operating Temperature Range (°C)
CSTCR_G	4.00 – 7.99	±0.5	±0.20	-20 to 80
CSTNE_G	8.00 – 13.99	±0.5	±0.20	-40 to 85
CSTNE_V	14.00 – 20.00	±0.5	±0.30	-40 to 85

MHz Lead Type for Consumer Electronics (Standard Frequency Tolerance)



CSTLS_G



CSTLS_X

(in mm)

Series	Frequency (MHz) 0 10 20 30 40 50 60 70	Frequency Tolerance (%) 0 1	Frequency Shift by Temperature (% max.)	Operating Temperature Range (°C)
CSTLS_G	3.40 – 10.00	±0.5	±0.20 (15pF) -0.40/+0.20 (47pF)	-20 to 80
CSTLS_X	16.00 – 70.00	±0.5	±0.20	-20 to 80

Filters

Broad lineup of Filters for video, audio, RF/Local, Duplexers, and Filters for IF

Summary

Using Murata's ceramic proccessing technology and unique materials, we offer miniaturized filters with excellent properties for advanced digital audio/visual systems and communication equipment.

Lineup

●Ceramic Filters CERAFIL (Filters and Discriminators)
●Crystal Filters ●SAW Filters for Mobile Communications
●Dielectric Filters GIGAFIL ●Chip Multilayer LC Filters



https://www.murata.com/en-global/products/filter

Ceramic Filters CERAFIL

CERAFIL 10.7MHz Chip Type

Small and lightweight filters for IF in communications or AV equipment using unique piezoelectric material.



SFECK / SFECV Series

(in mm)

Type	Series	3dB Bandwidth (kHz)		
		E	J	K
		330	150	110
High-reliability Type	SFECK10M7□	-	●	●
Standard Type	SFECV10M7□	-	●	●
Standard Type	SFECV15M0□	●	-	-

□ is filled with the letter designating the required 3dB bandwidth.



SFECF Series

(in mm)

Type	Series	3dB Bandwidth (kHz)				
		D	E	F	G	H
		350	330	280	230	180
Standard Type	SFECF10M7□	●	●	●	●	●

□ is filled with the letter designating the required 3dB bandwidth.

Ceramic Discriminators

In combination with ICs, this type obtains stable demodulation characteristics in a wide bandwidth.



CDSCB Series

(in mm)

Series	Center Frequency
CDSCB	10.700MHz±30kHz

The recommended part number depends on IC specifications. Please contact us with the IC part number to be applied.

Crystal Filters

Our original wafer-thin technology has made it possible to make highly reliable filters in various applications such as radio communication worldwide.



(in mm)

XDCAF / XDCAG / XDCAH Series

Series	Type	Frequency Range (MHz)	Number of Poles
XDCAF	TM7050F	20 to 80 [Fundamental] 70 to 150 [3rd overtone]	2
XDCAG	TM7050G		4
XDCAH	TM7050H		4

*Please be sure to consult with our sales representative or engineer if you require other center frequency.

SAW Filters for Mobile Communications

SAW Duplexers

Low loss, high attenuation performance, small size, highly selective pass band, chip size package



(in mm)

SAYEY Series

RF Filters

Low loss, high attenuation performance, small size, highly selective pass band, chip size package

Single Filter

(in mm)

SAFFB Series

Dual Filter



SAWEN Series



SAWFD Series

(in mm)

SAW Filters and SAW Duplexers may be used only in the following equipment:
Mobile phones, cordless telephones (except automobile telephone), smartphones, tablet PC, PC (including laptop/netPC), game machines, cameras (except for business use and for security), STB, electronic dictionaries, and digital audio instruments.
Please contact us for other usages.

Dielectric Filters GIGAFIL

This is a high frequency dielectric filter for Wi-Fi routers, accespoints, communication infrastructures of mobile phone base stations, for example.
It employs a unique plate construction which enables the filter to be compact and have a low profile.

TDF Series

	Series	Frequency Range (MHz) 100 1000 2000 3000 4000 5000 6000 7000	Number of Resonators	Input Power Range
RF/IF/Local Filter	**TDF**	2000 – 6000	2 to 5	1 to 10W*

*Power depends upon specifications.

Chip Multilayer LC Filters

Ultra-small and low-profile filters based on ceramic multilayer technology.

Band Pass Filters

LFB15 Series



LFB18 Series



LFB21 Series



LFB2H Series



LFB31 Series

(in mm)

Low Pass Filters

LFL15 Series



LFL18 Series



LFL21 Series

(in mm)

Detailed Catalogs

For more details, please refer to our printed catalogs and the PDF catalogs on our website.

- Ceramic Filters (CERAFIL)/Crystal Filters — Cat. No. P51E
- Ceramic Filters (CERAFIL) Application Manual — Cat. No. P11E

RF Components

Broad lineup of RF Components for RF/Local circuits in communications equipment

Summary

To enhance the technical advantages of communication equipment, Murata offers miniaturized, sophisticated components to meet the demands of many applications.

Lineup

- Antennas
- Baluns (Chip Multilayer and Wire Wound/Film type)
- Couplers (Chip Multilayer) ●Chip Multilayer Hybrid Dividers
- Chip Multilayer Diplexers
- Microwave Coaxial Connectors

Antennas

Antenna Coils

Rx 1D-ANT



(in mm)

SA3M08 Series

Series	Inductance (mH)	Q (Reference)
SA3M08	1.0 to 18.0	25

Rx 3D-ANT



SA3D12 Series



SA3D14 Series

(in mm)

Series		Inductance (mH)	Q (Reference)
SA3D12	X	1.0 to 6.3	20
	Y	1.0 to 6.3	20
	Z	1.0 to 9.0	20
SA3D14	X	1.0 to 6.3	20
	Y	1.0 to 6.3	20
	Z	1.0 to 9.0	20

Baluns

SMD baluns constructed with a copper conductor and ceramic material. Ideal for high-frequency applications. Small-size and low-loss baluns can be customized for balance impedance of 50Ω to 200Ω.

Chip Multilayer Type



LDB18 Series



LDB21 Series

LDM0Q Series

LDM15 Series



LDM18 Series

(in mm)

Film Type



DXP2AB Series

(in mm)

Wire Wound Type



DXW21B Series



DXW21H Series



B4F Series



B5F Series

B5FL Series

(in mm)

RF Components

Couplers

An ultra-small, low-profile directional coupler based on ceramic multilayer technology.
This coupler achieves ultra-small size, low insertion loss, and high isolation.

Chip Multilayer Type

LDC15 Series
LDJ15 Series



LDC18 Series
LDJ18 Series



LDC21 Series
LDJ21 Series

*It is available with Integrated LPF for **LDC21 Series**.

(in mm)

Chip Multilayer Hybrid Dividers

Power divider with a multilayer low pass filter in an ultra-compact package.



LDD18 Series



LDD21 Series

(in mm)

Chip Multilayer Diplexers

A diplexer branching low and high band.
Suitable for band-switching for dual-band system.

LFD15 Series



LFD18 Series



LFD21 Series



LFD2H Series

(in mm)

Microwave Coaxial Connectors

Microwave Coaxial Connectors with Switch

The coaxial connector with switch is very useful for characteristic measurement in cellular phones and microwave circuits.



MM8430-2610

MM8130-2600



MM8030-2610

MM8930-2600

MM8930-2620

MM8830-2600

(in mm)

Type	Receptacle Part Number	Frequency Rating (GHz)	Voltage Standing Wave Ratio	Standard Measurement Probe Part Number
SWD	**MM8430-2610**	to 6	1.2 max. (DC to 3GHz) 1.3 max. (3GHz to 6GHz)	**MM126320 MXHS83QE3000**
SWF	**MM8130-2600**	to 6	1.2 max. (DC to 3GHz) 1.3 max. (3GHz to 6GHz)	
SWG	**MM8030-2610**	to 11	1.2 max. (DC to 3GHz) 1.3 max. (3GHz to 6GHz) 1.5 max. (6GHz to 11GHz)	**MM126320 MXHQ87WJ3000**
SWH	**MM8930-2600**	to 6	1.2 max. (DC to 3GHz) 1.3 max. (3GHz to 6GHz)	**MM126515 MXHQ87PA3000**
SWH-2Way	**MM8930-2620**	to 6	1.2 max. (DC to 3GHz) 1.3 max. (3GHz to 6GHz)	**RF: MM126526 ANT: MM126517 RF: MXHQ87PN3000 ANT: MXHQ87PP3000**
SWJ	**MM8830-2600**	to 9	1.2 max. (DC to 8GHz) 1.3 max. (8GHz to 9GHz)	**MM126715 MXHQ87PK3000**

Nominal Impedance: 50Ω Rated Voltage: 30Vrms Temperature Range: -40 to 85°C

Multi Line Connectors

Multi line connectors transmit signals from board to board. The connectors can transmit not only digital signals but also RF signals.



MM3529-2700A06

MM3531-2701A06



MM3529-2700A10



MM3531-2701A10



MM3529-2700A14

MM3531-2700A14



MM3529-2700A20

MM3531-2700A20

(in mm)

Type	Receptacle Part Number	Plug Receptacle Part Number (Mating Height (mm))	Pitch (mm)	Frequency Rating (GHz)	Voltage Standing Wave Ratio
MLF06	**MM3529-2700A06**	**MM3531-2701A06 (0.69max.)**	0.35	to 20	1.2 max. (DC to 3GHz) 1.2 max. (3GHz to 6GHz) 1.3 max. (6GHz to 9GHz) 1.3 max. (9GHz to 12GHz) 1.35 max. (12GHz to 15GHz) 1.5 max. (15GHz to 18GHz) 1.65 max. (18GHz to 20GHz)
MLF10	**MM3529-2700A10**	**MM3531-2701A10 (0.69max.)**			
MLF14	**MM3529-2700A14**	**MM3531-2700A14 (0.69 max.)**			
MLF20	**MM3529-2700A20**	**MM3531-2700A20 (0.69 max.)**			

Nominal Impedance: 50Ω Rated Voltage: 30Vrms Temperature Range: -40 to 85°C

Microwave Coaxial Cable Connectors/Board to Board Connectors

Murata microwave coaxial connectors are small, thin, and suitable for low-profile design.
The connectors have high RF performance.

JSC



MM5829-2700

MM5831-2700

MXJA01_

MXJGB3_

MXJF56_

KSC

MM6829-2700

MM6831-2700

MXKGB3_

MXKF56_

LSC



MM7829-2700

MM7831-2700

MXLAB3_

MXLF56_

(in mm)

Type	Receptacle Part Number	Pulg Receptacle Part Number (Mating Height (mm))	Cable Number (Mating Height (mm))	Cable Dia. (mm)	Frequency Rating (GHz)	Voltage Standing Wave Ratio
JSC	**MM5829-2700**	**MM5831-2700 (0.8 max.)**	**MXJA01_ (1.0 max.)**	0.81	to 12	1.3 max. (DC to 3GHz) 1.4 max. (3GHz to 6GHz) 1.5 max. (6GHz to 9GHz) 1.6 max. (9GHz to 12GHz)
			MXJGB3_ (1.0 max.)	0.49		
			MXJF56_ (1.0 max.)	0.53		
KSC	**MM6829-2700**	**MM6831-2700 (0.6 max.)**	**MXKGB3_ (0.8 max.)**	0.49	to 12	1.3 max. (DC to 3GHz) 1.4 max. (3GHz to 6GHz) 1.6 max. (6GHz to 9GHz) 1.7 max. (9GHz to 12GHz)
			MXKF56_ (0.8 max.)	0.53		
LSC	**MM7829-2700**	**MM7831-2700 (0.6 max.)**	**MXLAB3_ (0.8 max.)**	0.49	to 6	1.3 max. (DC to 3GHz) 1.4 max. (3GHz to 6GHz)
			MXLF56_ (0.8 max.)	0.53		

Nominal Impedance: 50Ω Rated Voltage: 30Vrms Temperature Range: -40 to 85°C
Mating Height is mated with receptacle.

Detailed Catalogs

For more details, please refer to our printed catalogs and the PDF catalogs on our website.

▪ Microwave Coaxial Connectors Cat. No. O30E

Memo

Sensors

Summary

Murata pursued sensing functions making full use of MEMS and processing technology, and magnetoresistive elements including ceramic material technology in order to develop highly efficient and highly reliable devices, modules, and systems.
A lineup of various sensors respond to the sensing needs of various applications for automobile, wearable, medical care, and health care.

Lineup

●Infrared Sensors ●Ultrasonic Sensors
●AMR Sensors (Magnetic Sensors) ●Shock Sensors
●Accelerometers ●Inclinometers ●Gyro Sensors
●Temperature Sensors (Thermistors)

https://www.murata.com/en-global/products/sensor

Sensor Guide (Select by Method/Principle)

Temperature

Thermistors: The resistance changes with the temperature.



Infrared

Pyroelectric infrared sensors: The sensor reacts to the infrared radiation emitted from the human body to output an electric charge.

IRA Series

For more details on Thermistors, please refer to p. 80

Detailed Catalogs

For more details, please refer to our printed catalogs and the PDF catalogs on our website.



- MEMS Sensors & Sensing Elements — Cat. No. S47E
- NTC Thermistors — Cat. No. R44E
- POSISTOR for Circuit Protection — Cat. No. R90E
- NTC/PTC Thermistors for Automotive — Cat. No. R03E

Distance

Ultrasonic sensors: The sensor sends and receives ultrasonic waves in order to detect distances from the state of the reflected wave.

MA300D1-1
(for Dual Use)

MA40S4R (for Receiver)
MA40S4S (for Transmitter)

MA58MF14-7N
(for Dual Use)

MA40H1S-R
(for Dual Use)

Magnetic/ Open and Shut

Magnetic switches: This switch switches built-in ICs when the magnetoresistive element detects the magnetic proximity.

MR Series

Inertial force

Shock sensors: This sensor generates an electric charge according to the acceleration (stress) applied to the piezoelectric element.

PKGS Series

Accelerometers: This sensor detects the acceleration from the change of the capacitance that occurs in the 3DMEMS element.

SCA Series

Inclinometers: This sensor detects the gravitational acceleration of the Earth to calculate the angle of gradient.

SCA Series

Gyro sensors: This sensor detects the angular velocity from the change in the capacitance that occurs in the 3DMEMS element.

SCC Series
SCR Series

Lineup

Detection	Murata's Sensors			Applications										
				AV Equipment					Communications Devices					
	Products	Series or Main Part Number	Dimensions (mm)	TV	Audio	DVD, CD	Digital Video Camera	Digital Camera	PC	Scanner	Multifunction Machine	Printer	FAX	Electronic Bulletin Board
Infrared	Pyroelectric Infrared Sensors	**IRA Series**	ø9.2 H4.7	●	●	●			●	●	●	●	●	●
Ultrasonic	Open Structure Type Ultrasonic Sensors	**MA40S4R** (for Receiver) **MA40S4S** (for Transmitter)	ø9.9 H7.1											●
		MA40H1S-R (SMD/for Dual Use)	5.2X5.2X1.15	●					●		●			●
	Drip-proof Type Ultrasonic Sensors	**MA58MF14-7N** (for Dual Use)	ø14.0 H9.0											
	High Frequency Type Ultrasonic Sensors	**MA300D1-1** (for Dual Use)	ø9.9 H7.3							●	●	●		
Magnetic	AMR Sensors (Magnetic Sensors)	**MR Series**	MRMS201A-001: 2.8X2.9X1.1 MRMS501A-001: 1.45X1.45X0.55			●	●	●	●					
Acceleration	Shock Sensors	**PKGS Series**	3.2X2.0X1.05						●					
	Accelerometers	**SCA Series**	7.6X8.6X3.3											
	Inclinometers	**SCA Series**	7.6X8.6X3.3								●			
Angle Velocity	Gyro Sensors	**SCC Series** **SCR Series**	12.1X15.0X4.35											
Temperature	NTC Thermistors	**Chip Type NC_ Series**	NCP02: 0.4X0.2X0.2 NCP03: 0.6X0.3X0.3 NC_15: 1.0X0.5X0.5 NC_18: 1.6X0.8X0.8	●	●	●	●	●	●	●	●	●	●	●
		Lead Type NX Series	NXF: ø1.2 L25 to 150 NXR: ø4.0 L10 to 40	●	●	●	●	●	●	●	●	●	●	●
	PTC Thermistors POSISTOR	**Chip Type PR_ Series**	PRF15: 1.0X0.5X0.5 PRF18: 1.6X0.8X0.8 PRF21: 2.0X1.25X0.9	●	●	●	●	●	●	●	●	●	●	●
		Lead Type PTF Series	ø5.0 max. T4.0 max. ø7.5 T3.0	●	●				●	●	●	●	●	●

Applications																														
	Home Electronics											Security				Car Electronics			Toy		Others								Wearable	
	Refrigerator	Electric Rice-cooker	Air Conditioner	Air Purification System	Humidifier	Cleaner	Laundry Machine	Food Fan	Water Heater	Toilet Seats with a Warm-water Shower Feature	Lighting	Security Camera	Security Light	Indoor Security Sensor	Intrusion Detection Sensor	Navigation System	Climate Control	Parking Assist	Radio Control (Attitude Control)	Game Controller	Machine Tool	ATM, CD	Vending Machine	Amusement Machine	Construction Machinery	Farm Machinery	Railroad Equipment		Murata's Sensors Products
	●	●	●	●							●	●	●	●	●							●	●	●					Pyroelectric Infrared Sensors
	●		●			●					●	●	●	●	●							●	●	●					Open Structure Type Ultrasonic Sensors
	●		●			●					●	●	●	●	●							●	●	●					
																		●											Drip-proof Type Ultrasonic Sensors
																						●							High Frequency Type Ultrasonic Sensors
	●	●	●	●	●	●	●	●	●	●	●				●						●	●	●	●					AMR Sensors (Magnetic Sensors)
																													Shock Sensors
							●														●			●	●	●			Accelerometers
																					●				●	●			Inclinometers
							●									●					●			●	●	●			Gyro Sensors
		●	●	●	●	●	●	●	●	●	●					●	●	●	●	●	●	●		●				●	NTC Thermistors
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				●	
	●	●	●	●	●	●	●	●	●	●	●					●	●	●		●				●					PTC Thermistors POSISTOR
					●	●	●	●	●	●	●													●					

Thermistors

Facilitate your designs and products utilizing our thermal design and thermistor products.

Summary

Murata's semi-conductive ceramics and electrode printing technologies, such as PTC and NTC Thermistors, provide vital protection and sensing within electronic equipment. Simulation software tools are also available for your convenience.

Lineup

●NTC Thermistors for temperature sensor/compensation, and automotive

●PTC Thermistors POSISTOR for overheat sensing, overcurrent protection, inrush current suppression, and automotive

https://www.murata.com/en-global/products/thermistor

NTC Thermistors for Temperature Sensor/ Temperature Compensation

Chip Type

Chip NTC Thermistors have Ni barrier terminations, provide excellent solderability, and offer high stability in harsh environments due to their unique inner construction.



NCP02 Series | NCP03 Series | NCP15 Series NCU15 Series | NCP18 Series NCU18 Series

(in mm)

Series	Size Code inch (mm)	Resistance (25°C) (Ω)	B-Constant (25-50°C) (K)	Maximum Operating Current for Sensor (25°C) (mA)	Maximum Voltage (V)	Typical Dissipation Constant (25°C) (mW/°C)	Operating Temperature Range (°C)
NCP02	01005 (0402)	10k to 470k	3380 to 4250	0.015 to 0.100	5	1	-40 to 125
NCP03	0201 (0603)	1.0k to 220k	3500 to 4485	0.021 to 0.316	5	1	-40 to 125
NCP15	0402 (1005)	220 to 470k	3500 to 4500	0.015 to 0.674	5	1	-40 to 125
NCU15	0402 (1005)	10k to 100k	3380 to 4250	0.032 to 0.100	5	1	-40 to 125
NCP18	0603 (1608)	220 to 470k	3500 to 4500	0.015 to 0.674	5	1	-40 to 125
NCU18	0605 (1608)	10k to 470k	3380 to 4500	0.032 to 0.100	5	1	-40 to 125

Maximum Operating Current for Sensor raises the Thermistor's temperature by 0.1°C.
There are also items for automotive applications in the NCP/NCU Series.

Detailed Catalogs

For more details, please refer to our printed catalogs and the PDF catalogs on our website.

- NTC Thermistors — Cat. No. R44E
- POSISTOR for Circuit Protection — Cat. No. R90E
- NTC/PTC Thermistors for Automotive — Cat. No. R03E

Thermo String Type

Small flexible lead type NTC Thermistors with a small head and a thin lead wire.



Twist
NXFT15_1B Series



Without twist
NXFT15_2B Series



Without twist
NXFT_AB Series

(in mm)

Series	Resistance (25°C) (Ω)	B-Constant (25-50°C) (K)	Maximum Operating Current for Sensor (25°C) (mA)	Thermal Time Constant (25°C) (s)	Full Length (mm)	Operating Temperature Range (°C)
NXFT15_1/2B_ (Cooper wire type)	3k to 100k	3380 to 4250	0.04 to 0.22	4	60 to 150	-40 to 125
NXFT15_AB_ (Nickel Cooper wire type)	3k to 100k	3380 to 4250	0.024 to 0.14	3	21 to 50	-40 to 125

Maximum Operating Current for Sensor raises the Thermistor's temperature by 0.1°C.
There are also items for automotive applications in the NXF Series.

Lead Type

This product is a thermistor for normal temperature level sensors having self-subsistence due to strong lead strength based on chip NTC.



NXRT15_1B_ Series



NXRT15_5B_/Insulation Series*

(in mm)

Series	Resistance (25°C) (Ω)	B-Constant (25-50°C) (K)	Maximum Operating Current for Sensor (25°C) (mA)	Thermal Time Constant (25°C) (s)	Full Length (mm)	Operating Temperature Range (°C)
NXRT15_1B_	2k to 100k	3380 to 4250	0.04 to 0.27	4	10 to 50	-40 to 125
NXRT15_5B_ (Insulation*)	2k to 100k	3380 to 4250	0.05 to 0.36	4	25 to 50	-40 to 125

Maximum Operating Current for Sensor raises the Thermistor's temperature by 0.1°C.
There are also items for automotive applications in the NXR Series.
*Insulation: Lead wire insulation type.

PTC Thermistors POSISTOR for Overheat Sensing

Chip Type

For overheat sensing for power transistors, power diodes, and power ICs in hybrid circuits.

PRF15 Series



PRF18 Series



PRF21 Series

(in mm)

Series	Sensing Temperature Range (°C) 60 70 80 90 100 110 120 130 140 150	Sensing Temperature Tolerance (°C)	Maximum Voltage (V)	Size Code inch (mm)
PRF15		±3/±5	32	0402 (1005)
PRF18		±3/±5	32	0603 (1608)
PRF21		±5	32	0805 (2012)

There are also items for automotive applications in the PRF Series.

Lead Type

For protecting power transistors, stereo main amplifiers, etc., from overheating, and also for sensing the temperature of other components that may be overheated.



PTFL Series



PTFM Series

(in mm)

Series	Sensing Temperature Range (TS) (°C) 60 70 80 90 100 110 120 130 140 150	Maximum Voltage (V)	Resistance (25°C) (max.) (Ω)	Resistance (TS-10°C) (max.) (Ω)	Resistance (TS°C) (min.) (Ω)
PTF□_471Q		16	100	330	470
PTF□_222Q		16	330	1.5k	2.2k

The blank is filled with type codes. (L: Lead type, M: with lug-terminal)
Operating Temperature Range is -10 to TS+10°C.

PTC Thermistors POSISTOR for Inrush Current Suppression

This series is able to support overcurrent or inrush current issues on the power supply circuit.



PTGL07AS Series



PTGL14 to 20AS Series

(in mm)

Series	Resistance (25°C) (Ω)	Maximum Voltage (V)	Maximum Inrush Current (Ao-p)	Maximum Charge Energy (J)	Operating Temperature Range (°C)
PTGL07AS	120 to 200	280	5.66 to 8.46	7.8 (105°C)	-40 to 105
PTGL14 to 20AS	33 to 100	280	13 to 39	56.9 to 181.7 (60 to 85°C)	-20 to 85

Maximum Inrush Current shows the maximum inrush current value introduced into the Posistor at operating temperature range.

PTC Thermistors POSISTOR for Overcurrent Protection

Chip Type

Overcurrent Protection device with resettable function suitable for current-limiting resistors.

PRG15 Series



PRG18 Series



PRG21 Series

(in mm)

Series	Maximum Voltage (V)	Hold Current (60°C) (mA)	Trip Current (-10°C) (mA)	Maximum Current (A)	Resistance (25°C) (Ω)	Size Code inch (mm)
PRG15	6 to 30	17 to 88	65 to 318	0.6 to 3.5	2.2 to 68	0402 (1005)
PRG18	6 to 30	7 to 220	25 to 850	0.06 to 7.5	1.0 to 470	0603 (1608)
PRG21	6 to 32	30 to 500	110 to 2000	0.59 to 37	0.2 to 42	0805 (2012)

Maximum Current shows typical transformer capacities that can be used.
There are also items for automotive applications in the PRG Series.

Lead Type

Best suited to meet the requirements of power supplies and motor protection.
Error-free operation is ensured by rush current.



(in mm)

PTGL Series
*The Lead shape is an example.

Series	Maximum Voltage (V)	Hold Current (60°C) (mA)	Trip Current (-10°C) (mA)	Maximum Current (A)	Resistance (25°C) (Ω)
PTGL	16	370 to 1200	1040 to 3360	2.0 to 10.0	0.15 to 1.0
	24	120 to 140	500 to 580	2.0	3.3 to 4.7
	30	122 to 685	240 to 1900	1.5 to 7.0	0.8 to 10
	32	40 to 60	170 to 240	1.5	15 to 33
	51	168 to 592	332 to 1168	1.0 to 5.0	1.2 to 10
	56	90 to 380	240 to 980	1.0 to 2.5	3.3 to 22
	60	88 to 439	175 to 867	1.0 to 5.0	2.2 to 22
	80	50 to 190	135 to 530	0.7 to 3.0	9.4 to 55
	125	30 to 220	75 to 550	0.3 to 1.2	10 to 180
	140	74 to 310	147 to 670	0.5 to 3.5	4.7 to 56
	250	90 to 100	280 to 300	0.5 to 0.6	12 to 39
	265	28 to 300	70 to 830	0.2 to 4.1	6.0 to 180

Maximum Current shows typical transformer capacities that can be used.
There are also items for automotive applications in the PTGL Series.

Power Devices

Eco-friendly and high-quality power devices

Summary

To meet consumer needs Murata offers power supply products and energy devices that can be used with a variety of equipment, such as video equipment, household information appliances, and communication/transfer equipment. Murata provides standard and customized products using highly reliable. Murata makes components utilizing advanced design and high-density packaging technology.

Lineup

- DC-DC Converters
- High Voltage Power Supplies
- Switching Power Supplies

https://www.murata.com/en-global/products/power

DC-DC Converters

DC-DC converters are vital to the demands of electronic equipment.
Murata offers DC-DC converters that set the standard for miniaturization, low-profile, high-efficiency, power-saving and low-noise power supplies. Murata also provides standard products and customized products, ultra-low-profile products, and products for FPGAs.

Non-isolated Type

MYMGK00504ERSR
MYMGK1R804ERSR

MYMGK00506ERSR
MYMGK1R806FRSR

MYMGK1R820ERSR
MYMGK1R820FRSR

MYSGK1R830FRSR

MYLSM00502ERPL

MYSGK02506BRSR

MYMGA5R04RELA5RA



MYMGC series

OKL-T/20 series
OKL2-T/20 series

OKL-T/12 series
OKL2-T/12 series

OKL-T/3 series
OKL2-T/3 series

OKL-T/6 series
OKL2-T/6 series

MYSSM02406BEPL

MYUSP3R303FMP

Part number	Output Current (A)	Input Voltage (V)	Output Voltage (V)	Efficiency (%)	I2C or PMBus	Package	Size (mm)		
							W	L	T
MYLSM00502ERPL	2.5	4.5 to 17	1 to 5.25	89.4	Not available	SMD	7.9	7.9	2.3
MYMGK1R804FRSR	4	4.5 to 8	0.7 to 1.8	93.1	Not available	SMD	7.5	9.0	5.0
MYMGK00504ERSR	4	8 to 15	0.7 to 5	96.1	Not available	SMD	7.5	9.0	5.0
MYMGK1R806FRSR	6	4.5 to 8	0.7 to 1.8	90.4	Not available	SMD	7.5	9.0	5.0
MYMGK00506ERSR	6	8 to 15	0.7 to 5	95.4	Not available	SMD	7.5	9.0	5.0
MYMGK1R812FRSR	12	4.5 to 8	0.7 to 1.8	92	Not available	SMD	9.0	10.5	5.6
MYMGK1R812ERSR	12	8 to 15	0.7 to 1.8	90.4	Not available	SMD	9.0	10.5	5.6
MYMGK1R820FRSR	20	4.5 to 8	0.7 to 1.8	89.2	Not available	SMD	9.0	10.5	5.6

These are just a few examples of our large assortment of power products.

Continued on the following page. ↗

Part number	Output Current (A)	Input Voltage (V)	Output Voltage (V)	Efficiency (%)	I2C or PMBus	Package	Size (mm)		
							W	L	T
MYMGK1R820ERSR	20	8 to 15	0.7 to 1.8	87.8	Not available	SMD	9.0	10.5	5.6
MYSGK1R830FRSR	30	4.5 to 15	0.7 to 1.8	89.7	Not available	SMD	14.0	11.0	8.3
MYSGK02506BRSR	6	13.5 to 42	5 to 25	98	Not available	SMD	14.7	16.3	7.5
MYMGA5R04RELA5RA	4	8.0 to 16.0	3.3 to 5	94	Not available	SMD	9.0	10.5	5.6
MYMGC0R88RFLF2RV	8	3.3 to 5.5	0.85	81	I2C	SMD	11.9	15.0	2.4
MYMGC1R83BFPF2RV (Quad output)	3.2 0.5 0.5 1.5	3.3 to 5.5	0.85 0.85 1.2 1.8	81	I2C	SMD	11.9	15.0	2.4
MYMGC3R32EFPF2RV (Quad output)	2.5 1 2 1.5	4.3 to 5.5	1.2 1.8 3.3 2.5	91	I2C	SMD	11.9	15.0	2.4
OKL-T/3-W5P-C	3	2.4 to 5.5	0.6 to 3.63	95.3	Not available	SMD	12.2	12.2	6.2
OKL-T/6-W12P-C	6	4.5 to 14	0.591 to 5.5	93	Not available	SMD	12.2	12.2	7.2
OKL2-T/12-W12P2-C	12	4.5 to 14	0.69 to 5.5	95	Not available	SMD	20.32	11.43	8.55
OKL2-T/20-W12P2-C	20	4.5 to 14	0.69 to 5.5	94	Not available	SMD	33.02	13.46	8.7
MYSSM02406BEPL	6	30.5 to 40	12 to 24	97.6	Not available	SMD	30.2	20.9	8.3
MYUSP3R303FMP	3	3 to 5.5	0.7 to 3.3	94	Not available	SMD	11.0	8.5	5.6

These are just a few examples of our large assortment of power products.

Isolated DC-DC Converter for PoE

MYBSP0055AABFT
MYBSP0122BABFT

MYBSP0055AABF
MYBSP0122BABF

MYBSP00502ABF
MYBSP01201ABF

MYBTA00512ABT

MYBSC00520ABT
MYBSC0128CABT
MYBSC0128CAZT

MYBSS054R6EBF

Part number	Output Power (W)	Input Voltage (V)	Output Voltage (V)	Efficiency (%)	PoE controller	Package	Size (mm)		
							W	L	T
MYBSP00502ABF	10	37 to 57	5	80	Available	SMD	26.0	14.8	6.2
MYBSP01201ABF	12	37 to 57	12	84	Available	SMD	26.0	14.8	6.2
MYBSP0055AABF	25.5	37 to 57	5	90.5	Available	SMD	35.5	22.4	10.55
MYBSP0122BABF	25.5	37 to 57	12	92.5	Available	SMD	35.5	22.4	10.55
MYBSP0055AABFT	25.5	37 to 57	5	90.5	Available	SMD	35.5	22.4	10.55
MYBSP0122BABFT	25.5	37 to 57	12	92.5	Available	SMD	35.5	22.4	10.55
MYBTA00512ABT	60	36 to 75	5	92	Not available	SMD	23.36	19.05	12.7
MYBSC00520ABT	100	36 to 75	5	92	Not available	SMD	33.0	23.2	10.35
MYBSC0128CABT	100	36 to 75	12	92.5	Not available	SMD	33.0	23.2	10.35
MYBSC0128CAZT	100	36 to 75	12	92.5	Not available	Insert	33.0	23.2	9.32
MYBSS054R6EBF	30	10.8 to 27	54	90	Not available	SMD	35.5	22.4	8.9

Isolated Type

MYBEA01212AZT



MYBEA01212AZTB
MYBEA01210CZTB

MYBEA01210CZT

MYBSA00804KZT
MYBSA0122ECZT

MYBEB01212AZTB

MYBSC00520ABT
MYBSC0128CABT
MYBSC0128CAZT

MYBTA00512ABT

MPD5D017S
MPD5D018S

Part number	Output Power (W)	Input Voltage (V)	Output Voltage (V)	Efficiency (%)	Footprint (Brick)	Package	Size (mm)		
							W	L	T
MYBEA01212AZT	144	36 to 75	12	92.5	1/8	Insert	58.4	22.8	8.46
MYBEA01212AZTB	144	36 to 75	12	92.5	1/8	Insert	58.4	22.8	11.3
MYBEA01210CZT	120	18 to 36	12	93	1/8	Insert	58.4	22.8	8.46
MYBEA01210CZTB	120	18 to 36	12	93	1/8	Insert	58.4	22.8	11.3
MYBEB01212AZTB	100	36 to 75	12	91.5	1/8	Insert	58.4	22.8	12.2
MYBTA00512ABT	60	36 to 75	5	92	1/32	SMD	23.36	19.05	12.7
MYBSC00520ABT	100	36 to 75	5	92	1/16	SMD	33.0	23.2	10.35
MYBSC0128CABT	100	36 to 75	12	92.5	1/16	SMD	33.0	23.2	10.35
MYBSC0128CAZT	100	36 to 75	12	92.5	1/16	Insert	33.0	23.2	9.32
MPD5D017S	4.95	36 to 75	3.3	84	NA	SMD	26.8	14.6	4.7
MPD5D018S	5	36 to 75	5	84	NA	SMD	26.8	14.6	4.7
MYBSA00804KZT	33.6	18 to 60	8	88	1/16	Insert	33.0	22.7	8.95
MYBSA0122ECZT	30	19.2 to 30	12	91	1/16	Insert	33.0	22.7	8.95

These are just a few examples of our large assortment of power products.

High Voltage Power Supplies



MPL3000 Series
(AC/DC Ballast)

Series	Applications	Input Voltage Vin	Output Power	Other Specification
MPL3000 (AC/DC Ballast)	Projector	250 to 420V DC	to 350W	For extra-high pressure mercury lamp

For more details on our products, please contact us.

Switching Power Supplies

LED Lighting

Applications	Input Voltage	Output Voltage	Safety Standard	EMI Standard	Remarks
LED Lighting	90 to 264V AC	8 to 25V 30 to 50V	PSE	VCCI, CISPR	PWM Dimming, Accepted for DALI, UART

For more details on our products, please contact us.

For Ionizer Modules, please refer to p. 100.

Batteries

Battery solutions for energy storage systems and various small devices

Summary

Murata offers battery solutions for a wide range of applications from IoT & wearable devices to energy storage systems for enterprise and household use.

Lineup

- Laminated Type Lithium Ion Batteries
- Cylindrical Type Lithium Ion Batteries
- Li-ion Energy Storage System
- Micro Batteries

Laminated Type Lithium Ion Batteries

Laminated type lithium ion battery has laminate film for packaging. These batteries are known for their excellent safety, thinner form factors, and size flexibility.

Cylindrical Type Lithium Ion Batteries

Cylindrical type lithium ion batteries are packaged in metal cans. These batteries can be used at high rate and maintain high capacity.

Li-ion Energy Storage System

Possible to customize capacity in order to meet wide usage

2.1kWh Energy Storage Module



(in mm)

(Excluding terminal)
IJ1101M
27kg

Model Name	Nominal Capacity	Rated Capacity	Nominal Voltage	Maximum Discharge Current	Charge Voltage	Maximum Charge Current	Safety Standard
IJ1101M	2.1kWh (42.0Ah)	2.0kWh (39.5Ah)	51.2V	50A	56.0V	40A	EU RE Directive UL 1973 FCC Part 15 Class B

Storage Temperature: -20 to 45°C (Recommended room temperature)
Operating Ambient Temperature: Discharge: -20 to 40°C (Discharge current ≦ 50.0A)
40 to 50°C (Discharge current ≦ 40.0A)
Charge: 10 to 45°C (Charge current ≦ 40.0A)
0 to 10°C (Charge current ≦ 12.0A)

High Rate Module



(in mm)

(Excluding terminal)
IJ1201M
18kg

*use for Japan market

Model Name	Nominal Capacity	Rated Capacity	Nominal Voltage	Maximum Discharge Current	Charge Voltage	Maximum Charge Current	Safety Standard
IJ1201M	1.2kWh (24Ah)	1.15kWh (22.5Ah)	51.2V	90A	56.0V	22.5A	-

Storage Temperature: -20 to 45°C (Recommended room temperature)
Operating Ambient Temperature: Continuous Discharge: 0 to 30°C (Discharge current ≦ 90.0A)
30 to 35°C (Discharge current ≦ 75.0A)
35 to 40°C (Discharge current ≦ 67.5A)
Non-Continuous Discharge: 30 to 40°C (Discharge current ≦ 90.0A, Time ≦ 60 sec)
Charge: 10 to 40°C (Charge current ≦ 22.5A)
0 to 10°C (Charge current ≦ 6.75A Recommended)

Battery Management Unit (BMU)

(in mm)

(Excluding terminal)
IJ5101C
12kg

*use for Japan market

(Excluding terminal)
IJ8101C
14kg

Model Name	Operating Voltage	Operating Current	Communication Interface	Configuration	Safety Standard
IJ5101C	60 to 420V	0 to 100A	RS232C/RS485C	Series: to 7 series Mix Combination: to 6 series and to 2 parallels Maximum module connections: 32 modules	-
IJ8101C	300 to 1000V	0 to 100A	RS232C/RS485C	Series: to 16 series Mix Combination: to 16 series and to 2 parallels	EU LV Directive EU EMC Directive UL 1973 FCC Part 15 Class B *It is certificated along with IJ1101M. *UL 1973 is certified for maximum of 90 A.

Storage Temperature: -20 to 65°C (Recommended room temperature)
Operating Ambient Temperature: -20 to 50°C (Recommended room temperature)

BMU-HUB

(in mm)

(Excluding terminal)
IJ1101K
3.4kg

Model Name	Operating Voltage	Purpose	Configuration	Safety Standard
IJ1101K	DC12V, DC24 to 60V	Interface unit to connect IJ8101C for utility	Parallel: to 64BMU Maximum module connections: 64X32=2048 modules (maximum 4.3MWh)	EU EMC Directive FCC Part 15 Class B

Storage Temperature: -20 to 65°C (Storage and use at room temperature is recommended)
Operating Ambient Temperature: -20 to 60°C (Storage and use at room temperature is recommended)

Cable

Model Name	Type	Specification
IJT-102F	Communication Cable 20cm	RS485
IJT-103F	Communication Cable 30cm	RS485
IJT-115F	Communication Cable 150cm	RS485
IJT-130F	Communication Cable 300cm	RS485
IJD-103F/R	Thicker Power Cable 30cm (red)	AWG4
IJD-103F/B	Thicker Power Cable 30cm (black)	AWG4
IJD-110F/R	Thicker Power Cable 100cm (red)	AWG4
IJD-110F/B	Thicker Power Cable 100cm (black)	AWG4

Coin Manganese Dioxide Lithium Batteries

Coin manganese dioxide lithium batteries are small-sized primary batteries for various applications such as TPMS (Tire Pressure Monitoring System) or smart entry systems for automobile, IoT devices, and backup power source for memory.

Standard

A lineup of 11 models is offered from small size and thin models to high-capacity models.

Model	Electrical Characteristics			Dimensions			Operating Temperature Range (°C)
	Nominal Voltage (V)	Nominal Capacity (mAh)	Standard Discharge Current (mA)	Diameter (mm)	Height (mm)	Weight (g)	
CR1216	3	30	0.1	12.5	1.6	0.67	-30 to 70
CR1220	3	40	0.1	12.5	2.0	0.77	-30 to 70
CR1616	3	60	0.1	16.0	1.6	1.1	-30 to 70
CR1620	3	80	0.1	16.0	2.0	1.3	-30 to 70
CR1632	3	140	0.2	16.0	3.2	1.9	-30 to 70
CR2016	3	90	0.1	20.0	1.6	1.8	-30 to 70
CR2025	3	160	0.2	20.0	2.5	2.6	-30 to 70
CR2032	3	220	0.2	20.0	3.2	3.1	-30 to 70
CR2430	3	300	0.2	24.5	3.0	4.4	-30 to 70
CR2450	3	610	0.2	24.5	5.0	6.5	-30 to 70
CR2477	3	1000	0.4	24.5	7.7	11	-30 to 70

Nominal capacity indicates duration until discharge voltage drops down to 2.0V when discharged at nominal discharge current at 23°C.

Heat-resistant

Ideal for devices used in severe operating temperature environments including automobiles and FA, etc.

Model	Electrical Characteristics			Dimensions			Operating Temperature Range (°C)
	Nominal Voltage (V)	Nominal Capacity (mAh)	Recommended Continuous Discharge Current (mA)	Diameter (mm)	Height (mm)	Weight (g)	
CR2032W	3	210	≦1	20.0	3.2	3.1	-40 to 125
CR2050W	3	345	≦1	20.0	5.0	4.2	-40 to 125
CR2450W	3	550	≦1	24.5	5.0	6.7	-40 to 125
CR2477W	3	1000	≦1	24.5	7.7	11	-40 to 125

Continued on the following page. ↗

Extended Temperature

Designed for automotive devices and outdoor IoT systems, including smart meters and FA control systems. Recommended as an alternative smaller and thinner solution to conventional cylindrical lithium batteries.

Model	Electrical Characteristics				Dimensions			Operating Temperature Range (°C)
	Nominal Voltage (V)	Nominal Capacity (mAh)	Recommended Continuous Discharge Current (mA)	Maximum pulse discharge current*1 (mA)	Diameter (mm)	Height (mm)	Weight (g)	
CR2032X	3.0	220	≦1	30	20.0	3.2	3.0	-40 to 85
CR2450X	3.0	600	≦1	30	24.5	5.0	6.2	-40 to 85
CR2477X	3.0	1000	≦1	30	24.5	7.7	9.5	-40 to 85
CR3677X*2	3.0	2000	≦1	80	36.5	7.7	20	-40 to 85

*1 Current for maintaining minimum 2V voltage with pulsed discharge of 3 seconds and 50% nominal capacity discharged (ambient temperature 23°C)
*2 Shipment of mass-produced CR3677X is scheduled to start at the end of 2019.

Operating temperature



Voltage comparison after 85˚C storage



High Drain

Ideal for tracking devices for logistics and asset management by adopting Low Power Wide Area (LPWA) networks such as LoRa and SIGFOX as well as for outdoor infrastructures, FA control systems, and environment monitoring sensors.

Model	Electrical Characteristics				Dimensions			Operating Temperature Range (°C)
	Nominal Voltage (V)	Nominal Capacity (mAh)	Recommended Continuous Discharge Current (mA)	Maximum pulse discharge current*1 (mA)	Diameter (mm)	Height (mm)	Weight (g)	
CR2032R	3.0	200	≦3	50	20.0	3.2	3.0	-30 to 70
CR2450R	3.0	500	≦3	50	24.5	5.0	6.2	-30 to 70

*1 Current for maintaining minimum 2V voltage with pulsed discharge of 3 seconds and 50% nominal capacity discharged (ambient temperature 23°C)

Max. pulse discharge current



*50% depth of discharge battery's maximum pulse discharge current over 2V for 3s (23°C)

Discharge time (45mA pulse discharge)



*Pulse discharge condition:
45mA x 3s, 33s off, 2V cut off (23°C)

Continued on the following page. ↗

Tab-welder

Mounting Direction		H			V	M
Tab Specification	Shape	E		O	E	P
	Width of Negative Tab Tip (mm)	0.75	0.75	1.8	0.75	2.0
	Width of Positive Tab Tip (mm)	0.75X2	0.75X2	2.8	0.75X2	2.0
	Pitch (mm)	17.8	20.5	20.5	N/A	N/A
Standard	CR2032	CR2032-HE8	CR2032-HE1	CR2032-HO6	CR2032-VE3	
	CR2430	CR2430-HE1	CR2430-HE2	CR2430-HO1	CR2430-VE1	
	CR2450	CR2450-HE5	CR2450-HE6	CR2450-HO5	CR2450-VE6	
	CR2477		CR2477-HE2	CR2477-HO4	CR2477-VE1	
Extended Temperature	CR2032X		CR2032X-HE1	CR2032X-HO6		
	CR2450X		CR2450X-HE6	CR2450X-HO5		
	CR2477X		CR2477X-HE2	CR2477X-HO4		
Heat-resistant	CR2032W		CR2032W-HE1	CR2032W-HO6		
	CR2050W					CR2050W-MP1
	CR2450W		CR2450W-HE6	CR2450W-HO5		CR2450W-MP1
	CR2477W		CR2477W-HE2	CR2477W-HO4		
High Drain	CR2032R		CR2032R-HE1	CR2032R-HO6		
	CR2450R		CR2450R-HE6	CR2450R-HO5		

For tab shapes or specifications not included in the above list, please consult your sales representative.

Silver Oxide Batteries

Silver oxide batteries are small-sized primary batteries with high capacity and stable discharge characteristics. They are suitable for medical devices and precision instruments. All models are 100% made in Japan, and environmentally friendly (0% mercury).

Model	Electrical Characteristics		Dimensions			Operating Temperature Range (°C)
	Nominal Voltage (V)	Nominal Capacity (mAh)	Diameter (mm)	Height (mm)	Weight (g)	
SR621	1.55	20	6.8	2.15	0.32	-10 to 60
SR626	1.55	28	6.8	2.60	0.40	-10 to 60
SR721	1.55	29	7.9	2.10	0.42	-10 to 60
SR726	1.55	35	7.9	2.60	0.50	-10 to 60
SR41	1.55	45	7.9	3.60	0.65	-10 to 60
SR48	1.55	75	7.9	5.40	1.2	-10 to 60
SR920	1.55	40	9.5	2.05	0.59	-10 to 60
SR927	1.55	60	9.5	2.70	0.79	-10 to 60
SR936	1.55	75	9.5	3.60	1.1	-10 to 60
SR1120	1.55	60	11.6	2.05	0.92	-10 to 60
SR1130	1.55	85	11.6	3.05	1.4	-10 to 60
SR43	1.55	110	11.6	4.20	1.8	-10 to 60
SR44	1.55	160	11.6	5.40	2.2	-10 to 60

Data is not guaranteed, and is provided for reference purposes only.
Please contact us for other models.

Alkaline Manganese Batteries

Alkaline manganese batteries are small-sized primary batteries with high performance. They are suitable for various applications such as toys, medical devices and health appliances. All models are 100% made in Japan, and environmentally friendly (0% mercury).

Model	Electrical Characteristics		Dimensions			Operating Temperature Range (°C)
	Nominal Voltage (V)	Nominal Capacity (mAh)	Diameter (mm)	Height (mm)	Weight (g)	
LR41	1.5	45	7.9	3.60	0.57	-10 to 60
LR1130	1.5	70	11.6	3.05	1.2	-10 to 60
LR43	1.5	110	11.6	4.20	1.6	-10 to 60
LR44	1.5	120	11.6	5.40	2.0	-10 to 60

Data is not guaranteed, and is provided for reference purposes only.
Please contact us for other models.

Sound Components (Buzzer)

Piezoelectric ceramic materials that expand and shrink by applying voltage are used in piezoelectric sound components.

Summary

Using Murata's unique ceramic material, we offer a variety of piezoelectric sound components.

Lineup

- SMD Piezoelectric Sounders
- Pin Type Piezoelectric Sounders
- Piezoelectric Buzzers
- Piezoelectric Diaphragms

https://www.murata.com/en-global/products/sound

SMD Piezoelectric Sounders

Low power consumption, lightweight.
Optimized for small devices such as blood glucose meters, clinical thermometers, photoflashes for cameras, and portable terminals.
Applicable for automotive usage based on our design and manufacturing technology.

PKMCS1818E20



PKLCS1212E20



PKLCS1212E24



PKLCS1212E40



PKMCS0909E40

(in mm)

Applications	Mounting Type	Drive Type	Main Part Number	Sound Pressure Level (typ.)	Measurement Condition of Sound Pressure Level
For Automotive	Surface Mounting Type	External Drive	**PKMCS1818E20A0-R1**	100dB	12Vo-p, 2.0kHz, square wave, 10cm
			PKLCS1212E20A0-R1	76dB	±1.5Vo-p, 2.0kHz, square wave, 10cm
			PKLCS1212E24A0-R1	80dB	±1.5Vo-p, 2.4kHz, square wave, 10cm
			PKLCS1212E40A1-R1	84dB	±1.5Vo-p, 4.0kHz, square wave, 10cm
For Consumer			**PKLCS1212E2000-R1**	76dB	±1.5Vo-p, 2.0kHz, square wave, 10cm
			PKLCS1212E2400-R1	80dB	±1.5Vo-p, 2.4kHz, square wave, 10cm
			PKLCS1212E4001-R1	84dB	±1.5Vo-p, 4.0kHz, square wave, 10cm
			PKMCS0909E4000-R1	72dB	±1.5Vo-p, 4.0kHz, square wave, 10cm

Detailed Catalogs

For more details, please refer to our printed catalogs and the PDF catalogs on our website.

- Piezoelectric Sound Components Cat. No. P37E

Pin Type Piezoelectric Sounders

Low power consumption, lightweight.
These products are optimized for operation confirmation sounds and warning sounds in household appliances such as air conditioners, washers, and refrigerators.

PKM13EPYH



PKM17EPP

PKM22EPH



PKM22EPPH20



PKM22EPPH40

(in mm)

Packaging	Mounting Type	Drive Type	Main Part Number	Sound Pressure Level (typ.)	Measurement Condition of Sound Pressure Level
Taping	Pin Type	External Drive	**PKM13EPYH4000-A0**	78dB	±1.5Vo-p, 4.0kHz, square wave, 10cm
Bulk			**PKM13EPYH4002-B0**	78dB	±1.5Vo-p, 4.0kHz, square wave, 10cm
			PKM17EPP-2002-B0	79dB	3.0Vo-p, 2.0kHz, square wave, 10cm
			PKM22EPH2001	85dB	±1.5Vo-p, 2.0kHz, square wave, 10cm
			PKM22EPPH2001-B0	79dB	±1.5Vo-p, 2.0kHz, square wave, 10cm
			PKM22EPPH4007-B0	92dB	±1.5Vo-p, 4.0kHz, square wave, 10cm

Piezoelectric Buzzers

This is a unified piezoelectric sounder connected to a built-in self-drive circuit, and it easily generates sound with only a DC power supply.
Suitable for gas detector alarms/burglar alarms/home-electronic appliances.

PKB24SPCH

(in mm)

Mounting Type	Drive Type	Main Part Number	Sound Pressure Level (min.)	Measurement Condition of Sound Pressure Level
Pin Type	Self Drive	**PKB24SPCH3601-B0**	90dB	12Vdc, 10cm

Piezoelectric Diaphragms

Low power consumption, lightweight.
Suitable for clocks/calculators/digital cameras/burglar alarms, and various alarms.



7BB-□□-□

Drive Type	Main Part Number	Plate Size (øD)
External Drive	**7BB-12-9**	ø12.0mm
	7BB-15-6	ø15.0mm
	7BB-20-6	ø20.0mm
	7BB-27-4	ø27.0mm

□: Indicates Metal Plate Diameter and Resonant Frequency Type.

Wireless Communication Modules

Available for a wide range of applications such as automotive, mobile computing devices, and household appliances.

Wi-Fi Modules/ Bluetooth · Wi-Fi Combo Modules



Features
Compact, highly efficient, and flexible custom-made correspondence

Applications
Mobile phones, automotive, tablet PC, POS, HT, electric equipment, smart grid, etc.

Bluetooth Modules/ Bluetooth Low Energy Modules

Features
Compact, highly efficient, and flexible custom-made correspondence

Applications
Mobile phones, automotive, PMP, POS, HT, healthcare, wireless remote control, etc.

Low Power Wide Area Network (LPWAN) Wireless Module

Features
LPWA Wireless Technology-Low-Power consumption, wide area coverage, enables IoT applications. Compact, high efficient, support various communication standards.

Applications
Positioning Tracking, Smart Houses, Agriculture, Healthcare/Medical, Industrial, Logistics, Utilities (Water, Gas Metering), etc.

Micromechatronics

Utilizing the vibration and deformation properties of piezoelectric materials

Microblowers

Tiny air blowers/pumps without a motor

Features

The structure is designed to operate as a blower and pump by applying the ultrasonic vibrations of the ceramic as the drive source. This is achieved in an extremely compact, thin, and silent device with a high flow rate.



MZB1001T02



MZB3004T04



MZB3005T06

MZB4001T05

(in mm)

Part Number	MZB1001T02	MZB3004T04	MZB3005T06	MZB4001T05
Size	20(W) x 20(L) x 1.85(H) (Nozzle Height 1.6)	21(W) x 19(L) x 3.4(H) (Nozzle Height 4.5)	19(W) x 19(L) x 2.3(H)	Φ28 x 5(H) (Each Nozzle Length 6.5)
Flow rate (@0kPa)	1.2L/min (@21Vdc)	0.2L/min (@18Vdc)	0.2L/min (@18Vdc)	1.3L/min (@28Vdc)
Pressure (@0L/min)	2.5kPa (@21Vdc)	60kPa (@19.5Vdc)	60kPa (@19.5Vdc)	-20kPa (@28Vdc)
Resonance frequency	26kHz	23kHz	23kHz	21kHz
Input Voltage (*1)	11.5Vdc to 21Vdc	8Vdc to 19.5Vdc (*2)	8Vdc to 19.5Vdc (*2)	20Vdc to 28Vdc
Operating Temperature range	0°C to 70°C	0°C to 45°C (*3)(*4)	0°C to 45°C (*3)(*4)	5°C to 50°C (*3)(*5)

*The above value shows typical characteristics.

(*1) A drive circuit is required for the operation. Driving circuits are not common. The voltage is the voltage applied to them.
(*2) Only when the back pressure condition is 10kPa or more; it can be driven with a voltage of 18Vdc or more.
(*3) When operated continuously, sufficient performance may not be demonstrated due to the generation of heat.
(*4) Please use in environments where the temperature of the metal surface (marking surface) is 60°C or less.
(*5) Please use in environments where the temperature of the resin surface is 60°C or less.

· The microblower cannot be used for automobile applications (including accessories).
Please refrain from use for automobile applications.
· If the microblower is used for medical applications, Murata requires a special contract to cover the use in the medical application to be agreed upon before the start of mass production.
· Please contact us for other details.

Application Examples

Aroma diffuser, gas/breath suction equipment, blood pressure measuring, breast pump, liquid transfer equipment by air pressure

Ionizer Modules: Ionissimo

High-concentration ion, compact design, ozone control

Ionissimo is an ionizer module with unprecedented compactness and high efficiency, capable of generating a large number of ions owing to Murata's own high-voltage technology and structural design. The ion generator is connected to the driving power supply for modularization and ease of incorporating into equipment.

MHM Series



Features

- A large number of ions will be created by the original structure.
- Compact equipment may be designed due to small ionizer element and driving power supply.
- Ozone amounts may be optimized for specific applications by controlling the generation of ozone without changing the number of ions.

Applications

Air conditioner, air purifier, static eliminator, vacuum cleaner, etc.

Items	MHM314 Type	MHM305 Type	MHM306 Type	MHM400 Type
Input Voltage (VDC)	+10.8 to 13.2	←	←	←
Power	0.9W	0.4W	0.6W	0.6W
Ion Polarity	Negative	←	←	Positive
Ion Amount (*1)	>20000000pcs/cc (*2)	>20000000pcs/cc	←	←
Ozone Level	0.1mg/H (typ.)	<0.1mg/H	<1.0mg/H	<0.1mg/H
Operating Temp.	-10 to 50°C	←	←	←
Operating Humidity	20 to 80%RH (without dewdrop)	←	←	←

(*1) Measuring distance: 20cm
(*2) MHM314's ion amount is around 3 times more than MHM305.

View a demonstration video of Ionissimo Ionizer Modules on our website.

Ozonizer Modules: Ionissimo

By using low-temperature co-fired ceramic substrate (LTCC) for the discharger ozone will be generated stably.

MHM Series



Features

· Stable ozone generation.
· MHM501 type can be used under high humidity conditions.
· Small size

Applications

Refrigerator, vacuum cleaner, dishwasher, clothes washer, etc.

Items	MHM500 Type	MHM501 Type	MHM502 Type
Input Voltage (VDC)	+11 to 13	←	←
Power	1.0W	1.0W (with heater)	6.0W
Ozone Level	<2.5mg/H	<2.5mg/H	<60mg/H
Operating Temp.	-10 to 50℃	←	←
Operating Humidity	20 to 80%RH (without dewdrop)	20 to 95%RH	20 to 85%RH (without dewdrop)

View a demonstration video of Ionissimo Ozonizer Modules on our website.

Others

RFID Devices

RFID for transferring identification data by wireless communication. The state-of-the-art technology allows IC tags to be attached to places where traditional barcode and QR code technology could suffer from aging. Murata offers a comprehensive range of items required to introduce RFID, from IC tags to high-quality antennas, reader/writers, and software applications. With the complete kits from Murata, RFID is seamlessly and reliably implemented.

HF band RFID tag

Part number	LXMS33HCNG-134	LXMS33HCNK-171	LXMS33HCNL-167	LXMSAPHA08-136	LXMSAPHA17-176
Application	Small product management				
Appearance					
RFID standard	ISO15693 NFC Forum Type5	ISO14443 TypeA NFC Forum Type2		ISO15693 NFC Forum Type5	ISO14443 TypeA NFC Forum Type2
Frequency	13.56MHz				
IC	NXP ICODE SLIX	NXP NTAG210	NXP NTAG212	NXP ICODE SLIX	NXP NTAG213
UID memory	64bit				
NDEF memory	896bit	384bit	1024bit	896bit	1152bit
Size(L x W x H)	3.2 x 3.2 x 0.7 mm	3.2 x 3.2 x 0.75 mm		8.3 x 8.3 x 0.8 mm	
Read range*	20mm	15mm	15mm	42mm	32mm

*Reference

UHF band RFID tag

Part number	LXMS21NCNH-147	LXMSJZNCMF-198	LXMS21ACMF-183	LXMS21ACNP-184	LXMSANAA19-181	LXTBKZMCMG-010
Application	Small product management		Electronic equipment management		Garment management	Metal product management
Appearance						
RFID standard	ISO18000-63 and EPC Global Gen2(v1.2.0)	ISO18000-63 and EPC Global Gen2v2	ISO18000-63 and EPC Global Gen2v2	ISO18000-63 and EPC Global Gen2(v1.2.0)	ISO18000-63 and EPC Global Gen2v2	ISO18000-63 and EPC global Gen2v2
Frequency	865-928MHz				902-928MHz	865-928MHz
IC	NXP UCODE G2iM	Impinj Monza R6	Impinj Monza R6	NXP UCODE 7xm	Impinj Monza R6	Impinj Monza R6P
UID memory	256bit	96bit	96bit	448bit	96bit	128bit
NDEF memory	512bit	NA	NA	2048bit	NA	32bit
Size(L x W x H)	2.0 x 1.25 x 0.55 mm	1.2 x 1.2 x 0.55 mm	2.0 x 1.2 x 0.5 mm		40 x 6 x 0.9 mm	6 x 2.0 x 2.3mm
Read range*	10mm (500mW reader)	10mm (500mW reader)	9m (4W EIRP)	7m (4W EIRP)	2m (4W EIRP)	1.5m (4W EIRP)

*Reference

Note: Monza is a registered trademark of USA-based Impinj, Inc. in the United States and/or in other countries.
Note: ICODE and UCODE are registered trademarks of USA-based NXP Semiconductors N.V. in the United States and/or in other countries.

Femtet, CAE Software

User-Friendly Simulation Software Tailored for a Wide Range of Engineering Challenges

Femtet is a Multiphyiscs CAE software with multiple functionalities developed by Murata Manufacturing Co, Ltd.

Features

Femtet

Femtet is simulation software based on the finite element method. Its easy operation and comprehensive functionality make stress-free analysis environment possible.

Seven Solvers and Multiphysics

Solves seven major physical phenomena and multiphysics.

Efficient Designing

Capable of batch processing and parametric analysis that are essential for tuning and optimization of design.
VBA macro function is available to realize optimum design.

Comprehensive Functionalities

Equipped with comprehensive modules needed for modeling (CAD), meshing, simulations, and results display, it supports cost-effective simulation activities.

Database Management

Manages databases of materials, boundary conditions, body attributes, and models.
The database can be shared and used among a group of users.

CAD Translator

Lets you use the CAD data on hand right away by supporting various kinds of CAD formats to import and export.

Examples

Mechanical Stress

Thermal Conductivity



Electromagnetic Waves



Magnetic Fields



Electric Fields



Piezoelectricity

Acoustic Waves



Murata Software

Application Guides

AI speaker (Voice recognition)



1 Connectivity

Microwave Coaxial Connectors with Switch

Chip Multilayer LC Filters
LF Series

Chip Multilayer Hybrid Baluns
LDB/LDM Series

Chip Multilayer Diplexers
LFD Series

Chip Multilayer Hybrid Couplers
LDC/LDJ Series

Chip Inductors (Chip Coils)
LQP03HQ/LQW18AN Series

Crystal Units
XRC Series

2 Audio SoC/MPU

Crystal Units
XRC Series

MEMS Resonators
WMRAG Series

3 Traceability

RFID Tag
LXMS/LXTB Series

4 Speaker

Frequency Specified Noise Filters
BLF02 Series

Chip LC Trap Filters
LQZ02HQ Series

5 Peripheral Interface

Chip Common Mode Choke Coils
DLM0N/NFP0Q Series

6 Sensor

Pyroelectric Infrared Sensors
IRA-S Series

Ultrasonic Sensors
MA40 Series

7 DC-DC Converter

Power Inductors
DFEC Series

Power Inductors
DFES/LQH3NP Series

8 Power Conditioning

Thermistors
NCP03/NXR Series



Chip Ferrite Beads
BLM18/21 Series

Chip Common Mode Choke Coils
DLW5AT/5BT Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose GRM Series High Frequency Filter Circuit/Coupling/Decoupling/For Step-up

Hearable



1 Connectivity

RF Inductors
LQP02HQ/LQW15AN Series

Microwave Coaxial Cable Connectors
Microwave Coaxial Connectors with Switch

Chip Multilayer LC Filters
LF Series

Chip Multilayer Hybrid Baluns
LDB/LDM Series

Chip Multilayer Diplexers
LFD Series

Chip Multilayer Hybrid Couplers
LDC/LDJ Series

Chip LC Trap Filters
LQZ02HQ Series

Frequency Specified Noise Filters
BLF02RD Series

NFC Antennas
FLAN Series

Crystal Units
XRC Series

MEMS Resonators
WMRAG Series

2 Speaker

Chip LC Trap Filters
LQZ02HQ Series

Frequency Specified Noise Filters
BLF02 Series

3 Sensor

Thermistors
NCP03/FTN Series

4 DC-DC Converter

Power Inductors
DFE18SAN Series

5 Battery

Thermistors
NCP03/FTN Series

6 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose			
	Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up

HEMS



1 Energy · Management

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

2 Storage Battery

Thermistors
PRF/PRG/PTG/NCU Series

Isolated DC-DC Converters
MYB Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Chip Multilayer Ceramic Capacitors
for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding
SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc
Ceramic Capacitors for General Purpose
DE1/DE2 Series

Energy Storage Module Model
IJ1101M Series

BMU (Battery Management Unit)
IJ8101C Series

BMU-HUB
IJ1101K Series

3 Solar Panel

Isolated DC-DC Converters
MYB Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Chip Multilayer Ceramic Capacitors
for General Purpose
GR/GA Series

4 Smart Meter

Chip Multilayer LC Filters
LF Series

Chip Multilayer Hybrid Baluns
LDB/LDM Series

Wi-Fi Modules

LPWA Modules

Isolated DC-DC Converters
MYB Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Isolated DC-DC Converters
for PoE + PD
MYBSP Series

Chip Multilayer Ceramic Capacitors for Ethernet LAN
and Primary - Secondary Coupling of DC-DC Converters
GR4 Series

Safety Standard Certified Resin Molding
SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc
Ceramic Capacitors for General Purpose
DE1/DE2 Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series

Coin Manganese Dioxide Lithium Batteries
Standard Type/Heat-resistant Type

Microwave Coaxial
Connectors with Switch

MEMS Resonators
WMRAG Series

5 Home Gateway

Wi-Fi
Modules

Bluetooth
Modules

LPWA
Modules

Microwave Coaxial
Connectors with Switch

Isolated DC-DC Converters
for PoE + PD
MYBSP Series

Crystal Units
XRC Series

MEMS Resonators
WMRAG Series

6 Home Entertainment Equipment

Bluetooth Modules

Wi-Fi Modules

LPWA Modules

Ultrasonic Sensors
MA40 Series

Magnetic Sensors (AMR Sensors)
MR Series

Isolated DC-DC Converters
MYB Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Crystal Units
XRC Series

MEMS Resonators
WMRAG Series

7 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Smartmeter



1 Communication (Wireless)

Wi-Fi Modules

LPWA Modules

Chip Multilayer LC Filters
LF Series

Chip Multilayer Hybrid Baluns
LDB/LDM Series

Microwave Coaxial Connectors with Switch

ESD Protection Devices
LXES Series

Thermistors
NCP/PRF/PRG/NCU Series

Crystal Units
XRC Series

Chip Inductors (Chip Coils)
LQW/LQP/LQG Series

MEMS Resonators
WMRAG Series

2 Communication (Wired)

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Leaded MLCC for General Purpose
RDE Series

Thermistors
NCP/PRF/PRG/NCU Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

ESD Protection Devices
LXES Series

3 Metering

Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP Series

Thermistors
NCP/PRF/PRG/NCU Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series

Magnetic Sensors (AMR Sensors)
MR Series

MEMS Resonators
WMRAG Series

4 Power Conditioning

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYSLM Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series



Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Leaded MLCC for General Purpose
RDE Series

Chip Inductors (Chip Coils)
LQH Series

Thermistors
NCP/PRF/PRG/NCU Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Coin Manganese Dioxide Lithium Batteries
Standard Type/Heat-resistant Type

5 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Thermostat



1 CPU

Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
LLL/LLA/LLM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCP/PRF Series

MEMS Resonators
WMRAG Series

2 Display Panel

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Ceramic Resonators CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series

Thermistors
NCP/PRF Series

3 Interface

Bluetooth Modules

LPWA Modules

Wi-Fi Modules

Crystal Units
XRC Series

Ceramic Resonators CERALOCK
CST Series

Chip Inductors (Chip Coils)
LQM/LQH/LQB Series

ESD Protection Devices
LXES Series

Microwave Coaxial Connectors with Switch

MEMS Resonators
WMRAG Series

4 Temperature Sensor

Ceramic Resonators CERALOCK
CST Series

Thermistors
NCP/PRF/PRG/PTG Series

5 Humidity Sensor

Ceramic Resonators CERALOCK
CST Series

Thermistors
NCP/PRF/PRG/PTG Series

6 Power Management

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Thermistors
NCP/PRF/PRG Series

Ceramic Resonators CERALOCK
CST Series

7 Battery

Thermistors
NCP/PRF/PRG Series

8 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Human Detection



1 Microcontroller

Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
LLL/LLA/LLM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

Thermistors
NCP/PRF Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series

MEMS Resonators
WMRAG Series

3 Alarm

Piezoelectric Sounders
PKMCS/PKLCS /PKM Series

5 PIR Sensor

Isolated DC-DC Converters for PoE + PD
MYBSP Series

Silicon Capacitors

Pyroelectric Infrared Sensors
IRA-S Series

Ultrasonic Sensors
MA40 Series

2 LED

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Thermistors
NCP/PRF/PRG/ PTG Series

4 Connectivity

Wi-Fi Modules

Crystal Units
XRC Series

Chip Inductors (Chip Coils)
LQW/LQP/LQG Series

ESD Protection Devices
LXES Series

MEMS Resonators
WMRAG Series

6 Power Management

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Ceramic Resonators CERALOCK
CST Series

Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP Series

Thermistors
NCP/PRF/PRG Series

7 Battery

Coin Manganese Dioxide Lithium Batteries
Standard Type

Thermistors
NCP/PRF/PRG Series

8 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Air Dispenser



1 CPU

Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
LLL/LLA/LLM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCP/PRF Series

2 Driver

Thermistors
NCP/NXRT/PRF Series

3 Power Management

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Ceramic Resonators CERALOCK
CST Series

Thermistors
NCP/PRF Series

4 Battery

Thermistors
NXR/PRF/PRG Series

5 Traceability

RFID Tag
LXMS/LXTB Series

6 Air pump

Microblowers



7 Real-time Clock

MEMS Resonators
WMRAG Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Blood Pressure Monitor



1 AD/DA Converter

Chip Ferrite Beads
BLM Series

Thermistors
NCP Series

2 CPU

Ceramic Resonators
CERALOCK
CST Series

Thermistors
NCP/NXR Series

4 Sound Component

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series

3 Display Panel

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
NFM Series

Chip Ferrite Beads
BLM Series

Ceramic Resonators
CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCP Series

5 USB

Ceramic Resonators
CERALOCK
CST Series

Crystal Units
XRC Series

ESD Protection Devices
LXES Series

Thermistors
PRG Series

6 Connectivity

ESD Protection Devices
LXES Series

Bluetooth Smart Modules
LBCA/LBMA Series

Wi-Fi Modules

Crystal Units
XRC Series

Thermistors
PRG Series

MEMS Resonators
WMRAG Series

7 NFC

NFC Antennas
FLAN Series

Crystal Units
XRC Series

Chip Ferrite Beads
BLM Series

Chip Inductors (Chip Coils)
LQW18C/LQM18J Series

ESD Protection Devices
LXES Series

8 Power Supply Unit

Thermistors
NCP Series

Thermistors
PRF/PRG Series

Coin Manganese Dioxide Lithium Batteries
Standard Type

Isolated DC-DC Converters for PoE + PD
MYBSP Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/
OKL/MYLSM Series

9 Traceability

RFID Tag
LXMS/LXTB Series

10 Air pump

Microblowers



General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Thermometer



1 Temperature Detection

Thermistors
NXR Series

2 CPU

Ceramic Resonators CERALOCK
CST Series

3 Display Panel

Thermistors
NCP Series

4 Sound Component

Piezoelectric Sounders
PKLCS/PKMCS Series

5 Connectivity

Bluetooth Modules
LBCA/LBMA Series

Crystal Units
XRC Series

MEMS Resonators
WMRAG Series

6 NFC

NFC Antennas
FLAN Series

Crystal Units
XRC Series

Chip Ferrite Beads
BLM Series

Chip Inductors (Chip Coils)
LQW18C/LQM18J Series

ESD Protection Devices
LXES Series

7 Power Supply Unit

Coin Manganese Dioxide
Lithium Batteries
Standard Type

Alkaline Manganese
Batteries

8 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Blood Glucose Meter



1 AD/DA Converter

Chip Ferrite Beads
BLM Series

Thermistors
NCP Series

2 CPU

Ceramic Resonators CERALOCK
CST Series

Thermistors
NCP/NXR Series

3 Display Panel

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
NFM Series

Chip Ferrite Beads
BLM Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCP Series

4 Sound Component

Piezoelectric Sounders
PKLCS/PKMCS Series

5 USB

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
PRG Series

7 Power Supply Unit

Coin Manganese Dioxide Lithium Batteries
Standard Type

Isolated DC-DC Converters for PoE + PD
MYBSP Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Thermistors
NCP Series

Thermistors
PRF/PRG Series

6 Connectivity

Bluetooth Smart Modules
LBCA/LBMA Series

Wi-Fi Modules

Crystal Units
XRC Series

Thermistors
PRG Series

MEMS Resonators
WMRAG Series

8 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Diagnostic Imaging Apparatus



1 Photo Detector

Thermistors
NCP/PRF Series

2 DSP

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

3 Memory

Isolated
DC-DC Converters
MYB Series



Non-Isolated DC-DC Converters
MYMGK/MYSGK/
OKL/MYLSM Series

4 Control Circuit

Isolated DC-DC Converters
MYB Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Ceramic Resonators CERALOCK
CST Series

5 Display Panel

Metal Terminal Type Multilayer Ceramic Capacitors
for General Purpose
KRM Series

Ceramic Resonators
CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series



Isolated DC-DC Converters
for PoE + PD
MYBSP Series

Thermistors
PRF/PRG Series

6 DC-DC Converter

Metal Terminal Type Multilayer Ceramic Capacitors
for General Purpose
KRM Series

Polymer Aluminum
Electrolytic Capacitors
ECAS/ECNS Series

Thermistors
NCP/PRF Series

7 Power Supply

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard CertifiedLead Type Disc CeramicCapacitors for General Purpose
DE1/DE2 Series

Ceramic Resonators CERALOCK
CST Series

Thermistors
NCP/PRF Series

8 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Automotive

Powertrain/Safety

1. ECU
2. AT
3. Auxilliary Motors
4. TPMS
5. ABS/ESC
6. Headlamp
7. EPS
8. IMU
9. Fuel Injection System

1 ECU

Gyro Sensors
SCC Series

Metal Terminal Type Multilayer Ceramic Capacitors for Automotive
KCM Series

Chip Multilayer Ceramic Capacitors for Automotive
GCM Series

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive
GCJ Series

AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCG Series

Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCB Series

150°C/175°C/200°C Operation Leaded MLCC for Automotive
RH Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
PRF/PTG/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

High Reliability Common Mode Choke Coils
DLW31SH/DLW32SH/
DLW43SH/DLW43MH Series

Silicon Capacitors

2 AT

Accelerometers
SCA Series

Metal Terminal Type Multilayer Ceramic Capacitors for Automotive
KCM Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
PRF/PTG/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

3 Auxiliary Motors

Metal Terminal Type Multilayer Ceramic Capacitors for Automotive
KCM Series

150°C/175°C/200°C Operation Leaded MLCC for Automotive
RH Series

Ceramic Resonators CERALOCK
CST Series

Large-current Common Mode Choke Coils
PLT10HH/PLT5BP Series

Thermistors
PRF/PTG/NCU Series

Crystal Units
XRC Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

4 TPMS

Shock Sensors
For Tire Pressure Monitoring System, PKGS Series

Ceramic Filters CERAFIL
SFECF Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Pressure Sensor Elements
SCB10H Series

Thermistors
PRF/NCU Series

Antenna Coil
SA3M08 Series

Coin Manganese Dioxide Lithium Batteries
Heat-resistant Type

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

High Reliability Chip Inductors
LQG15HH Series

5 ABS/ESC

Accelerometers
SCA Series

Gyro Sensors
SCC Series

Metal Terminal Type Multilayer Ceramic Capacitors for Automotive
KCM Series

Chip Multilayer Ceramic Capacitors for Automotive
GCM Series

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive
GCJ Series

AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCG Series

Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCB Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCG18/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

6 Headlamp

Accelerometers
SCA Series

Chip Multilayer Ceramic Capacitors for Automotive
GCM Series

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive
GCJ Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCG18/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

7 EPS

Metal Terminal Type Multilayer Ceramic Capacitors for Automotive
KCM Series

Chip Multilayer Ceramic Capacitors for Automotive
GCM Series

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive
GCJ Series

AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCG Series

Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCB Series

Leaded MLCC for Automotive
RCE Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCG18/NCU Series

Thermistors
PRF/PTG/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

8 IMU

Gyro Sensors
SCC Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

9 Fuel Injection System

Leaded MLCC for Automotive
RCF Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

General Purpose (High Reliability)

Chip Multilayer Ceramic Capacitors for Automotive	GCM Series	Coupling/Decoupling	150°c
Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive	GCB Series	Coupling/Decoupling	
Leaded MLCC for Automotive	RCE Series	Noise Suppression/Decoupling	125°c
150°C/175°C/200°C Operation Leaded MLCC for Automotive	RH Series	Noise Suppression/Decoupling	150°c 175°c 200°c
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for Automotive/Feed Through Noise Filters	NFM_H/NFE_H Series	Noise Suppression	125°c
Chip Inductors (Chip Coils)	LQH32PH/LQH44PH/LQH43PH/LQH5BPH Series	Voltage Conversion	125°c
Chip Inductors (Chip Coils)	LQG15HH Series	Impedance Matching/Choke	125°c
Chip Ferrite Beads	BLM_SH/BLM_BH/BLE_SH Series	Noise Suppression	125°c
Chip Common Mode Choke Coils	DLW31SH/DLW32SH/DLW43SH/DLW43MH/DLW5ATH/DLW5BTH Series	Common Mode Noise Suppression	125°c

125°c 125°c max. 150°c 150°c max. 175°c 175°c max. 200°c 200°c max.

HEV/PHEV/EV

1. Charger
2. BMS
3. Electrically-Driven Compressor
4. Electric Pump
5. Inverter
6. DC-DC Converter

1 Charger

- Metal Terminal Type Multilayer Ceramic Capacitors for Automotive — KCM Series
- Chip Multilayer Ceramic Capacitors for Automotive — GCM Series
- Soft Termination Chip Multilayer Ceramic Capacitors for Automotive — GCJ Series
- Safety Standard Certified Lead Type Disc Ceramic Capacitors for Automotive — DE6 Series
- High Temperature Film Capacitors for Automotive — FH Series
- Ceramic Resonators CERALOCK — CST Series
- Crystal Units — XRC Series
- Large-current Common Mode Choke Coils — PLT10HH/PLT5BP Series
- Thermistors — PRF/PTG/NCU Series
- High Reliability Chip Ferrite Beads — BLM_SH1/BH1/TH1/JH1 Series

2 BMS

- Metal Terminal Type Multilayer Ceramic Capacitors for Automotive — KCM Series
- Chip Multilayer Ceramic Capacitors for Automotive — GCM Series
- Soft Termination Chip Multilayer Ceramic Capacitors for Automotive — GCJ Series
- AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive — GCG Series
- Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive — GCB Series
- Ceramic Resonators CERALOCK — CST Series
- Crystal Units — XRC Series
- Thermistors — PRF/PTG/NCU Series
- High Reliability Chip Ferrite Beads — BLM_SH1/BH1/TH1/JH1 Series

3 Electrically-Driven Compressor

- Metal Terminal Type Multilayer Ceramic Capacitors for Automotive — KCM Series
- Chip Multilayer Ceramic Capacitors for Automotive — GCM Series
- Soft Termination Chip Multilayer Ceramic Capacitors for Automotive — GCJ Series
- AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive — GCG Series
- Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive — GCB Series
- Thermistors — PRF/PTG/NCU Series
- High Temperature Film Capacitors for Automotive — FH Series
- Ceramic Resonators CERALOCK — CST Series
- Crystal Units — XRC Series
- High Reliability Chip Ferrite Beads — BLM_SH1/BH1/TH1/JH1 Series

4 Electric Pump

- Metal Terminal Type Multilayer Ceramic Capacitors for Automotive — KCM Series
- Chip Multilayer Ceramic Capacitors for Automotive — GCM Series
- Soft Termination Chip Multilayer Ceramic Capacitors for Automotive — GCJ Series
- AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive — GCG Series
- Large-current Common Mode Choke Coils — PLT10HH/PLT5BP Series
- Thermistors — PRF/PTG/NCU Series
- High Temperature Film Capacitors for Automotive — FH Series
- Ceramic Resonators CERALOCK — CST Series
- Crystal Units — XRC Series
- High Reliability Chip Ferrite Beads — BLM_SH1/BH1/TH1/JH1 Series

5 Inverter

Metal Terminal Type Multilayer Ceramic Capacitors for Automotive
KCM Series

Chip Multilayer Ceramic Capacitors for Automotive
GCM Series

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive
GCJ Series

AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCG Series

Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCB Series

150°C/175°C/200°C Operation Leaded MLCC for Automotive
RH Series

Large-current Common Mode Choke Coils
PLT10HH/PLT5BP Series



Thermistors
PRF/PTG/NCU Series

High Temperature Film Capacitors for Automotive
FH Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

6 DC-DC Converter

Metal Terminal Type Multilayer Ceramic Capacitors for Automotive
KCM Series

Chip Multilayer Ceramic Capacitors for Automotive
GCM Series

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive
GCJ Series

AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCG Series

Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCB Series

High Temperature Film Capacitors for Automotive
FH Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Large-current Common Mode Choke Coils
PLT10HH/PLT5BP Series



Thermistors
PRF/PTG/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

General Purpose

AEC-Q 200 Compliant Chip Multilayer Ceramic Capacitors for Infortainment	GRT Series	Coupling/Decoupling
Chip Inductors (Chip Coils)	LQW Series	Matching/High Frequency Choke
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
EMI Suppression Filters EMIFIL	NFL/NFE Series	Noise Suppression
Chip Common Mode Choke Coils	DLW Series	Common Mode Noise Suppression

General Purpose (High Reliability)

Chip Multilayer Ceramic Capacitors for Automotive	GCM Series	Coupling/Decoupling	150°c
Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive	GCB Series	Coupling/Decoupling	
Leaded MLCC for Automotive	RCE Series	Noise Suppression/Decoupling	125°c
150°C/175°C/200°C Operation Leaded MLCC for Automotive	RH Series	Noise Suppression/Decoupling	150°c 175°c 200°c
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for Automotive/Feed Through Noise Filters	NFM_H/NFE_H Series	Noise Suppression	125°c
Chip Inductors (Chip Coils)	LQH32PH/LQH44PH/LQH43PH/LQH5BPH Series	Voltage Conversion	125°c
Chip Inductors (Chip Coils)	LQG15HH Series	Impedance Matching/Choke	125°c
Chip Ferrite Beads	BLM_SH/BLM_BH/BLE_SH Series	Noise Suppression	125°c
Chip Common Mode Choke Coils	DLW31SH/DLW32SH/DLW43SH/DLW43MH/DLW5ATH/DLW5BTH Series	Common Mode Noise Suppression	125°c

125°c 125°c max. 150°c 150°c max. 175°c 175°c max. 200°c 200°c max.

Information/Comfort/Accessory

1. Navigation/ Infotainment
2. Remote Keyless Entry
3. Meter/HUD
4. Power Seat/ Power Mirror
5. Parking Assist

1 Navigation/Infotainment

- Accelerometers SCA Series
- Gyro Sensors SCC Series
- Ceramic Filters CERAFIL SFECF Series
- Piezoelectric Sounders PKLCS/PKMCS Series
- Bluetooth Modules
- Wi-Fi Modules
- DC-DC Converters
- Ceramic Resonators CERALOCK CST Series
- Crystal Units XRC Series
- Thermistors PRF/PRG/PTG/NCU Series
- Chip Multilayer Diplexers LFD Series
- Chip Multilayer LC Filters LF Series
- Chip Multilayer Hybrid Baluns LDB/LDM Series
- Chip Multilayer Hybrid Couplers LDC/LDJ Series
- Chip Ferrite Beads BLM Series

2 Remote Keyless Entry

- Ceramic Filters CERAFIL SFECF Series
- Ceramic Resonators CERALOCK CST Series
- Crystal Units XRC Series
- Piezoelectric Sounders PKLCS/PKMCS Series
- Antenna Coils SA3D14/SA3D12/SA3M08 Series
- Coin Manganese Dioxide Lithium Batteries Standard Type
- Chip Inductors (Chip Coils) LQW/LQP/LQG Series
- Chip Ferrite Beads BLM Series

3 Meter/HUD

- DC-DC Converters
- Ceramic Resonators CERALOCK CST Series
- Crystal Units XRC Series
- Thermistors PRF/PTG/NCU Series
- Chip Ferrite Beads BLM Series
- Piezoelectric Sounders PKLCS/PKMCS Series

4 Power Seat/Power Mirror

Piezoelectric Sounders
PKLCS/PKMCS Series



Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
PRF/PTG/NCU Series

Chip Ferrite Beads
BLM Series

5 Parking Assist

Gyro Sensors
SCC Series

Ultrasonic Sensors
MA58 Series

Piezoelectric Sounders
PKLCS/PKMCS Series



Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
PRF/PTG/NCU Series

Chip Ferrite Beads
BLM Series

General Purpose

AEC-Q 200 Compliant Chip Multilayer Ceramic Capacitors for Infortainment	GRT Series	Coupling/Decoupling
Chip Inductors (Chip Coils)	LQW Series	Matching/High Frequency Choke
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
EMI Suppression Filters EMIFIL	NFL/NFE Series	Noise Suppression
Chip Common Mode Choke Coils	DLW Series	Common Mode Noise Suppression

General Purpose (High Reliability)

Chip Multilayer Ceramic Capacitors for Automotive	GCM Series	Coupling/Decoupling	150°c
Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive	GCB Series	Coupling/Decoupling	
Leaded MLCC for Automotive	RCE Series	Noise Suppression/Decoupling	125°c
150°C/175°C/200°C Operation Leaded MLCC for Automotive	RH Series	Noise Suppression/Decoupling	150°c 175°c 200°c
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for Automotive/Feed Through Noise Filters	NFM_H/NFE_H Series	Noise Suppression	125°c
Chip Inductors (Chip Coils)	LQH32PH/LQH44PH/LQH43PH/LQH5BPH Series	Voltage Conversion	125°c
Chip Inductors (Chip Coils)	LQG15HH Series	Impedance Matching/Choke	125°c
Chip Ferrite Beads	BLM_SH/BLM_BH/BLE_SH Series	Noise Suppression	125°c
Chip Common Mode Choke Coils	DLW31SH/DLW32SH/DLW43SH/DLW43MH/DLW5ATH/DLW5BTH Series	Common Mode Noise Suppression	125°c

125°c 125°c max. 150°c 150°c max. 175°c 175°c max. 200°c 200°c max.

Bike/EV Bike

Electromotive

1. Charger/Battery
2. Inverter
3. DC-DC Converter

Electric Installation

4. Accelerometer for Fuel Cut
5. Headlamp
6. Fuel Injection System

1 Charger/Battery

- Lithium Ion Storage Modules
- Metal Terminal Type Multilayer Ceramic Capacitors for Automotive KCM Series
- Chip Multilayer Ceramic Capacitors for Automotive GCM Series
- Soft Termination Chip Multilayer Ceramic Capacitors for Automotive GCJ Series
- Safety Standard Certified Lead Type Disc Ceramic Capacitors for Automotive DE6 Series
- Ceramic Resonators CERALOCK CST Series
- Crystal Units XRC Series
- Large-current Common Mode Choke Coils PLT10HH/PLT5BP Series
- Thermistors PRF/PTG/NCU Series
- High Reliability Chip Ferrite Beads BLM_SH1/BH1/TH1/JH1 Series

2 Inverter

- Chip Multilayer Ceramic Capacitors for Automotive GCM Series
- Soft Termination Chip Multilayer Ceramic Capacitors for Automotive GCJ Series
- AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive GCG Series
- Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive GCB Series
- 150°C/175°C/200°C Operation Leaded MLCC for Automotive RH Series
- Large-current Common Mode Choke Coils PLT10HH/PLT5BP Series
- Ceramic Resonators CERALOCK CST Series
- Crystal Units XRC Series
- High Reliability Chip Ferrite Beads BLM_SH1/BH1/TH1/JH1 Series
- Thermistors PRF/PTG/NCU Series

3 DC-DC Converter

- DC-DC Converters MYPMA Series
- Metal Terminal Type Multilayer Ceramic Capacitors for Automotive KCM Series
- Chip Multilayer Ceramic Capacitors for Automotive GCM Series
- Soft Termination Chip Multilayer Ceramic Capacitors for Automotive GCJ Series
- AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive GCG Series
- Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive GCB Series
- Ceramic Resonators CERALOCK CST Series
- Crystal Units XRC Series
- Large-current Common Mode Choke Coils PLT10HH/PLT5BP Series
- Thermistors PRF/PTG/NCU Series
- High Reliability Chip Ferrite Beads BLM_SH1/BH1/TH1/JH1 Series

4 Accelerometer for Fuel Cut

Accelerometers
SCA Series

Gyro Sensors
SCC Series

Metal Terminal Type Multilayer Ceramic Capacitors for Automotive
KCM Series

Chip Multilayer Ceramic Capacitors for Automotive
GCM Series

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive
GCJ Series

AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCG Series

Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCB Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCG18/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

5 Headlamp

Accelerometers
SCA Series

Gyro Sensors
SCC Series

Chip Multilayer Ceramic Capacitors for Automotive
GCM Series

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive
GCJ Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCG18/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

6 Fuel Injection System

Metal Terminal Type Multilayer Ceramic Capacitors for Automotive
KCM Series

Chip Multilayer Ceramic Capacitors for Automotive
GCM Series

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive
GCJ Series

AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCG Series

Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCB Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
PRF/PTG/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

General Purpose

AEC-Q 200 Compliant Chip Multilayer Ceramic Capacitors for Infortainment	GRT Series	Coupling/Decoupling
Chip Inductors (Chip Coils)	LQW Series	Matching/High Frequency Choke
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
EMI Suppression Filters EMIFIL	NFL/NFE Series	Noise Suppression
Chip Common Mode Choke Coils	DLW Series	Common Mode Noise Suppression

General Purpose (High Reliability)

Chip Multilayer Ceramic Capacitors for Automotive	GCM Series	Coupling/Decoupling	150°c
Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive	GCB Series	Coupling/Decoupling	
Leaded MLCC for Automotive	RCE Series	Noise Suppression/Decoupling	125°c
150°C/175°C/200°C Operation Leaded MLCC for Automotive	RH Series	Noise Suppression/Decoupling	150°c 175°c 200°c
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for Automotive/Feed Through Noise Filters	NFM_H/NFE_H Series	Noise Suppression	125°c
Chip Inductors (Chip Coils)	LQH32PH/LQH44PH/LQH43PH/LQH5BPH Series	Voltage Conversion	125°c
Chip Inductors (Chip Coils)	LQG15HH Series	Impedance Matching/Choke	125°c
Chip Ferrite Beads	BLM_SH/BLM_BH/BLE_SH Series	Noise Suppression	125°c
Chip Common Mode Choke Coils	DLW31SH/DLW32SH/DLW43SH/DLW43MH/DLW5ATH/DLW5BTH Series	Common Mode Noise Suppression	125°c

125°c 125°c max. 150°c 150°c max. 175°c 175°c max. 200°c 200°c max.

Smart Phones



1 Cellular RF

SAW Duplexers
SAY Series

SAW Filters
SAF Series

Chip Multilayer LC Filters
LF Series

Chip Multilayer Diplexers
LFD Series

Chip Multilayer Hybrid Baluns
LDB/LDM Series

Chip Multilayer Hybrid Dividers
LDD Series

Chip Multilayer Hybrid Couplers
LDC/LDJ Series

High-Frequency Matching Transformers
SMST Series

Microwave Coaxial Cable Connectors
Microwave Coaxial Connectors with Switch

Chip Inductors (Chip Coils)
LQW/LQP Series

ESD Protection Devices
LXES Series

Band-Selectable Phase Adjustment Device (B-SPADE)

Thermistors
NCP/PRF Series

2 Cellular BB

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
NFM Series

Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP Series

Frequency Specified Noise Filters
BLF Series

Chip LC Trap Filters
LQZ02HQ Series

Thermistors
NCP/PRF Series

3 CPU

Crystal Units
XRC Series

Chip Ferrite Beads
BLM Series

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
NFM Series

Silicon Capacitors

Thermistors
NCP/PRF Series

4 Display Panel

Ceramic Resonators CERALOCK
CST Series

EMI Suppression Filters EMIFIL
NFA Series

ESD Protection Devices
LXES Series

Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP Series

Thermistors
NCP/PRF Series

5 Camera Module

Chip Multilayer Ceramic Capacitors for Camera Flash Circuit Only
GR7 Series

Chip Ferrite Beads
BLM Series

ESD Protection Devices
LXES Series

Thermistors
NCP/PRF Series

6 USB

Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP/DLM Series

Chip Ferrite Beads
BLM Series

ESD Protection Devices
LXES Series

Thermistors
NCP/PRF Series

7 Connectivity

Chip Multilayer Diplexers
LFD Series

Chip Multilayer Hybrid Couplers
LDC/LDJ Series

Bluetooth Modules

Wi-Fi Modules

Bluetooth - Wi-Fi Combo Modules

SAW Filters
SAF Series

Chip Multilayer LC Filters
LF Series

Chip Multilayer Hybrid Baluns
LDB/LDM Series

Microwave Coaxial Cable Connectors
Microwave Coaxial Connectors with Switch



ESD Protection Devices
LXES Series

Thermistors
NCP/PRF Series

Crystal Units
XRC Series

8 NFC

NFC Antennas
FLAN Series

Crystal Units
XRC Series

Chip Ferrite Beads
BLM Series

Chip Inductors (Chip Coils)
LQW18C/LQM18J Series

Variable Capacitors
LXRW Series

ESD Protection Devices
LXES Series

9 DC-DC Converter

Chip Multilayer Ceramic Capacitors
on Interposer Board for General Purpose
ZRB Series

Metal Terminal Type Multilayer Ceramic Capacitors
for General Purpose
KRM Series

Polymer Aluminum
Electrolytic Capacitors
ECAS/ECNS Series

Thermistors
NCP/PRF Series

10 Battery

Thermistors
NCP/PRF/PRG Series

12 Traceability

RFID Tag
LXMS/LXTB Series

11 Power Supply

Chip Multilayer
Ceramic Capacitors
for General Purpose
GR/GA Series

Safety Standard Certified Resin
Molding SMD Type Ceramic
Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc
Ceramic Capacitors for General Purpose
DE1/DE2 Series

Chip Inductors (Chip Coils)
LQM/LQH/DFE Series

MEMS Resonators
WMRAG Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Wearable Devices



1 Connectivity

Bluetooth Modules
Wi-Fi Modules
Bluetooth - Wi-Fi Combo Modules
SAW Filters
SAF Series
Chip Multilayer LC Filters
LF Series
Chip Multilayer Hybrid Baluns
LDB/LDM Series
Chip Multilayer Diplexers
LFD Series
Chip Multilayer Hybrid Couplers
LDC/LDJ Series
Microwave Coaxial Cable Connectors
Microwave Coaxial Connectors with Switch
Crystal Units
XRC Series
ESD Protection Devices
LXES Series
Thermistors
NCP/PRF Series
MEMS Resonators
WMRAG Series

2 NFC

NFC Antennas
FLAN Series
Crystal Units
XRC Series
Chip Inductors (Chip Coils)
LQW18C/LQM18J Series
Variable Capacitors
LXRW Series
ESD Protection Devices
LXES Series

3 Cellular RF

Chip Multilayer Diplexers
LFD Series
SAW Duplexers
SAY Series
SAW Filters
SAF Series
Chip Multilayer LC Filters
LF Series
Chip Multilayer Hybrid Baluns
LDB/LDM Series
Chip Multilayer Hybrid Dividers
LDD Series
Chip Multilayer Hybrid Couplers
LDC/LDJ Series
High-Frequency Matching Transformers
SMST Series
Microwave Coaxial Cable Connectors
Microwave Coaxial Connectors with Switch
ESD Protection Devices
LXES Series
Band-Selectable Phase Adjustment Device
(B-SPADE)
Thermistors
NCP/PRF Series

4 Cellular BB

Thermistors
NCP/PRF Series

5 CPU

Crystal Units
XRC Series
Silicon Capacitors
Thermistors
NCP/PRF Series

6 Display Panel

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

ESD Protection Devices
LXES Series

Thermistors
NCP/PRF Series

7 Camera Module

Chip Multilayer Ceramic Capacitors
for Camera Flash Circuit Only
GR7 Series

ESD Protection Devices
LXES Series

Thermistors
NCP/PRF Series

8 Peripheral Interface

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Chip Common Mode Choke Coils/
Common Mode Noise Filters
DLW/DLP/NFP/DLM Series

ESD Protection Devices
LXES Series

Thermistors
NCP/PRF Series

9 Sensor

Thermistors
NCP/PRF Series

10 DC-DC Converter

Chip Multilayer Ceramic Capacitors
on Interposer Board
for General Purpose
ZRB Series

Metal Terminal Type
Multilayer Ceramic Capacitors
for General Purpose
KRM Series

Polymer Aluminum
Electrolytic Capacitors
ECAS/ECNS Series

Thermistors
NCP Series

11 Battery

Coin Manganese Dioxide
Lithium Batteries
Standard Type

Thermistors
NCP/PRF/PRG Series

12 Wireless Power Charge

LW Reversed Low ESL Chip
Multilayer Ceramic Capacitors
for General Purpose
LLL Series

Thermistors
NCP/PRF Series

13 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Piezoelectric Sounders	PKLCS/PKMCS Series	Sound Component

Base Stations



1 Cellular RF

Chip Multilayer Diplexers
LFD Series

Chip Multilayer LC Filters
LF Series

Chip Multilayer Hybrid Baluns
LDB/LDM Series

Chip Multilayer Hybrid Couplers
LDC/LDJ Series

Chip Inductors (Chip Coils)
LQW/LQP/LQG Series

ESD Protection Devices
LXES Series

Thermistors
PRF Series

Precision TCXO
XTCLH/XNCLH Series

Silicon Capacitors

Single-Layer Microchip Capacitors
CLB Series

Thin Film Circuit Substrates (RUSUB)
RU Series

MEMS Resonators
WMRAG Series

2 Cellular BB

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
NFM Series

Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP Series

Precision TCXO
XTCLH/XNCLH Series

Thermistors
PRF Series

3 CPU

Crystal Units
XRC Series

Chip Ferrite Beads
BLM Series

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
NFM Series

Thermistors
PRF Series

4 Connectivity

Wi-Fi Modules

Chip Multilayer LC Filters
LF Series

Chip Multilayer Hybrid Baluns
LDB/LDM Series

Chip Multilayer Diplexers
LFD Series

Chip Multilayer Hybrid Couplers
LDC/LDJ Series

ESD Protection Devices
LXES Series

Thermistors
PRF Series

Crystal Units
XRC Series

5 DC-DC Converter

Isolated DC-DC Converters
MYB Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Thermistors
PRF Series

6 Power Supply (AC)

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Chip Inductors (Chip Coils)
LQM/LQH/DFE Series

7 Power Supply (PoE)

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Crystal Units
XRC Series

Chip Inductors (Chip Coils)
LQM/LQH/DFE Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series



8 Li-ion Energy Storage System

Energy Storage Module Model
IJ1101M Series

BMU (Battery Management Unit)
IJ8101C Series

BMU-HUB
IJ1101K Series

9 Asset Management

RFID Tag
LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Coin Manganese Dioxide Lithium Batteries	Standard Type/Heat-resistant Type	Battery Backup

G-PON



1 Optical Transmitter Module/Optical Receiver Module

Wire Bonding Mount Multilayer Microchip Capacitors for General Purpose
GMA Series

Wire Bonding/AuSn Soldering Mount Chip Multilayer Ceramic Capacitors for General Purpose
GMD Series

Single-Layer Microchip Capacitors
CLB Series

Thin Film Circuit Substrates (RUSUB)
RU Series

Silicon Capacitors

2 DC-DC Converter

Isolated DC-DC Converters
MYB Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Thermistors
PRF Series

3 Interface

Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
LLL/LLA/LLM Series

Crystal Units
XRC Series

Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP/DLM Series

ESD Protection Devices
LXES Series

4 Routers

Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
LLL/LLA/LLM Series

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Wire Bonding Mount Multilayer Microchip Capacitors for General Purpose
GMA Series

Wire Bonding/AuSn Soldering Mount Chip Multilayer Ceramic Capacitors for General Purpose
GMD Series

Crystal Units
XRC Series

Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP Series

Single-Layer Microchip Capacitors
CLB Series

Thin Film Circuit Substrates (RUSUB)
RU Series

Precision TCXO
XTCLH/XNCLH Series

5 Servers

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

6 Asset Management

RFID Tag
LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Coin Manganese Dioxide Lithium Batteries	Standard Type/Heat-resistant Type	Battery Backup

Lighting



1 Lighting Equipment

Ballast for LED Lighting

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Wi-Fi Modules

LPWA Modules

Thermistors
NCP/PRF/PRG/PTG Series

Microwave Coaxial Connectors with Switch

Piezoelectric Sounders
PKLCS/PKMCS Series

Crystal Units
XRC Series

2 Lighting Control

Wi-Fi Modules

LPWA Modules

Crystal Units
XRC Series

Ceramic Resonators CERALOCK
CST Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series

Microwave Coaxial Connectors with Switch

Pyroelectric Infrared Sensors
IRA-S Series

Ultrasonic Sensors
MA40 Series

MEMS Resonators
WMRAG Series

3 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Data Center





1 Environmental Monitoring

Wi-Fi Modules

LPWA Modules

Magnetic Sensors (AMR Sensors)
MR Series

Thermistors
NCU Series

MEMS Resonators
WMRAG Series

2 Server

Isolated DC-DC Converters
MYB Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

3 Switch/Router

Isolated DC-DC Converters
MYB Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/
MYLSM Series

Low ESL Chip Multilayer
Ceramic Capacitors
for General Purpose
LLL/LLA/LLM Series

Chip Multilayer
Ceramic Capacitors
for General Purpose
GR/GA Series

Wire Bonding Mount Multilayer
Microchip Capacitors
for General Purpose
GMA Series

Wire Bonding/AuSn Soldering Mount
Chip Multilayer Ceramic Capacitors
for General Purpose
GMD Series

Chip Common Mode Choke Coils/
Common Mode Noise Filters
DLW/DLP/NFP Series

Crystal Units
XRC Series

Silicon Capacitors

Precision TCXO
XTCLH/XNCLH Series

Single-Layer Microchip Capacitors
CLB Series

Thin Film Circuit Substrates (RUSUB)
RU Series

4 Li-ion Energy Storage System

Energy Storage Module Model
IJ1101M Series

BMU
(Battery Management Unit)
IJ8101C Series

BMU-HUB
IJ1101K Series

5 Asset Management

RFID Tag
LXTB Series

6 Power Supply

AC-DC Power Supplies 1U Frond End

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Coin Manganese Dioxide Lithium Batteries	Standard Type/Heat-resistant Type	Battery Backup

Industrial Automation



1 PLC/Industrial PC

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

Chip Ferrite Beads
BLM Series

3 Terminals Low ESL Chip
Multilayer Ceramic Capacitors for General Purpose
NFM Series

Thermistors
PRF/NCU Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series

MEMS Resonators
WMRAG Series

2 Sensor · Actuator

Accelerometers
SCA Series

Gyro sensors
SCC Series

Magnetic Sensors (AMR Sensors)
MR Series

3 Programmable Display

Ceramic Resonators
CERALOCK
CST Series

Crystal Units
XRC Series

Power Inductors
LQH Series

Chip Common Mode Choke Coils/
Common Mode Noise Filters
DLW/DLP/NFP Series

Coin Manganese Dioxide
Lithium Batteries
Standard Type/Heat-resistant Type

Non-Isolated DC-DC Converters
MYMGK/MYSGK/
OKL/MYLSM Series

Isolated DC-DC Converters
for PoE + PD
MYBSP Series

4 Interface (LAN · USB · RS485/232 · Wireless Communication)

Wireless Communication Modules
Based on the ISA100 Wireless™ Standard
Type 1EU

MEMS Resonators
WMRAG Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

Chip Common Mode Choke Coils/Common Mode Noise Filters
DLW/DLP/NFP/DLM Series

ESD Protection Devices
LXES Series

Thermistors
PRG Series

5 Motor Driver/AC Servo/Inverter

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Large-current Common Mode Choke Coils
PLT10/PLT5B/DLW5A/DLW5B/UCMH Series

Thermistors
PRF/PTG Series

MEMS Resonators
WMRAG Series

6 DC-DC Converter (Module · Component)

Isolated DC-DC Converters
MYB Series



Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Metal Terminal Type Multilayer
Ceramic Capacitors for General Purpose
KRM Series

Polymer Aluminum
Electrolytic Capacitors
ECAS/ECNS Series

Power Inductors
LQH Series

Thermistors
PRF/NCU Series

7 Power Supply (Component for AC-DC Converter)

Chip Multilayer Ceramic Capacitors
for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding
SMD Type Ceramic Capacitors
for General Purpose
DK1 Series

Safety Standard Certified Lead Type
Disc Ceramic Capacitors
for General Purpose
DE1/DE2 Series

Ceramic Resonators CERALOCK
CST Series

Thermistors
PRF/NCU Series

8 Production Control

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Piezoelectric Sounders	PKLCS/PKMCS Series	Sound Component

3D Printer



1 CPU

Isolated DC-DC Converters
MYB Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Ceramic Resonators CERALOCK
CST Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

Thermistors
NCP/PRF Series

2 Display Panel/Buzzer

Ceramic Resonators CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/
PKM Series

MEMS Resonators
WMRAG Series

3 Interface

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

Chip Common Mode Choke Coils/
Common Mode Noise Filters
DLW/DLP/NFP/DLM Series

ESD Protection Devices
LXES Series

Thermistors
PRG Series

4 Connectivity

Wi-Fi Modules

Crystal Units
XRC Series

Chip Inductors (Chip Coils)
LQW/LQP/LQG Series

ESD Protection Devices
LXES Series

5 Motor Drive

Isolated DC-DC Converters
MYB Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Large-current Common Mode Choke Coils
PLT10HH/PLT5BPH/DLW5ATN/UCMH Series

Thermistors
PRF/PTG Series

6 Heated Printer Head

Thermistors
NCP/PRF Series

7 DC-DC Converter

Metal Terminal Type Multilayer Ceramic Capacitorsfor General Purpose
KRM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series



Thermistors
NCP/PRF Series

8 Power Supply

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Thermistors
NCP/PRF/PRG Series

9 Asset Management

RFID Tag
LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Electronic POS



1 CPU

ESD Protection Devices
LXES Series

Ceramic Resonators CERALOCK
CST Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/
OKL/MYLSM Series

Crystal Units
XRC Series

MEMS Resonators
WMRAG Series

2 Digital Panel/Buzzer

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Ceramic Resonators CERALOCK
CST Series

Power Inductors
LQH Series

Thermistors
PRF/PRG Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series

3 Interface

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP/DLM Series

ESD Protection Devices
LXES Series

Thermistors
PRG Series

Ceramic Resonators CERALOCK
CST Series

4 Connectivity

Bluetooth Modules

Bluetooth - Wi-Fi Combo Modules

Bluetooth Smart Modules

Wi-Fi Modules

NFC Antennas
FLAN Series

Crystal Units
XRC Series

Microwave Coaxial Connectors with Switch

5 DC-DC Converter

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Power Inductors
LQH/DEM/DFE Series

Thermistors
NCP/PRF Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series



6 Battery

Thermistors
NCP/PRF/PRG Series

7 Power Supply

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Thermistors
NCP/PRF/PRG Series

8 RFID Reader/Writer(HF)

Crystal Units
XRC Series

9 RFID Reader/Writer(UHF)

Crystal Units
XRC Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Coin Manganese Dioxide Lithium Batteries	Standard Type	Battery Backup

Heavy Duty Vehicles

Safety

1. ECU
2. TPMS
3. ABS/ESC
4. Headlamp

Comfort/Information

5. Fine Navigation
6. Power Seat/ Power Mirror
7. Cabin Leveling

Operation

8. Motor Grader/Blade Control
9. Forklift/Container Handling

Safety

1 ECU

Accelerometers
SCA Series

Gyro Sensors
SCC Series

Metal Terminal Type Multilayer Ceramic Capacitors for Automotive
KCM Series

Chip Multilayer Ceramic Capacitors for Automotive
GCM Series

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive
GCJ Series

AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCG Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCB Series

Leaded MLCC for Automotive
RH/RCE Series

Thermistors
PRF/PTG/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

2 TPMS

Shock Sensors For Tire Pressure Monitoring System, PKGS Series

Pressure Sensor Elements
SCB10H Series

Thermistors
PRF/NCU Series

Ceramic Filters CERAFIL
SFECF Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Coin Manganese Dioxide Lithium Batteries
Heat-resistant Type

High Reliability Chip Inductors
LQG15HH Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

3 ABS/ESC

Accelerometers
SCA Series

Gyro Sensors
SCC Series

Metal Terminal Type Multilayer Ceramic Capacitors for Automotive
KCM Series

Chip Multilayer Ceramic Capacitors for Automotive
GCM Series

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive
GCJ Series

AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCG Series

Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive
GCB Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCG18/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

4 Headlamp

Chip Multilayer Ceramic Capacitors for Automotive
GCM Series

Soft Termination Chip Multilayer Ceramic Capacitors for Automotive
GCJ Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCG18/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

Comfort/Information

5 Fine Navigation

Accelerometers
SCA Series

Gyro Sensors
SCC Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

Ceramic Resonators
CERALOCK
CST Series

Crystal Units
XRC Series

6 Power Seat/Power Mirror

Piezoelectric Sounders
PKLCS/PKMCS Series



Ceramic Resonators
CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
PRF/PTG/NCU Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

7 Cabin Leveling

Accelerometers
SCA Series

Gyro Sensors
SCC Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

Operation

8 Motor Grader/Blade Control

Accelerometers
SCA Series

Gyro Sensors
SCC Series

Crystal Units
XRC Series

Ceramic Resonators CERALOCK
CST Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

9 Forklift/Container Handling

Accelerometers
SCA Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

High Reliability Chip Ferrite Beads
BLM_SH1/BH1/TH1/JH1 Series

General Purpose

AEC-Q 200 Compliant Chip Multilayer Ceramic Capacitors for Infortainment	GRT Series	Coupling/Decoupling
Chip Inductors (Chip Coils)	LQW Series	Matching/High Frequency Choke
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
EMI Suppression Filters EMIFIL	NFL/NFE Series	Noise Suppression
Chip Common Mode Choke Coils	DLW Series	Common Mode Noise Suppression

General Purpose (High Reliability)

Chip Multilayer Ceramic Capacitors for Automotive	GCM Series	Coupling/Decoupling	150°c
Ni Plating + Pd Plating Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive	GCB Series	Coupling/Decoupling	
Leaded MLCC for Automotive	RCE Series	Noise Suppression/Decoupling	125°c
150°C/175°C/200°C Operation Leaded MLCC for Automotive	RH Series	Noise Suppression/Decoupling	150°c 175°c 200°c
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for Automotive/Feed Through Noise Filters	NFM_H/NFE_H Series	Noise Suppression	125°c
Chip Inductors (Chip Coils)	LQH32PH/LQH44PH/LQH43PH/LQH5BPH Series	Voltage Conversion	125°c
Chip Inductors (Chip Coils)	LQG15HH Series	Impedance Matching/Choke	125°c
Chip Ferrite Beads	BLM_SH/BLM_BH/BLE_SH Series	Noise Suppression	125°c
Chip Common Mode Choke Coils	DLW31SH/DLW32SH/DLW43SH/DLW43MH/DLW5ATH/DLW5BTH Series	Common Mode Noise Suppression	125°c

125°c 125°c max. 150°c 150°c max. 175°c 175°c max. 200°c 200°c max.

Security Camera



1 Signal Processor

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
NFM Series

Thermistors
PRF/NCU Series

MEMS Resonators
WMRAG Series

2 DDR Memory

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Chip Ferrite Beads
BLM Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/
OKL/MYLSM Series

3 Camera Module

Chip Ferrite Beads
BLM Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series

4 Wi-Fi

Wi-Fi Modules

Chip Inductors (Chip Coils)
LQW/LQP/LQG Series

Chip Multilayer LC Filters
LF Series

Chip Multilayer Diplexers
LFD Series

Chip Multilayer Hybrid Baluns
LDB/LDM Series

Chip Multilayer Hybrid Couplers
LDC/LDJ Series

Crystal Units
XRC Series

5 DC-DC Converter

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Power Inductors
LQH/DFE Series

Thermistors
PRF/NCU Series

6 PoE PD (Powered Device)

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Crystal Units
XRC Series

Thermistors
NXRT/PRF/NCU Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series

7 PoE LAN Switch

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Crystal Units
XRC Series

Thermistors
NXRT/PRF/NCU Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series



8 Recorder

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
PRF/NCU Series

9 Sensor

Pyroelectric Infrared Sensors
IRA-S Series

Ultrasonic Sensors
MA40 Series

10 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Coin Manganese Dioxide Lithium Batteries	Standard Type/Heat-resistant Type	Battery Backup

Entrance and Exit Management System



1 CPU

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

2 Display

Ceramic Resonators CERALOCK
CST Series

ESD Protection Devices
LXES Series

Thermistors
NCP/PRF Series

3 RFID Reader/Writer (HF)

Crystal Units
XRC Series

4 RFID Reader/Writer (UHF)

Crystal Units
XRC Series

5 LAN

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

ESD Protection Devices
LXES Series

Thermistors
PRG Series

6 Buzzer

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series



7 Intrusion Detection

Ultrasonic Sensors
MA40 Series

Magnetic Sensors (AMR Sensors)
MR Series

Pyroelectric Infrared Sensors
IRA-S Series

8 DC-DC Converter

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series



Thermistors
NCP/PRF Series

9 Power Supply

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Ceramic Resonators CERALOCK
CST Series

Thermistors
NCP/PRFSeries

10 IC Card

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Air Conditioner



1 Sensor

Ultrasonic Sensors
MA40 Series

Thermistors
NCP/NXR/PRF Series

Magnetic Sensors (AMR Sensors)
MR Series

Pyroelectric Infrared Sensors
IRA-S Series

2 Sterilizing/Deodorizing

Ionizer Modules Ionissimo
MHM300 Series

Ozonizer Modules Ionissimo
MHM500 Series

High Voltage Resistors
MHR Series

3 CPU

Ceramic Resonators
CERALOCK
CST Series

MEMS Resonators
WMRAG Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/
OKL/MYLSM Series

4 Display Panel/Buzzer

Ceramic Resonators CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series



5 Motor Driver

Thermistors
NCP/NXR/PRF Series

6 Power Supply

Chip Multilayer Ceramic Capacitors
for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding
SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc
Ceramic Capacitors for General Purpose
DE1/DE2 Series



Thermistors
PTG Series

7 Remote Controller/Connectivity

Bluetooth Modules

Wi-Fi Modules

LPWA Modules

Microwave Coaxial Connectors with Switch

Crystal Units
XRC Series

Ceramic Resonators CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series



MEMS Resonators
WMRAG Series

8 Inverter/Motor Driver

Ceramic Resonators CERALOCK
CST Series

Thermistors
NCP/NXR/PRF Series

9 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Refrigerator



1 Sensor

Thermistors
NCP/NXR/PRF Series

Magnetic Sensors
(AMR Sensors)
MR Series

Pyroelectric Infrared Sensors
IRA-S Series

Ultrasonic Sensors
MA40 Series

2 Sterilizing/Deodorizing

Ionizer Modules
Ionissimo
MHM300 Series



Ozonizer Modules
Ionissimo
MHM500 Series

High Voltage Resistors
MHR Series

Microblowers



3 Automatic Icemaker

Microblowers



4 CPU

Ceramic Resonators
CERALOCK
CST Series

Non-Isolated
DC-DC Converters
MYMGK/MYSGK/
OKL/MYLSM Series

MEMS Resonators
WMRAG Series

5 Display Panel/Buzzer

Ceramic Resonators CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series



7 Inverter/Motor Driver

Ceramic Resonators
CERALOCK
CST Series

Thermistors
NCP/NXR/PRF Series

6 Connectivity

Bluetooth Modules

Wi-Fi Modules

LPWA Modules

Microwave Coaxial
Connectors with Switch

Crystal Units
XRC Series

MEMS Resonators
WMRAG Series

8 Power Supply

Chip Multilayer
Ceramic Capacitors
for General Purpose
GR/GA Series

Safety Standard Certified Resin
Molding SMD Type Ceramic
Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc
Ceramic Capacitors for General Purpose
DE1/DE2 Series

Thermistors
PTG Series

9 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Washing Machine



1 Sensor

Thermistors
NCP/NXR/PRF Series

Magnetic Sensors
(AMR Sensors)
MR Series

2 CPU

Ceramic Resonators
CERALOCK
CST Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/
OKL/MYLSM Series

MEMS Resonators
WMRAG Series

3 Display Panel/Buzzer

Ceramic Resonators
CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series



4 Inverter/Motor Driver

Thermistors
NCP/NXR/PRF Series

Ceramic Resonators
CERALOCK
CST Series

5 Connectivity

Bluetooth Modules

Wi-Fi Modules

LPWA Modules

Microwave Coaxial Connectors with Switch

Crystal Units
XRC Series

MEMS Resonators
WMRAG Series

6 Power Supply

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Thermistors
PTG Series

7 Sterilizing/Deodorizing

Ozonizer Modules
Ionissimo
MHM500 Series

8 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Coin Manganese Dioxide Lithium Batteries	Standard Type	Battery Backup

Air Purifier



1 Sensor

Ultrasonic Sensors
MA40 Series

Thermistors
NCP/NXR/PRF Series

Magnetic Sensors (AMR Sensors)
MR Series

Pyroelectric Infrared Sensors
IRA-S Series

2 Sterilizing/Deodorizing

Ionizer Modules Ionissimo
MHM300 Series



Ozonizer Modules Ionissimo
MHM500 Series

High Voltage Resistors
MHR Series

7 Inverter/Motor Driver

Thermistors
NCP/NXR/PRF Series

Ceramic Resonators CERALOCK
CST Series

3 CPU

Ceramic Resonators CERALOCK
CST Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/ OKL/MYLSM Series

MEMS Resonators
WMRAG Series

4 Display Panel/Buzzer

Ceramic Resonators CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/ PKM Series

5 Water Pump

Microblowers



6 Connectivity

Bluetooth Modules

Wi-Fi Modules

LPWA Modules

Microwave Coaxial Connectors with Switch

Crystal Units
XRC Series

MEMS Resonators
WMRAG Series

8 Power Supply

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Lead Type DiscCeramic Capacitors for General Purpose
DE1/DE2 Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Thermistors
PTG Series

9 Remote Controller

Ceramic Resonators CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series

10 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Coin Manganese Dioxide Lithium Batteries	Standard Type	Battery Backup

Microwave Oven



1 Sensor

Thermistors
NCP/NXR/PRF Series

Magnetic Sensors (AMR Sensors)
MR Series

2 CPU

Ceramic Resonators CERALOCK
CST Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

MEMS Resonators
WMRAG Series

3 Display Panel/Buzzer

Ceramic Resonators CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series



4 Connectivity

Bluetooth Modules

Wi-Fi Modules

LPWA Modules

Microwave Coaxial Connectors with Switch

Crystal Units
XRC Series

MEMS Resonators
WMRAG Series

5 Motor Driver

Thermistors
NCP/NXR/PRF Series

6 Power Supply

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Thermistors
PTG Series

7 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

IH Rice Cooker



1 Sensor

Thermistors
NCP/NXR/PRF Series

Magnetic Sensors
(AMR Sensors)
MR Series

3 Display Panel/Buzzer

Ceramic Resonators CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series



4 Connectivity

Bluetooth Modules

Wi-Fi Modules

LPWA Modules

Microwave Coaxial
Connectors with Switch

Crystal Units
XRC Series

MEMS Resonators
WMRAG Series

2 CPU

Ceramic Resonators
CERALOCK
CST Series

Non-Isolated
DC-DC Converters
MYMGK/MYSGK/
OKL/MYLSM Series

MEMS Resonators
WMRAG Series

6 Power Supply

Chip Multilayer Ceramic Capacitors
for General Purpose
GR/GA Series

Safety Standard Certified Resin
Molding SMD Type Ceramic
Capacitors for General Purpose
DK1 Series

Safety Standard Certified
Lead Type Disc Ceramic
Capacitors for General Purpose
DE1/DE2 Series

Thermistors
PTG Series

5 Motor Driver

Thermistors
NCP/NXR/PRF Series

7 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Coin Manganese Dioxide Lithium Batteries	Standard Type	Battery Backup

Vacuum Cleaner





1 Sterilizing/Deodorizing

Ionizer Modules Ionissimo
MHM300 Series



High Voltage Resistors
MHR Series

2 CPU

Ceramic Resonators CERALOCK
CST Series

MEMS Resonators
WMRAG Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

3 Display Panel/Buzzer

Ceramic Resonators CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series



4 Sensor

Ultrasonic Sensors
MA40 Series

Thermistors
NCP Series

Magnetic Sensors
(AMR Sensors)
MR Series

5 Connectivity

Bluetooth Modules

Wi-Fi Modules

LPWA Modules

MEMS Resonators
WMRAG Series

Microwave Coaxial Connectors with Switch

Crystal Units
XRC Series

6 Nozzle

Thermistors
PTG Series

7 Motor Driver

Thermistors
NCP/NXP/PRF Series

8 Power Supply

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Thermistors
PTG Series

9 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Tablet Terminators



1 CPU/Chip Set

- Low ESL Chip Multilayer Ceramic Capacitors for General Purpose LLL/LLA/LLM Series
- Polymer Aluminum Electrolytic Capacitors ECAS/ECNS Series
- Crystal Units XRC Series
- Chip Ferrite Beads BLM Series
- 3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose NFM Series
- Thermistors NCP/PRF Series
- Silicon Capacitors
- MEMS Resonators WMRAG Series

2 DDR Memory

- Polymer Aluminum Electrolytic Capacitors ECAS/ECNS Series
- Chip Ferrite Beads BLM Series

3 Display Panel

- Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose KRM Series
- Ceramic Resonators CERALOCK CST Series
- Power Inductors LQH Series
- Thermistors PRF/PRG Series

4 LVDS/eDP

- Chip Common Mode Choke Coils/ Common Mode Noise Filters DLW/DLP/NFP/DLM Series
- ESD Protection Devices LXES Series
- Thermistors NCP/PRF Series

5 HDD/SSD

- Shock Sensors PKGS Series
- Polymer Aluminum Electrolytic Capacitors ECAS/ECNS Series
- Actuators
- Crystal Units XRC Series
- Thermistors NCP/PRF Series

6 USB3.0/USB2.0

- Polymer Aluminum Electrolytic Capacitors ECAS/ECNS Series
- Crystal Units XRC Series
- Chip Common Mode Choke Coils/ Common Mode Noise Filters DLW/DLP/NFP/DLM Series
- Chip Ferrite Beads BLM Series
- ESD Protection Devices LXES Series
- Thermistors PRG Series

7 HDMI/Display Port

- ESD Protection Devices LXES Series
- Crystal Units XRC Series
- Thermistors PRG Series

8 Connectivity

Bluetooth Modules

Wi-Fi Modules

Bluetooth - Wi-Fi Combo Modules

SAW Filters
SAF Series

Chip Multilayer LC Filters
LF Series

Chip Multilayer Hybrid Baluns
LDB/LDM Series

Chip Multilayer Diplexers
LFD Series

Chip Multilayer Hybrid Couplers
LDC/LDJ Series

Microwave Coaxial Cable Connectors/Microwave Coaxial Connectors with Switch

Crystal Units
XRC Series

ESD Protection Devices
LXES Series

MEMS Resonators
WMRAG Series

9 NFC

NFC Antennas
FLAN Series

Crystal Units
XRC Series

Chip Ferrite Beads
BLM Series

Chip Inductors (Chip Coils)
LQW18C/LQM18J Series

Variable Capacitors
LXRW Series

ESD Protection Devices
LXES Series

10 DC-DC Converter

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Chip Multilayer Ceramic Capacitors on Interposer Board for General Purpose
ZRB Series

Thermistors
NCP/PRF Series

11 Battery

Ceramic Resonators CERALOCK
CST Series

Thermistors
NXR/PRF/PRG Series

12 Power Supply

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Ceramic Resonators CERALOCK
CST Series

Thermistors
NCP/PRF Series

13 Clock Device

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

14 HMI/Actuator/Speaker

ESD Protection Devices
LXES Series

15 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Notebook Computers



1 CPU/Chip Set

Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
LLL/LLA/LLM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

Chip Ferrite Beads
BLM Series

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
NFM Series

Thermistors
NCP/PRF Series

Silicon Capacitors

MEMS Resonators
WMRAG Series

2 DDR Memory

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Chip Ferrite Beads
BLM Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/ OKL/MYLSM Series

3 Display Panel

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Ceramic Resonators CERALOCK
CST Series

Power Inductors
LQH Series

Thermistors
PRF/PRG Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

4 LVDS/eDP

ESD Protection Devices
LXES Series

Thermistors
NCP/PRF Series

5 ODD

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCP Series

6 HDD/SSD

Shock Sensors
PKGS Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Actuators

Crystal Units
XRC Series

Thermistors
NCP/PRF Series

Non-IsolatedDC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

7 LAN

Chip Multilayer Ceramic Capacitors for Ethernet LAN and Primary-secondary Coupling of DC-DC converters
GR4 Series

Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP/DLM Series

Crystal Units
XRC Series

8 USB3.0/USB2.0

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

Chip Ferrite Beads
BLM Series

ESD Protection Devices
LXES Series

Thermistors
PRG Series

Non-IsolatedDC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

9 Connectivity

Bluetooth Modules

Wi-Fi Modules

Bluetooth - Wi-Fi Combo Modules

SAW Filters
SAF Series

Chip Multilayer LC Filters
LF Series

Chip Multilayer Hybrid Baluns
LDB/LDM Series

Chip Multilayer Diplexers
LFD Series

Chip Multilayer Hybrid Couplers
LDC/LDJ Series

Microwave Coaxial Cable Connectors
Microwave Coaxial Connectors with Switch

ESD Protection Devices
LXES Series

Crystal Units
XRC Series

MEMS Resonators
WMRAG Series

10 HDMI/Display Port

ESD Protection Devices
LXES Series

Crystal Units
XRC Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Thermistors
PRG Series

11 NFC

NFC Antennas
FLAN Series

Crystal Units
XRC Series

Chip Ferrite Beads
BLM Series

Chip Inductors (Chip Coils)
LQW18C/LQM18J Series

Variable Capacitors
LXRW Series

ESD Protection Devices
LXES Series

12 DC-DC Converter

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Chip Multilayer Ceramic Capacitors on Interposer Board for General Purpose
ZRB Series

Thermistors
NCP/PRF Series

13 Battery

Ceramic Resonators CERALOCK
CST Series

Thermistors
NXR/PRF/PRG Series

14 Power Supply

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Ceramic Resonators CERALOCK
CST Series

Thermistors
NCP/PRF Series

15 HMI/Actuator/Speaker

ESD Protection Devices
LXES Series

16 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Coin Manganese Dioxide Lithium Batteries	Standard Type	Battery Backup

MFP (Multi Function Printer/Product/Peripheral)



1 Image Processor

Isolated DC-DC Converters
MYB Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
LLL/LLA/LLM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

Thermistors
NCP/PRF Series

2 Control Panel

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series



Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP Series

Thermistors
NCP/PRF Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/ OKL/MYLSM Series

Isolated DC-DC Converters for PoE + PD
MYBSP Series

MEMS Resonators
WMRAG Series

3 Scanner

Ultrasonic Sensors
MA300 Series

4 ADF

Accelerometers
SCA Series

Ultrasonic Sensors
MA300 Series

5 Paper Feed Unit & Tray

Magnetic Sensors (AMR Sensors)
MR Series

6 Drum Unit

Thermistors
NCP/PRF Series

7 Polygon Mirror

Accelerometers
SCA Series

8 Laser Unit

Thermistors
NCP/PRF Series

9 Engine Controller

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
PRF/PTG Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

10 Interface

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

Chip Common Mode Choke Coils/
Common Mode Noise Filters
DLW/DLP/NFP/DLM Series

ESD Protection Devices
LXES Series

Thermistors
PRF Series

11 Connectivity

Wi-Fi Modules

NFC Antennas
FLAN Series

Crystal Units
XRC Series

Chip Inductors (Chip Coils)
LQW/LQP/LQG Series

ESD Protection Devices
LXES Series

MEMS Resonators
WMRAG Series

12 Power Supply

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

High Voltage Resistors
MHR Series

Large-current Common Mode Choke Coils
PLT10HH/PLT5BPH/DLW5A/DLW5B/UCMH Series

13 Anti-counterfeit

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Coin Manganese Dioxide Lithium Batteries	Standard Type	Battery Backup

Televisions



1 Tuner

Microchip Transformers (Baluns)
DXP18B Series

Crystal Units
XRC Series

Chip Inductors (Chip Coils)
LQW Series

ESD Protection Devices
LXES Series

2 Signal Processor

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
NFM Series

NFC Antennas
FLAN Series

Thermistors
NCP/PRF Series

MEMS Resonators
WMRAG Series

3 Display Panel

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Chip Multilayer Ceramic Capacitors on Interposer Board for General Purpose
ZRB Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP Series

Power Inductors
LQH Series

Thermistors
NCP/PRF Series

4 Sound Circuit

Chip Common Mode Choke Coils
DLW/DLP Series

5 HDD/DVD/BD

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Thermistors
NCP/PRF Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

6 Interface

Bluetooth Modules

Bluetooth Smart Modules

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Ceramic Resonators CERALOCK
CST Series

Crystal Units
XRC Series

Chip Common Mode Choke Coils/
Common Mode Noise Filters
DLW/DLP/NFP/DLM Series

ESD Protection Devices
LXES Series

Thermistors
PRG Series

7 Control Circuit

Bluetooth Modules

Ceramic Resonators CERALOCK
CST Series

8 Remote Controller/Connectivity

Bluetooth Modules

Wi-Fi Modules

Bluetooth Smart Modules

MEMS Resonators
WMRAG Series

Ceramic Resonators CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series



ESD Protection Devices
LXES Series

Crystal Units
XRC Series

Chip Inductors (Chip Coils)
LQW/LQP/LQG/LQB Series

9 DC-DC Converter

Metal Terminal Type Multilayer Ceramic Capacitors
for General Purpose
KRM Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Power Inductors
LQH Series

Thermistors
NCP/PRF Series

10 Power Supply

Chip Multilayer Ceramic
Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin
Molding SMD Type Ceramic
Capacitors for General Purpose
DK1 Series

Safety Standard Certified
Lead Type Disc Ceramic
Capacitors for General Purpose
DE1/DE2 Series

Thermistors
NCP/PRF/PTG Series

11 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression

Set-top Box



1 Tuner

Crystal Units
XRC Series

Chip Inductors (Chip Coils)
LQW Series

ESD Protection Devices
LXES Series

Microchip Transformers (Baluns)
DXP18B Series

2 Signal Processor

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose
NFM Series

MEMS Resonators
WMRAG Series

3 Sound Circuit

Chip Common Mode Choke Coils
DLW/DLP Series

4 HDD/SSD

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

Thermistors
NCP/PRF Series

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

5 EoC (MoCA)

Chip Multilayer Hybrid Baluns
LDB/LDM Series

Chip Multilayer LC Filters
LF Series

Crystal Units
XRC Series

6 Interface

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Crystal Units
XRC Series

Chip Common Mode Choke Coils/ Common Mode Noise Filters
DLW/DLP/NFP/DLM Series

ESD Protection Devices
LXES Series

Thermistors
PRG Series

7 Connectivity

Wi-Fi Modules

Microwave Coaxial Connectors with Switch

Crystal Units
XRC Series

ESD Protection Devices
LXES Series

8 DC-DC Converter

Non-Isolated DC-DC Converters
MYMGK/MYSGK/OKL/MYLSM Series

Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose
KRM Series

Chip Multilayer Ceramic Capacitors on Interposer Board for General Purpose
ZRB Series

Polymer Aluminum Electrolytic Capacitors
ECAS/ECNS Series

Power Inductors
LQH/DFE Series

Thermistors
NCP/PRF Series

9 Power Supply

Chip Multilayer Ceramic Capacitors for General Purpose
GR/GA Series

Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose
DK1 Series

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose
DE1/DE2 Series

Thermistors
NCP/PRF/PTG Series

10 Remote Controller

Crystal Units
XRC Series

Ceramic Resonators CERALOCK
CST Series

Piezoelectric Sounders
PKMCS/PKLCS/PKM Series



11 Traceability

RFID Tag
LXMS/LXTB Series

General Purpose

Chip Multilayer Ceramic Capacitors for General Purpose	GRM Series	High Frequency Filter Circuit/Coupling/Decoupling/For Step-up
High Q Chip Multilayer Ceramic Capacitors for General Purpose	GJM Series	High Frequency Filter Circuit
Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	GRJ Series	Coupling/Decoupling/For Step-up
3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	NFM Series	Noise Suppression
Polymer Aluminum Electrolytic Capacitors	ECAS/ECNS Series	Smoothing/Transient Backup
Chip Inductors (Chip Coils)	LQW/LQP/LQG Series	High Frequency Circuit-Impedance Matching/Resonance
Chip Inductors (Chip Coils)	LQM/LQH/DFE Series	Voltage Conversion
Chip Ferrite Beads	BLM/NFZ Series	Noise Suppression
Feed Through Chip EMI Filters	NFE Series	Noise Suppression
Chip Common Mode Choke Coils/Common Mode Noise Filters	DLW/DLP/NFP Series	Noise Suppression
Coin Manganese Dioxide Lithium Batteries	Standard Type	Battery Backup

SimSurfing

The best partner for your circuit design







SimSurfing is a web application which allows circuit designers to see our components' characteristics data, and to select the one that best suits the requirement.

View and download data
You can see various characteristics graphs for our products with easy operation, or download data files including s-parameter, spice models, etc.

Simulate circuit conditions
Simsurfing includes advanced equivalent circuit models which show the characteristics data close to actual measurement (for some components including MLCC & RF inductors).

Compare characteristics
Easily compare characteristics data on the same graph.

For more information about SimSurfing visit
www.murata.com/tool/simsurfing

or visit the SimSurfing site directly at
ds.murata.co.jp/simsurfing/?lcid=en-us

muRata
INNOVATOR IN ELECTRONICS

K70E.pdf
Dec.12,2019

Index

B	B4F	Baluns	71
	B5F	Baluns	71
	BL0	Noise Suppression Filters (Lead Type)	47
	BLA	Noise Suppression Filters (Chip Ferrite Bead)	41
	BLE	Noise Suppression Filters (Chip Ferrite Bead)	42
	BLF	Noise Suppression Filters (Chip Ferrite Bead)	43
	BLL	Noise Suppression Filters (Lead Type)	47
	BLM	Noise Suppression Filters (Chip Ferrite Bead)	41
	BLT	Noise Suppression Filters (Chip Ferrite Bead)	43
	BN	Noise Suppression Filters (Block Type)	46
C	CD	Ceramic Discriminators	67
	CL	Single-Layer Microchip Capacitors	30
	CR	Coin Manganese Dioxide Lithium Batteries	91
	CS	Ceramic Resonators CERALOCK	65
D	D5	Inductors (Coils)	52
	D6	Inductors (Coils)	52
	DE1	Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose / IEC60384-14 Class X1/Y1	24
	DE2	Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose / IEC60384-14 Class X1/Y2	25
	DE6	Safety Standard Certified Lead Type Disc Ceramic Capacitors for Automotive	28
	DEM	Inductors (Coils)	51
	DFE	Inductors (Coils)	50
	DG	Inductors (Coils)	52
	DK1	Safety Standard Certified Resin Molding SMD Type Ceramic Capacitors for General Purpose	28
	DL	Noise Suppression Filters (Chip Common Mode Choke Coil)	45
	DS	Noise Suppression Filters (Lead Type)	47
	DS1	Inductors (Coils)	53
	DS7	Inductors (Coils)	52
	DXP	Baluns	71
	DXW	Baluns	71
E	ECAS	Polymer Aluminum Electrolytic Capacitors	29
	ECNS	Polymer Aluminum Electrolytic Capacitors	29
F	FC	Inductors (Coils)	52
	FD	Inductors (Coils)	52
	FHA	Film Capacitors	40
	FSDVA	Inductors (Coils)	60
G	GA2	Based on the Electrical Appliance and Material Safety Law of Japan Chip Multilayer Ceramic Capacitors for General Purpose	10
	GA3	Safety Standard Certified Chip Multilayer Ceramic Capacitors for General Purpose	10
	GC3	High Effective Capacitance & High Ripple Current Chip Multilayer Ceramic Capacitors for Automotive	17
	GCD	MLSC Design Chip Multilayer Ceramic Capacitors for Automotive	18
	GCE	Soft Termination MLSC Design Chip Multilayer Ceramic Capacitors for Automotive	18
	GCG	AgPd Termination Conductive Glue Mounting Chip Multilayer Ceramic Capacitors for Automotive	20
	GCH	Chip Multilayer Ceramic Capacitors for Implantable Medical devices (Non Life support circuit)	21
G	GCJ	Soft Termination Chip Multilayer Ceramic Capacitors for Automotive	17
	GCM	Chip Multilayer Ceramic Capacitors for Automotive	15
	GCQ	High Q Chip Multilayer Ceramic Capacitors for Automotive	18
	GJM	High Q Chip Multilayer Ceramic Capacitors for General Purpose	9
	GMA	Wire Bonding Mount Multilayer Microchip Capacitors for General Purpose	13
	GMD	Wire Bonding/AuSn Soldering Mount Chip Multilayer Ceramic Capacitors for General Purpose	14
	GQM	High Q and High Power Chip Multilayer Ceramic Capacitors for General Purpose	9
	GR3	High Effective Capacitance & High Ripple Current Chip Multilayer Ceramic Capacitors for General Purpose	8
	GR4	Chip Multilayer Ceramic Capacitors for Ethernet LAN and primary-secondary coupling of DC-DC converters	9
	GR4	Chip Multilayer Ceramic Capacitors for Splitter Circuit of G-Fast, xDSL	9
	GRJ	Soft Termination Chip Multilayer Ceramic Capacitors for General Purpose	8
	GRM	Chip Multilayer Ceramic Capacitors for General Purpose	6
	GRM	Chip Multilayer Ceramic Capacitors for LCD Backlight Inverter Circuit only	8
	GRT	AEC-Q200 Compliant Chip Multilayer Ceramic Capacitors for Infotainment	14
I	IJ	Li-ion Energy Storage System	88
	IR	Pyroelectric Infrared Sensors	78
K	KC3	High Effective Capacitance & High Allowable Ripple Current Metal Terminal Type Multilayer Ceramic Capacitors for Automotive	19
	KCA	Safety Standard Certified Metal Terminal Type Multilayer Ceramic Capacitors for Automotive	20
	KCM	Metal Terminal Type Multilayer Ceramic Capacitors for Automotive	19
	KR3	High Effective Capacitance & High Allowable Ripple Current Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose	13
	KRM	Metal Terminal Type Multilayer Ceramic Capacitors for General Purpose	13
L	LDB	Baluns	71
	LDC	Couplers	72
	LDD	Chip Multilayer Hybrid Dividers	72
	LDJ	Couplers	72
	LDM	Baluns	71
	LFB	Chip Multilayer LC Filters	69
	LFD	Chip Multilayer Diplexers	72
	LFL	Chip Multilayer LC Filters	69
	LLA	8 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	11
	LLL	LW Reversed Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	11
	LLM	10 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	12
	LLR	LW Reversed Controlled ESR Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	12
	LQ	Inductors (Coils)	50, 57, 59
	LR	Alkaline Manganese Batteries	95
	LXMS	RFID tag	102
	LXRW	Variable Capacitors	34
	LXTB	RFID tag	102
M	MA	Ultrasonic Sensors	78
	MHM	Ionizer Modules Ionissimo	100
	MHM	Ozonizer Modules Ionissimo	101
	MHR	High Voltage Resistors	62
	MM	Microwave Coaxial Connectors (Receptacle)	73
	MPD	DC-DC Converters	87
	MPL	High Voltage Power Supplies	87
	MR	AMR Sensors (Magnetic Sensors)	78
	MX	Microwave Coaxial Connectors (Cable)	74
	MY	DC-DC Converters	85
	MZB	Microblowers	99
N	NC	NTC Thermistors	78, 80
	NF	Noise Suppression Filters (Feed Through Chip EMI Filters), (Chip LC Filters),(Chip EMIFIL), (Chip Common Mode Noise Filters)	43, 44, 45
	NFM	3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for General Purpose	12
	NFM	3 Terminals Low ESL Chip Multilayer Ceramic Capacitors for Automotive	19
	NX	NTC Thermistors	78, 81
O	OK	DC-DC Converters	85
P	PKB	Piezoelectric Buzzers	97
	PKG	Shock Sensors	78
	PKL	Piezoelectric Sounders	96
	PKM	Piezoelectric Sounders	96, 97
	PLT	Noise Suppression Filters (Common Mode Choke Coil)	46, 47
	PR	PTC Thermistors POSISTOR	78, 82, 83
	PT	PTC Thermistors POSISTOR	78, 82, 83, 84
R	RCE	Leaded MLCC for Automotive	26
	RDE	Leaded MLCC for General Purpose	22
	RHE	150°C Operation Leaded MLCC for Automotive	27
	RHS	175°C/200°C Operation Leaded MLCC for Automotive	28
	RU	Thin Film Circuit Substrates (RUSUB)	32
S	SA3	Antenna Coils	70
	SAF	SAW Filters for Mobile Communications	68
	SAW	SAW Filters for Mobile Communications	68
	SAY	SAW Filters for Mobile Communications	68
	SCA	Accelerometers	78
	SCA	Inclinometers	78
	SCC	Gyro Sensors	78
	SCR	Gyro Sensors	78
	SF	Ceramic Filters CERAFIL	67
	SR	Silver Oxide Batteries	94
T	TD	Dielectric Filters GIGAFIL	69
U	UCMH	Noise Suppression Filters (Chip Common Mode Choke Coil)	46
V	VF	EMIGUARD	47
W	WM	MEMS Resonator	64
X	XD	Crystal Filters	68
	XR	Crystal Units	64
	XT	Crystal Oscillators	65
	5CCEG	Inductors (Coils)	60
	7B	Piezoelectric Diaphragms	97
	935*	Silicon Capacitors	34
	939*	Silicon Capacitors	34

Global Locations

For details please visit www.murata.com

⚠Note

1 Export Control

For customers outside Japan:

No Murata products should be used or sold, through any channels, for use in the design, development, production, utilization, maintenance or operation of, or otherwise contribution to (1) any weapons (Weapons of Mass Destruction [nuclear, chemical or biological weapons or missiles] or conventional weapons) or (2) goods or systems specially designed or intended for military end-use or utilization by military end-users.

For customers in Japan:

For products which are controlled items subject to the "Foreign Exchange and Foreign Trade Law" of Japan, the export license specified by the law is required for export.

2 Please contact our sales representatives or product engineers before using the products in this catalog for the applications listed below, which require especially high reliability for the prevention of defects which might directly damage a third party's life, body or property, or when one of our products is intended for use in applications other than those specified in this catalog.

1. *Aircraft equipment*
2. *Aerospace equipment*
3. *Undersea equipment*
4. *Power plant equipment*
5. *Medical equipment*
6. *Transportation equipment (vehicles, trains, ships, etc.)*
7. *Traffic signal equipment*
8. *Disaster prevention / crime prevention equipment*
9. *Data-processing equipment*
10. *Application of similar complexity and/or reliability requirements to the applications listed above*

3 Product specifications in this catalog are as of September 2019. They are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. If there are any questions, please contact our sales representatives or product engineers.

4 Please read rating and ⚠CAUTION (for storage, operating, rating, soldering, mounting and handling) in this catalog to prevent smoking and/or burning, etc.

5 This catalog has only typical specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

6 Please note that unless otherwise specified, we shall assume no responsibility whatsoever for any conflict or dispute that may occur in connection with the effect of our and/or a third party's intellectual property rights and other related rights in consideration of your use of our products and/or information described or contained in our catalogs. In this connection, no representation shall be made to the effect that any third parties are authorized to use the rights mentioned above under licenses without our consent.

7 No ozone depleting substances (ODS) under the Montreal Protocol are used in our manufacturing process.

Murata Manufacturing Co., Ltd.

www.murata.com

muRata
INNOVATOR IN ELECTRONICS

K70E.pdf
Dec.12,2019